

# Machine building

## Customer case study



## Instant customer service over a secure connection: Reliable remote access with wireless and security devices

### Summary

- Paper Converting Machine Company's existing remote communication solution was expensive and had limited functionality
- PCMC switched to Phoenix Contact's FL mGuard security devices for more reliable communication with machines around the world
- In addition, FL WLAN 5101 wireless Ethernet radios serve as wireless access points, providing a connection for a customer's industrial handheld tablet device
- The new system saves PCMC and its customers time and money while ensuring instant customer service over a secure connection

“We frequently can solve customers' issues immediately, especially if it is a new customer with a piece of equipment that they may not yet be completely familiar with.”

**Todd Lemke, Electrical Project Engineer at PCMC**

### Customer profile

Paper Converting Machine Company ([www.pcmc.com](http://www.pcmc.com)) in Green Bay, Wisconsin, builds machinery for a variety of industries, including tissue converting and packaging, flexographic printing, and nonwovens. With three major production centers in the U.S., the UK, and Italy, and more than a thousand team members worldwide, PCMC sells and services its machines installed at customers' manufacturing facilities across the globe.

### Challenge: Remote communication required expensive software

Originally, PCMC used Phoenix Contact managed Ethernet switches and a wireless WLAN basic radio for remote connectivity, but this proprietary system had limited functionality. In this system, PCMC sold each customer a PC that had all the software required to diagnose and maintain the machinery, and PCMC would remotely access that PC

when needed. Because it required the purchase and installation of a PC and remote access software, this system was expensive.

PCMC wanted a way to provide better remote maintenance and have the ability to troubleshoot customers' machines in a less expensive, more reliable, and more secure way.



**Figure 1: Phoenix Contact communications make it possible for a local operator to control this Aquaflex web printer from a handheld device and for engineers at PCMC to access the automation system remotely.**

## Solution: Fast wiring without tools

PCMC installed a Phoenix Contact mGuard RS2000 security appliance on each machine and an mGuard RS4000 system at PCMC's office in Green Bay, Wisconsin. The mGuard system in Green Bay accesses any remote mGuard router via a secure VPN connection.

This hardware-based solution provides a number of advantages over the prior software-based PC platform, as summarized in Table 1 and as detailed below. Loading software onto a general-purpose platform like an office-grade PC creates a software-based remote access solution that works well in many applications, but typically not as well as a specially designed and industrially rated hardware-based remote access solution like the mGuard.

Table 1: **Advantages of Hardware-Based Remote Access**

1. More secure
2. Resistant to tampering
3. Easier to use
4. Less expensive, as no PC is required
5. Requires no software to be loaded at remote PC
6. Doesn't require periodic software updates
7. Industrially hardened, unlike an office-grade PC
8. Provides consistent remote access methodology

"With more and more devices on Ethernet and the mGuard's ability to do network address translations, we are able to translate the machine's network to a PCMC network. This allows us to sit at our desks and connect to the machine as if we were sitting at the machine connected to its network," explains Todd Lemke, Electrical Project Engineer at PCMC.

"It also eliminated the possibility of the remote PC not functioning properly, or sometimes not being able to find it if it was a laptop. And we are able to save the additional cost of the previous remote PC and software," adds Lemke.

A PC used for remote access often needs to be industrially hardened, which can add to the costs. PCMC used a standard desktop PC to keep costs down, but office PCs are not designed for the harsh conditions typically found on the factory floor, such as electrical noise.

Another option is a laptop, but keeping track of the laptop can be a challenge. In addition, a laptop or PC can pose a security risk if different software programs are added.

To minimize the possibility, PCMC typically placed its PC in a cabinet without a monitor, keyboard or mouse to prevent the

customer from accidentally compromising it. Still, when remote access was needed, the PC or laptop had to be set up before it could be used.

The mGuard solution addressed all of these issues, as it was hardware-based instead of software-based. PCMC engineers can now access any machine from anywhere in the world from their desks at work without any additional log-in or configuration steps

(Figure 2). They no longer have to ask the customer to set up the PC so they can get online.



**Figure 2: Any PCMC engineer or technician anywhere in the world can access the automation system on a customer's machine over a secure connection.**

"Any person that is on the PCMC network has the ability to access any machine as long as they know the IP address assigned to that customer within the mGuard system," says Lemke. "An engineer can also be sitting in the airport or any other remote location with an Internet connection, VPN into the PCMC network, and use mGuard to access a machine anywhere in the world."

The mGuard router provides the secure connection that PCMC needs by encrypting the network traffic and password, protecting all data that passes through the device. This protects any information passing over the remote connection as it transmits from one point to another.

The FL WLAN 5101, one of the newest versions of Phoenix Contact's wireless Ethernet radios, is installed on Fusion press machines and is used as a wireless access point, providing a connection for a customer's industrial handheld tablet device. An operator can use this tablet or laptop to control the machine from any nearby location (Figure 3). "We are using a handheld Windows Mobile device that has an HMI on it that was created by PCMC," explains Lemke. "It's used as an HMI to control the machine."

The mGuard and the radio operate on the same network so that PCMC engineers have remote access to all Ethernet-capable devices on the machine. This includes all of the key components of the automation system, including the HMI and the controller.



**Figure 3: With a Phoenix Contact wireless radio installed in the machine, an operator can use a tablet or laptop to control the machine from any nearby location.**

### mGuard versus PCs

The printing machinery industry, like many others, is rapidly moving to remote access for all the advantages noted above,

such as remote diagnostics, software downloads, and so on. PCMC was one of the pioneers of remote access in printing machinery, but as its competitors were catching up, it needed a better system—something that would be superior to all the other PC-based remote access systems used by its competitors.

“One thing the new system allows us to do that the old system did not is load firmware to certain devices from a remote location without an additional PC on the machine,” says Lemke. “This is due to allowing passive FTP to the devices.” But the mGuard system provides many more advantages over PC-based remote access, as shown in Table 2.

### Results: Remote access pays off

“We frequently can solve customers’ issues immediately, especially if it is a new customer with a piece of equipment that they may not yet be completely familiar with,” says Lemke. “It is not uncommon to get a call from the customer stating a problem, and by simply using the mGuard to access the machine’s operator station, we can look at the message screen, evaluate the situation, and point them in the right direction to get the machine back into production.”

PCMC can also go online with the machine’s PLC or other Ethernet-based controller and make modifications to the controller program that the customer may be requesting as a “special feature” different from the base machine design.

“This saves PCMC and our customers time and money,” adds Lemke. “We can have them on the phone, add the feature, get them to try it, give us immediate feedback, and modify as required. This process would take days if we did not have remote

access, and it would require a person to be at the facility to load the changes into the controller.”

PCMC engineers can also download new firmware, HMI applications, programs, and documentation using the mGuard remote access system.

PCMC is happy with mGuard and the wireless radio. “We install mGuard routers on the majority of PCMC machines we currently build,” says Lemke. “We also went back and installed it on some of our legacy equipment.”

Machines with mGuard routers as standard include PCMC’s Fusion and ELS-Max flexographic printing presses for printing, coating, and laminating; Clipper Flat Pack and Marlin cross-fold wet wipe machines for non wovens; and Forte and Centrum rewinders for tissue converting. “All of these machines currently use mGuard routers for remote connectivity for diagnostics and maintenance,” notes Lemke.

“Having a remote connectivity solution that meets both our and our customers’ security needs has greatly increased our support capabilities and the machine availability for our customers,” says Lemke. “Machine lines are seamlessly accessible when support is required, which means we can access a pool of our technicians and engineers, each of whom can very quickly dive in and assist in troubleshooting without having to travel.”

Lemke said this type of response is very important in a modern automation system: “As integrated diagnostic tools in the automation systems continue to advance, the ability to remotely access machines will grow in importance to meet the demands of our customers.”

**Table 2: mGuard versus PC-Based Remote Access**

Feature	mGuard	PC-based remote access	Comments
Passive FTP	YES – 1:1 NAT	NO – port mapping	FTP for FT, MLC and file transfer
Discrete enable	YES	NO	Customer control of connection
Power	24 VDC	120 VAC	DC power has higher availability
Mounting	DIN rail	shelf	Convenience and cost
Default gateway required	NO	YES	Per-node setup time savings and component swapping
Optional anti-malware	YES	NO	Saves time and money
IP Masquerade	YES	NO	Invisible access to the Internet
Query list	YES	NO	Automatically generates list of customers
E-mail from machine	YES – rules	NO	Built in to mGuard
Security	YES – rules	YES – 128-bit AES	More flexibility
Requires a certificate	YES – per client	NO	More secure
Connections per server	250	50	Hardware and maintenance savings
Preferred by PCMC IT	YES	NO	Easier to manage within infrastructure