

1209364

https://www.phoenixcontact.com/us/products/1209364

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail housing, 10U upper part, integrated 2.4" resistive touch display, resolution: 320 x 240 Pi xel(s), interface: 4-wire SPI half duplex, Housing cover, width: 56.88 mm, height: 109.8 mm, depth: 29.5 mm, color: light grey (7035)

Your advantages

- · Housing system for visualization and operation in the control cabinet
- · Coordinated housings with pre-installed touch displays
- · Time-saving assembly of ready-to-use modules
- · Can be machined for application-specific connection technology

Commercial data

Item number	1209364
Packing unit	1 pc
Minimum order quantity	12 pc
Sales key	AC15
Product key	ACHEBI
GTIN	4063151280352
Weight per piece (including packing)	58.366 g
Weight per piece (excluding packing)	43.98 g
Customs tariff number	85480090
Country of origin	CN



1209364

https://www.phoenixcontact.com/us/products/1209364

Set consists of

DCT T 2,4 QVGA S RTOUCH - Display

1132710

https://www.phoenixcontact.com/us/products/1132710

Resistive touch display, 2.4", resolution: 320 x 240 pixels, interface: SPI, contrast ratio: 500:1, aspect ratio: 3:4, interface: "4-wire SPI half duplex, Glue and Play solution", suitable for polyamide and polycarbonate





Refer to the data sheet for the range in the download area.

1209364

https://www.phoenixcontact.com/us/products/1209364

Technical data

General

Notes

Product properties		
Product type	Upper housing part	
Туре	10U upper part, integrated 2.4" resistive touch display	
Housing type	DIN rail housing	
Ventilation openings present	no	
Housing series	ME-IO	

Display

Bisplay	
Display type	Color display TFT
Diagonal	(Display)
	2.4 in. / 6.9 cm (Display)
Screen resolution	320 x 240 Pixel(s) (QVGA)
Display formats	4:3
Display lighting type	LED, white
Controller	ST7789V

Interfaces

|--|

Dimensions

Width	56.88 mm
Height	109.8 mm
Depth	29.5 mm

Material specifications

Color	light grey (7035)
Flammability rating according to UL 94	V0
CTI according to IEC 60112	600
Housing material	Polyamide

Environmental and real-life conditions

Vibration test

Specification	IEC 60068-2-6:2007-12
Result	Test passed
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.15 mm (10 Hz 58.1 Hz)



1209364

https://www.phoenixcontact.com/us/products/1209364


Acceleration	20 m/s²
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis
Shocks	
Specification	IEC 60068-2-27:2008-02
Result	Test passed
Acceleration	150 m/s²
Shock duration	11 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Test for substances that would hinder coating with paint or v	varnish
Specification	VDMA 24364:2018-05
Result	Test passed
Ambient conditions	
Max. IP code to attain	IP20
Ambient temperature (operation)	-20 °C 70 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-20 °C 55 °C
Ambient temperature (assembly)	-5 °C 70 °C
Relative humidity (storage/transport)	80 %
ounting	
Mounting type	Snap in
Mounting position	Vertical (horizontal DIN rail)
ackaging specifications	
Type of packaging	packed in cardboard
Outer packaging type	Carton



1209364

https://www.phoenixcontact.com/us/products/1209364

Drawings



Schematic figure for illustrating the item dimensions. The figure is not of the desired product. For further details, refer to the product drawings in the "Downloads" tab.



1209364

https://www.phoenixcontact.com/us/products/1209364

Classifications

ECLASS

	ECLASS-11.0	27182702
	ECLASS-13.0	27190605
ETIM		
	ETIM 9.0	EC001031
UNSPSC		
	UNSPSC 21.0	31261500



1209364

https://www.phoenixcontact.com/us/products/1209364

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com