

EB 2-31/UKH - Insertion bridge

0201388

<https://www.phoenixcontact.com/gb/products/0201388>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Insertion bridge, pitch: 31 mm, number of positions: 2, color: gray

Commercial data

Item number	0201388
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE1Z2X
Product key	BE1Z2X
GTIN	4017918098568
Weight per piece (including packing)	126.87 g
Weight per piece (excluding packing)	126.87 g
Customs tariff number	85366990
Country of origin	DE

Technical data

Product properties

Product type	Insertion bridge
Number of positions	2
Pitch	31 mm

Dimensions

Pitch	31 mm
-------	-------

Material specifications

Color	gray (RAL 7042)
Material	Copper
Insulating material	PVC

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	Screw mounting
---------------	----------------

EB 2-31/UKH - Insertion bridge



0201388

<https://www.phoenixcontact.com/gb/products/0201388>

Classifications

ECLASS

ECLASS-13.0	27250303
ECLASS-15.0	27250303

ETIM

ETIM 10.0	EC000489
-----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

EF3.1 Climate Change

CO2e kg	0.332 kg CO2e
---------	---------------