PHT22-FLD-GN/PT10/GN - Button

1108273

https://www.phoenixcontact.com/gb/products/1108273

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Illuminated flat button, 22 mm, circular, green, self-locking, including a button head, module holder, a N/O contact module using push-in connection technology and a LED module

Your advantages

- 22 mm illuminated button set with Push-in connection
- Self-retaining (latching) – ideal for switching functions
- Depending on the set variant, incl. contact module(s) (N/O / N/C, 1- or 2-way) + 1 LED module – flexible in use
- With integrated lighting option for clear status display
- Quick mounting in the control cabinet/control panel

Commercial data

Item number	1108273
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BE6122
Product key	BE6122
GTIN	4063151012908
Weight per piece (including packing)	48 g
Weight per piece (excluding packing)	45.2 g
Country of origin	CN

Technical data

Product properties

Product type	Actuator
Actuator type	Illuminated flat button
Function	Self-locking type
Extension of optional light source	Yes
Color (LED)	green (6021)
Type of light source	LED
with light source	Yes
Number of contacts as N/O contacts	1
Number of contacts as N/C contacts	0

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	5 W
LED voltage range	24 V ... 240 V ±10 % (AC/DC 50/60 Hz (AC))
Rated operating current (AC-15)	120 V 8 A
	230 V 6 A
	400 V 4 A
	600 V 2 A
Rated operating current (DC-13)	24 V 5 A
	110 V 1.1 A
	220 V 0.5 A

Input data

LED voltage range	24 V ... 240 V ±10 % (AC/DC 50/60 Hz (AC))

Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross-section rigid	0.5 mm² ... 2.5 mm²
Conductor cross-section flexible	0.5 mm² ... 1.5 mm²
Conductor cross-section, flexible [AWG]	20 ... 16 (converted acc. to IEC)
2 conductors with same cross section, rigid	0.5 mm² ... 2.5 mm²
2 conductors with the same cross-section AWG rigid	20 ... 16 (converted acc. to IEC)
2 conductors with same cross section, flexible	0.5 mm² ... 1.5 mm²
2 conductors with the same cross-section AWG flexible	20 ... 16 (converted acc. to IEC)
2 conductors with the same cross section, flexible, with ferrule with plastic sleeve	0.5 mm² ... 1.5 mm²

Thermal continuous current I_{th}	10 A
Rated insulation voltage	600 V
Operating voltage range (AC/DC)	5 V ... 600 V

Dimensions

Width	30 mm
Height	46 mm
Depth Installation	47.9 mm
Diameter Mounting	22.3 mm

Material specifications

Color	green
Contact material	AgNi10
Front ring material	Metal
Front ring color	silver

Environmental and real-life conditions

Oscillation/broadband noise

Specification	IEC 61373:2010-05
Spectrum	Long life test category 1, class B, body mounted
Frequency	5 Hz ... 150 Hz
Acceleration	0.6 g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Pulse shape	Half-sine
Acceleration	50g
Shock duration	11 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis
Result	Test passed

Degree of protection (IP code)

Degree of protection	IP66

Ambient conditions

Degree of protection (Connection terminal blocks)	IP20
Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	-30 °C ... 85 °C
Permissible humidity (operation)	≤ 95 % ((room temperature 25°C) no condensation)

Standards and regulations

	IEC 60947-5-1

Standards/specifications	GB 14048.5
	UL 60947-5-1

Mounting

Mounting type	Panel mount
Tightening torque	1 Nm ... 1.2 Nm

Drawings

Circuit diagram



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1108273

cULus Listed
Approval ID: E172140

CCC
Approval ID: 2024010305697836

TÜV Rheinland
Approval ID: R CN21G3UE 001

Classifications

ECLASS

ECLASS-15.0	27371228
ECLASS-13.0	27371228

ETIM

ETIM 10.0	EC001028

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk