
# TTC-6-1X2-M-EX-24DC-UT-I - Surge protection device

2906820

https://www.phoenixcontact.com/gb/products/2906820

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Surge protection with integrated status indicator and disconnect knife for one 2-wire floating Ex i signal circuit, e.g., 0(4) ... 20 mA current loop, HART-compatible. Can be used in safety-related circuits up to SIL 3.

## Your advantages

- Space-saving and cost-saving with a narrow overall width of just 6 mm
- Continuous monitoring of protective devices, plus mechanical status indicator with optional remote signaling
- Finding the right product for all possible requirements in MCR applications is easy, thanks to the complete range of products with customized features
- Signal circuits easily interrupted for maintenance work, thanks to vertical knife disconnection

## Commercial data

| | |
|---|---|
| Item number | 2906820 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | CL2263 |
| Product key | CL2263 |
| GTIN | 4055626135830 |
| Weight per piece (including packing) | 63.3 g |
| Weight per piece (excluding packing) | 63.1 g |
| Customs tariff number | 85363010 |
| Country of origin | DE |

# Technical data

## Product properties

| | |
|---|---|
| Product type | Surge protection for MCR technology |
| Product family | TERMITRAB complete |
| IEC test classification | C1 |
| | C2 |
| | C3 |
| | D1 |
| Type | DIN rail module, one-piece |
| Wire pairs per module | 1 |

Insulation characteristics

| | |
|---|---|
| Overvoltage category | III |
| Pollution degree | 2 |

## Electrical properties

| | |
|---|---|
| Nominal voltage $U_N$ | 24 V DC |


## Connection data

| | |
|---|---|
| Connection method | Screw connection |
| Screw thread | M3 |
| Tightening torque | 0.5 Nm ... 0.6 Nm |
| Conductor cross-section flexible | 0.2 mm² ... 2.5 mm² |
| Conductor cross-section rigid | 0.2 mm² ... 4 mm² |
| Conductor cross-section AWG | 24 ... 12 |

## Ex data

| | |
|---|---|
| Maximum inner capacitance $C_i$ | negligible |
| Max. internal inductance $L_i$ | negligible |
| Max. input current $I_i$ | 400 mA (T4 / -40 °C ... +50 °C) |
| | 250 mA (T4 / -40 °C ... +70 °C) |
| | 350 mA (T6 / -40 °C ... +35 °C) |
| | 100 mA (T6 / -40 °C ... +70 °C) |
| Max. input voltage $U_i$ | 30 V DC |
| Insulation voltage to ground | > 180 V DC |
| Ambient temperature (operation) | -40 °C ... 70 °C (with current derating) |

## Dimensions

| | |
|---|---|
| Dimensional drawing |   |
| Width | 6.2 mm +0.1 mm |
| Height | 105.8 mm |
| Depth | 83.5 mm (incl. DIN rail 7.5 mm) |

## Material specifications

| | |
|---|---|
| Color | blue (RAL 5015) |
| Flammability rating according to UL 94 | V-0 |
| Insulating material | PBT |
| Housing material | PBT |

## Mechanical properties

Mechanical data

| | |
|---|---|
| Open side panel | No |

## Protective circuit

| | |
|---|---|
| Direction of action | Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground |
| Nominal voltage $U_N$ | 24 V DC |
| Maximum continuous operating voltage $U_C$ | 30 V DC |
| Rated current | 600 mA (40 °C) |
| Operating effective current $I_C$ at $U_C$ | ≤ 5 µA |
| Protective conductor current $I_{PE}$ | ≤ 1 µA |
| Nominal discharge current $I_n$ (8/20) µs (line-line) | 5 kA |
| Nominal discharge current $I_n$ (8/20) µs (line-ground) | 5 kA |
| Pulse discharge current $I_{imp}$ (10/350) µs (line-line) | 0.5 kA |
| Pulse discharge current $I_{imp}$ (10/350) µs (line-earth) | 0.5 kA |
| Total discharge current $I_{Total}$ (8/20) µs | 10 kA |
| Voltage protection level $U_p$ (line-line) | ≤ 55 V (C1 - 1 kV / 500 A) |
| | ≤ 65 V (C2 - 10 kV / 5 kA) |
| | ≤ 55 V (C3 - 100 A) |
| Voltage protection level $U_p$ (line-earth) | ≤ 900 V (C1 - 1 kV / 500 A) |
| | ≤ 1.05 kV (C2 - 10 kV / 5 kA) |
| | ≤ 1.4 kV (C3 - 100 A) |
| Voltage protection level $U_p$ static (line-line) | ≤ 50 V (C1 - 1 kV / 500 A) |
| | ≤ 65 V (C2 - 10 kV / 5 kA) |
| Voltage protection level $U_p$ static (line-earth) | ≤ 900 V (C1 - 1 kV / 500 A) |
| | ≤ 1.05 kV (C2 - 10 kV / 5 kA) |
| Response time $t_A$ (line-line) | ≤ 1 ns |

| | |
|---|---|
| Response time $t_A$ (line-earth) | ≤ 100 ns |
| Input attenuation aE, sym. | typ. 0.3 dB (≤ 250 kHz / 150 Ω) |
| Cut-off frequency fg (3 dB), sym. in 150 Ω system | typ. 940 kHz |
| Capacity (Core-Core) | typ. 2 nF |
| Resistance per path | 1.65 Ω ±20 % |
| Surge protection fault message | optical |
| Max. required back-up fuse | 630 mA (FF) |
| Impulse durability (line-line) | C1 - 1 kV / 500 A |
| | C2 - 10 kV / 5 kA |
| | C3 - 100 A |
| Impulse durability (line-earth) | C1 - 1 kV / 500 A |
| | C2 - 10 kV / 5 kA |
| | C3 - 100 A |
| | D1 - 500 A |
| Pulse reset time (line-line) | ≤ 700 ms |
| Pulse reset time (line-earth) | ≤ 30 ms |

## Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Altitude | ≤ 2000 m (amsl) |
| Permissible humidity (operation) | 5 % ... 95 % |

## Approvals

Conformity/Approvals

| | |
|---|---|
| UL, USA / Canada | Class I, Div. 2, Groups A, B, C, D T4 |

## Standards and regulations

| | |
|---|---|
| Standards/specifications | EN 60079-0 |
| Note | 2018 |
| Standards/specifications | EN 60079-11 |
| Note | 2012 |

EN 61643-21


| | |
|---|---|
| Standards/specifications | EN 61643-21 |
| Note | 2001 + A1:2009 + A2:2013 |
| Standards/specifications | IEC 60079-0 |
| Note | 2017 |
| Standards/specifications | IEC 60079-11 |
| Note | 2008 |
| Standards/specifications | IEC 61643-21 |
| Note | 2000 + corrigendum 2001 + A1:2008, modified + A2:2012 |

## Mounting

| | |
|---|---|
| Mounting type | DIN rail: TH 35 - 7.5 mm |

## Drawings

Dimensional drawing





Schematic diagram

| TTC-6-1X2-M-EX-...-I | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Category | 1oo1 architecture, HFT=0 | | | | 1oo2 architecture, HFT=1 | | | | |
| | $PFD_{AVG}$ | PFH | Used budget of SIL 2 SIF | | $PFD_{AVG}$ | PFH | CCF | Used budget of SIL 3 SIF | |
| | | | $PFD_{AVG}$ | PFH | | | | $PFD_{AVG}$ | PFH |
| | $3.04_{x10^{-5}}$ | $5.40_{x10^{-9}}$ 1/h | 0.3 % | 0.5 % | $1.52_{x10^{-6}}$ | $2.70_{x10^{-10}}$ 1/h | 5 % | 0.2 % | 0.3 % |
| | | | | | $3.04_{x10^{-6}}$ | $5.40_{x10^{-10}}$ 1/h | 10 % | 0.3 % | 0.5 % |
| | Calculation based on exida report, Phoenix Contact 16/06-072 R023 V3R1<br>exida Profile 1, FMEDA Analysis 2, $T_{proof}$: 1 year, MT: 10 years, MTTR: 24 hours, PTC: 99%<br>Used standards<br>IEC/EN 61508, edition 2010 (device specific)<br>IEC/EN 61511, edition 2016 + COR1:2016 + A1:2017 (system specific) | | | | | | | | |


Functional safety scenarios

Diagram




Derating for non-Ex applications

Circuit diagram



## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/2906820

**CSA**
Approval ID: 70136717

**DNV GL**
Approval ID: TAE000027G

**UL Listed**
Approval ID: FILE E 138168

**CSAus**
Approval ID: 70136717

**UAE-RoHS**
Approval ID: 22-06-16191

**Functional Safety**
Approval ID: 16-06-072 R023 V3R1

**cUL Listed**
Approval ID: FILE E 333250

**INMETRO**
Approval ID: 19.0077 X

**NEPSI-EX**
Approval ID: GYJ20.1114X

**CCC**
Approval ID: 2020322316000780

**UKCA-EX**
Approval ID: DEKRA 23UKEX0110X

**cULus Listed**
Approval ID: File E 333250

**IECEx**
Approval ID: IECEx BVS 16.0090X

**ATEX**
Approval ID: BVS 16 ATEX E 125 X

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27171502 |
| ECLASS-15.0 | 27171502 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC001466 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121600 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 7(a), 7(c)-I |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | c7539712-8e63-4f9b-a2b0-732dfe2ca3a5 |

EF3.1 Climate Change

| | |
|---|---|
| CO2e kg | 1.428 kg CO2e |

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk