

# SACC-DSIV-MS-5CON-L90 SCOX - Device connector rear mounting



1239623

<https://www.phoenixcontact.com/pc/products/1239623>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 5-position, Pin, angled, M12-SPEEDCON, A-coding, Solder pins, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

## Commercial data

Item number	1239623
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	ABQEGI
GTIN	4063151425364
Weight per piece (including packing)	12.37 g
Weight per piece (excluding packing)	9.168 g
Customs tariff number	85366990
Country of origin	DE

# SACC-DSIV-MS-5CON-L90 SCOX - Device connector rear mounting



1239623

<https://www.phoenixcontact.com/pc/products/1239623>

## Technical data

### Notes

Order information:	Lock nut is included in the scope of delivery
--------------------	---

### Product properties

Product type	Circular connectors (device side)
Number of positions	5
Shielded	no
Coding	A
Thread type	M12

### Insulation characteristics

Overvoltage category	II
Degree of pollution	3

### Material specifications

Material Housing	GD-Zn
Material Housing surface	Ni
Material Insulating body	PA 6.6
Material Contact	CuZn
Material Contact surface	Au
Material Seal	NBR
Flammability rating according to UL 94	V0

### Electrical properties

Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage $U_N$	60 V
Nominal current $I_N$	4 A

### Connection data

#### Conductor connection

Connection method	Solder pins
Contact connection type	Pin

### Connector

#### Connection 1

Head design	Pin
Head cable outlet	angled
Head thread type	M12
Head locking type	SPEEDCON

# SACC-DSIV-MS-5CON-L90 SCOX - Device connector rear mounting



1239623

<https://www.phoenixcontact.com/pc/products/1239623>

Coding	A
--------	---

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation) (male connector/female connector)	-25 °C ... 85 °C (Plug / socket)

# SACC-DSIV-MS-5CON-L90 SCOX - Device connector rear mounting

1239623

<https://www.phoenixcontact.com/pc/products/1239623>

## Drawings

Schematic diagram



Pin assignment M12 male connector, 5-pos., A-coded, male side

# SACC-DSIV-MS-5CON-L90 SCOX - Device connector rear mounting



1239623

<https://www.phoenixcontact.com/pc/products/1239623>

## Classifications

### ECLASS

ECLASS-13.0	27440110
-------------	----------

### ETIM

ETIM 9.0	EC003569
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# SACC-DSIV-MS-5CON-L90 SCOX - Device connector rear mounting



1239623

<https://www.phoenixcontact.com/pc/products/1239623>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)