

# FL SWITCH EP7216-16GSFP-MV - Industrial Ethernet Switch



1688985

<https://www.phoenixcontact.com/us/products/1688985>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Managed Switch EP7000 series, 16 RJ45 ports 10/100/1000 Mbps, 16 SFP ports 100/1000 Mbps, degree of protection: IP20, Ambient temperature (operation): -40 °C ... 85 °C, Supply voltage range: 36 V DC ... 72 V DC



## Product description

Developed according to IEC 61850-3 (Ambient conditions)

## Your advantages

- Network structure according to IEC 61850
- IEEE 1613
- Layer 2 and Lite Layer 3 functions
- 32-port rackmount switch
- IEEE 1588 v2 precision timing support

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1688985       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | DN36          |
| Product key                          | DNN511        |
| GTIN                                 | 4067923248496 |
| Weight per piece (including packing) | 9,030 g       |
| Weight per piece (excluding packing) | 6,080 g       |
| Country of origin                    | CA            |

# FL SWITCH EP7216-16GSFP-MV - Industrial Ethernet Switch



1688985

<https://www.phoenixcontact.com/us/products/1688985>

## Technical data

### Dimensions

|        |           |
|--------|-----------|
| Width  | 443.56 mm |
| Height | 44.2 mm   |
| Depth  | 414.95 mm |

### Notes

Note on application

|                     |                         |
|---------------------|-------------------------|
| Note on application | Only for industrial use |
|---------------------|-------------------------|

### Material specifications

|                 |                          |
|-----------------|--------------------------|
| Color (Housing) | graphite gray (RAL 7024) |
|-----------------|--------------------------|

### Mounting

|               |                             |
|---------------|-----------------------------|
| Mounting type | Rack mounting (with holder) |
| Holder system | 19" rack                    |

### Interfaces

#### Ethernet

|                               |                                   |
|-------------------------------|-----------------------------------|
| Connection method             | RJ45                              |
| Note on the connection method | Auto negotiation and autocrossing |
| Transmission speed            | 10/100/1000 Mbps                  |
| Transmission physics          | Copper                            |
| Transmission length           | 100 m (per segment)               |
| No. of channels               | 16 (RJ45 ports)                   |

#### Ethernet (SFP)

|                      |                             |
|----------------------|-----------------------------|
| Connection method    | SFP                         |
| Transmission speed   | 100/1000 Mbps (full duplex) |
| Transmission physics | Depending on the SFP module |
| No. of channels      | 16 (SFP ports)              |

### Output data

Digital:

|             |  |
|-------------|--|
| Output name | Alarm relay output: 24 V DC, 1 A maximum |
|-------------|--|

### Product properties

|                |                       |
|----------------|-----------------------|
| Product type   | Switch                |
| Product family | Managed Switch EP7000 |

#### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
|----------------------|----|

# FL SWITCH EP7216-16GSFP-MV - Industrial Ethernet Switch



1688985

<https://www.phoenixcontact.com/us/products/1688985>

|                     |   |
|---------------------|---|
| Degree of pollution | 2 |
|---------------------|---|

## Switch functions

|                                  |                                 |
|----------------------------------|---------------------------------|
| Diagnostic functions             | SysLog                          |
| Signal contact control voltage   | 24 V DC                         |
| Signal contact control current   | 1 A                             |
| Filter functions                 | Link Aggregation                |
| IP parameterization              | DHCP Option 82                  |
| MAC address table                | 16k                             |
| Management                       | SNMPv1/v2/v3                    |
|                                  | Port mirroring                  |
|                                  | SSHv2                           |
|                                  | Telnet                          |
|                                  | MIB support                     |
| Redundancy                       | RSTP                            |
| Status and diagnostic indicators | LEDs: POWER, ERROR, Link status |
| Time synchronization             | IEEE 1588v2 (PTP)               |

## Security functions

|  |                             |
|--|-----------------------------|
| Authentication                                     | RADIUS Authentication       |
|  | TACACS+ Authentication      |
|  | ACLs (Access Control Lists) |
| Dynamic Host Configuration Protocol (DHCP) support | Client, Server and Relay    |
| Link Layer Discovery Protocol (LLDP)               | IEEE 802.1AB                |

## Electrical properties

|   |      |
|---|------|
| Maximum power dissipation for nominal condition | 50 W |
|---|------|

## Supply

|                      |  |
|----------------------|--|
| Supply voltage (DC)  | 48 V DC (Redundant DC power supplies are load sharing) |
| Supply voltage range | 36 V DC ... 72 V DC                                    |

## Function

|                                |         |
|--------------------------------|---------|
| Signal contact control voltage | 24 V DC |
| Signal contact control current | 1 A     |

## Connection data

### Power supply

|                                   |   |
|-----------------------------------|---|
| Connection method                 | Screw connection                            |
| Conductor cross-section, rigid    | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross-section, flexible | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross-section AWG       | 24 ... 12                                   |

## Environmental and real-life conditions

### Ambient conditions

# FL SWITCH EP7216-16GSFP-MV - Industrial Ethernet Switch



1688985

<https://www.phoenixcontact.com/us/products/1688985>

|  |  |
|--|--|
| Degree of protection                     | IP20   |
| Ambient temperature (operation)          | -40 °C ... 85 °C (Type tested to 85 °C for 16 hours) |
| Ambient temperature (storage/transport)  | -40 °C ... 85 °C                                     |
| Permissible humidity (operation)         | 5 % ... 95 % (non-condensing)                        |
| Permissible humidity (storage/transport) | 10 % ... 95 % (non-condensing)                       |

## Standards and regulations

|                          |                    |
|--------------------------|--------------------|
| Standard designation     | Ambient conditions |
| Standards/specifications | IEC 61850-3        |
|                          | IEEE 1613          |

## Approvals

### Conformity/Approvals

|             |              |
|-------------|--------------|
| Conformance | CE-compliant |
|-------------|--------------|

## EMC data

|                |  |
|----------------|--|
| Noise immunity | IEC 61850-3, IEEE 1613, EN 61000-6-2: 2005 |
|----------------|--|

## Signaling

|                |                                 |
|----------------|---------------------------------|
| Status display | LEDs: POWER, ERROR, Link status |
|----------------|---------------------------------|

# FL SWITCH EP7216-16GSFP-MV - Industrial Ethernet Switch



1688985

<https://www.phoenixcontact.com/us/products/1688985>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 19170401 |
| ECLASS-15.0 | 19170401 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC000734 |
|-----------|----------|

# FL SWITCH EP7216-16GSFP-MV - Industrial Ethernet Switch



1688985

<https://www.phoenixcontact.com/us/products/1688985>

## Environmental product compliance

### EU RoHS

|   |                             |
|---|-----------------------------|
| Fulfills EU RoHS substance requirements | Yes                         |
| Exemption                               | 6(c), 7(a), 7(c)-I, 7(c)-II |

### China RoHS

|  |   |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50   |
|  | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |   |
|-------------------------------------|---|
| REACH candidate substance (CAS No.) | 1-Methyl-2-pyrrolidone (NMP)(CAS: 872-50-4)                                 |
|                                     | N,N-dimethylacetamide(CAS: 127-19-5)  |
|                                     | 1, 2-dimethoxyethane; ethylene glycol dimethyl ether (EGDME)(CAS: 110-71-4) |
|                                     | Hexahydromethylphthalic anhydride(CAS: n/a)                                 |
|                                     | Lead titanium zirconium oxide(CAS: 12626-81-2)                              |
|                                     | Lead titanium trioxide(CAS: 12060-00-3)                                     |
|                                     | 4,4'-isopropylidenediphenol(CAS: 80-05-7)                                   |
|                                     | Terphenyl, hydrogenated(CAS: 61788-32-7)                                    |
|                                     | Lead(CAS: 7439-92-1)  |
|                                     | 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one(CAS: 71868-10-5)   |

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)