

# SAC-4P-M12Y/2X0,6-PUR/M 8FR VP - Sensor/actuator cable



1004861

<https://www.phoenixcontact.com/us/products/1004861>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coding: A, on Socket angled M8, coding: A and Socket angled M8, coding: A, cable length: 0.6 m

## Commercial data

Item number	1004861
Packing unit	1 pc
Minimum order quantity	100 pc
Product key	AF1COA
GTIN	4055626475219
Weight per piece (including packing)	51.4 g
Weight per piece (excluding packing)	51 g
Country of origin	PL

# SAC-4P-M12Y/2X0,6-PUR/M 8FR VP - Sensor/actuator cable

1004861

<https://www.phoenixcontact.com/us/products/1004861>

## Technical data

### Product properties

Product type	Distributor with cable
Number of positions	4

### Electrical properties

Nominal voltage $U_N$	48 V AC
	60 V DC

### Connector

#### Connection 1

Type	Plug straight M12
Coding type	A

#### Connection 2

Type	Socket angled M8
Coding type	A

#### Connection 3


Type	Socket angled M8
Coding type	A

### Cable/line

Cable length	0.6 m
--------------	-------

#### PUR halogen-free black [PUR]

##### Dimensional drawing



Cable weight	23 kg/km
UL AWM Style	20549 / 10493 (80°C/300 V)
Number of positions	4
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	32x 0.10 mm
AWG signal line	24
Conductor cross-section	4x 0.25 mm <sup>2</sup> (Signal line)
Wire diameter incl. insulation	1.17 mm ±0.02 mm (Signal line)

# SAC-4P-M12Y/2X0,6-PUR/M 8FR VP - Sensor/actuator cable



1004861

<https://www.phoenixcontact.com/us/products/1004861>

External cable diameter	3.95 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	brown, white, blue, black
Thickness, insulation	≥ 0.21 mm (Core insulation) approx. 0.50 mm (Outer cable sheath)
Overall twist	4 wires, twisted
Max. conductor resistance	max. 78 Ω/km (at 20 °C)
Insulation resistance	≥ 100 GΩ*km (at 20 °C)
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 3000 V
Smallest bending radius, fixed installation	20 mm
Smallest bending radius, movable installation	40 mm
Dynamic load capacity (bending)	Max. bending cycles: 10000000, Bending radius: 44 mm, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 5 m/s <sup>2</sup>
Dynamic load capacity (torsion)	Torsion: ±180 °/m, Torsion cycles: ≥5000000, Torsional frequency: 35 cycles/min.
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	in accordance with UL 758/1581 FT2 DIN EN 60332-2-2 (20 s)
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	Highly resistant to acids, alkaline solutions and solvents hydrolysis and microbe resistant partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Special properties	Flexible cable conduit capable Silicone-free Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -25 °C ... 80 °C (Cable, flexible installation)

# SAC-4P-M12Y/2X0,6-PUR/M 8FR VP - Sensor/actuator cable



1004861

<https://www.phoenixcontact.com/us/products/1004861>

## Classifications

### ECLASS

ECLASS-13.0	27060313
ECLASS-15.0	27060313

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# SAC-4P-M12Y/2X0,6-PUR/M 8FR VP - Sensor/actuator cable



1004861

<https://www.phoenixcontact.com/us/products/1004861>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)