

# HC-M-02-AT-M-35 - Contact insert module



1417392

<https://www.phoenixcontact.com/us/products/1417392>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert module, number of positions: 2, power contacts: 2, control contacts: 0, Pin, Axial screw connection, 1000 V, 100 A, 10 mm<sup>2</sup> ... 35 mm<sup>2</sup>, application: Power

## Commercial data

Item number	1417392
Packing unit	2 pc
Minimum order quantity	2 pc
Sales key	BF62
Product key	AF7ACE
GTIN	4055626112718
Weight per piece (including packing)	67.5 g
Weight per piece (excluding packing)	66.83 g
Customs tariff number	85366990
Country of origin	PL

## Technical data

### Mounting

Assembly note	<p>To ensure correct use, installation in housing with IP54 protection or better is required</p> <hr/> <p><b>Note regarding axial connection technology:</b></p> <p>Only for stranded wires. The specified conductor cross-sections refer to the geometric cross section of the cable used. Cables with a geometric cross section which deviates significantly from the nominal cable cross section must be checked before use.</p> <p>The axial connection technology connection space is designed for fine strand cables according to VDE 0295 Class 5. Deviating cable structures (e.g., Class 6 cables) must be checked before use.</p> <p><b>Assembly instructions</b></p> <p>Before assembly, ensure that the tapered screw is fully loosened (chamber is open). Cables must not be twisted. The wires must be pushed into the contact chamber as far as they will go (until the insulation touches the contact). Hold the wires in position and tighten using an Allen key. The used wire end must be cut off before reconnection. The terminal screw must only be retightened once to prevent the litz wires from breaking. To prevent damage to the contact, the wire/cable must be mechanically held at an appropriate distance from the connection point (e.g., when used in a plate cut out). For notes on correct execution, see DIN VDE 0100-520:2003-06. Unused connections must be tightened with maximum torque.</p>
Hexagonal socket	SW 4

### Product properties

Product type	Modular contact insert
Series	HC-M-HS
Application	Power
Number of positions	2
Connection profile	2
Contact numbering	1 - 2
Number of module slots	2
No. of power contacts	2
No. of control contacts	0
Contact material type	turned

#### Insulation characteristics

Overvoltage category	III
Degree of pollution	3

### Connection data

Connection technology	
-----------------------	--

# HC-M-02-AT-M-35 - Contact insert module



1417392

<https://www.phoenixcontact.com/us/products/1417392>

Connection technology	Axial screw connection
Conductor connection	
Conductor cross-section	10 mm <sup>2</sup> ... 35 mm <sup>2</sup> (The cross section specification refers to the geometric cross section of the cable used)
Connection cross section AWG	8 ... 2
Tightening torque	6 Nm (10 mm <sup>2</sup> ... 16 mm <sup>2</sup> )
	7 Nm (25 mm <sup>2</sup> )
	8 Nm (35 mm <sup>2</sup> )
Stripping length of the individual wire	14 mm (with an outside conductor diameter up to 9 mm)
	16 mm (with an outside conductor diameter up to 11.5 mm)

## Dimensions

Dimensional drawing	
Width	34.2 mm
Height	49 mm
Length	29.4 mm

## Mechanical characteristics

Minimum housing height	72 mm
Contact diameter	8 mm

## Electrical properties

Rated voltage (III/3)	1000 V
Rated surge voltage (III/2)	8 kV
Rated surge voltage (III/3)	8 kV
Rated surge voltage	8 kV
Rated current	100 A

## Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

## Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PC
Standards/regulations	PC

## Environmental and real-life conditions

# HC-M-02-AT-M-35 - Contact insert module



1417392

<https://www.phoenixcontact.com/us/products/1417392>

## Ambient conditions

Ambient temperature (operation)

-40 °C ... 125 °C

## Standards and regulations

### Testing

Standards/regulations

PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

# HC-M-02-AT-M-35 - Contact insert module





1417392

<https://www.phoenixcontact.com/us/products/1417392>

## Drawings

Dimensional drawing




Male insert

# HC-M-02-AT-M-35 - Contact insert module

1417392

<https://www.phoenixcontact.com/us/products/1417392>

Schematic diagram



Connector pin assignment

# HC-M-02-AT-M-35 - Contact insert module

1417392

<https://www.phoenixcontact.com/us/products/1417392>

Schematic diagram



Axial connection

Diagram



Derating diagram

# HC-M-02-AT-M-35 - Contact insert module



1417392

<https://www.phoenixcontact.com/us/products/1417392>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1417392>

### DNV

Approval ID: TAE000037S



### CSA

Approval ID: 158887

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
keine				
	600 V	100 A	- 2	-



### UL Recognized

Approval ID: E118976

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
keine				
	600 V	127 A	- 2	-



### cULus Recognized

Approval ID: E468743

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
keine				
	1000 V	100 A	- 2	-

# HC-M-02-AT-M-35 - Contact insert module



1417392

<https://www.phoenixcontact.com/us/products/1417392>

## Classifications

### ECLASS

ECLASS-13.0	27440217
ECLASS-15.0	27440217

### ETIM

ETIM 10.0	EC000438
-----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# HC-M-02-AT-M-35 - Contact insert module



1417392

<https://www.phoenixcontact.com/us/products/1417392>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

### EF3.1 Climate Change

CO2e kg	0.343 kg CO2e
---------	---------------

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)