

NBC-100,0-94S - Data cable



1423514

<https://www.phoenixcontact.com/us/products/1423514>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



By the meter, Data cable, Ethernet CAT7 (10 Gbps), shielded, PE-X halogen-free, black, 8-wire (4x2xAWG26/7; S/FTP), color single wire: white-blue, white-orange, white-green, white-brown, cable length: 100 m

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 1423514 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | BF11 |
| Product key | AF1LEA |
| GTIN | 4055626346007 |
| Weight per piece (including packing) | 5,773 g |
| Weight per piece (excluding packing) | 5,773 g |
| Customs tariff number | 85444995 |
| Country of origin | DE |

NBC-100,0-94S - Data cable

1423514

<https://www.phoenixcontact.com/us/products/1423514>

Technical data

Product properties

| | |
|---------------------|-------------------------|
| Product type | Data cable by the meter |
| Application | Railway applications |
| Sensor type | Ethernet |
| Number of positions | 8 |

Electrical properties

| | |
|-----------------------|---------|
| Nominal voltage U_N | 30 V AC |
| | 30 V DC |
| Transmission medium | Copper |
| Transmission speed | 10 Gbps |


Interfaces

| | |
|----------------------|------------------------|
| Signal type/category | Ethernet CAT7, 10 Gbps |
|----------------------|------------------------|

Cable/line

| | |
|--------------|-------|
| Cable length | 100 m |
|--------------|-------|

Ethernet BETAtrans® railway application CAT7 [94S]

| | |
|---------------------------------|--|
| Dimensional drawing |  |
| Cable weight | 59 kg/km |
| Copper weight | 28 kg/km |
| Number of positions | 8 |
| Shielded | yes |
| Cable type | Ethernet BETAtrans® railway application CAT7 [94S] |
| Conductor structure | 4x2xAWG26/7; S/FTP |
| Signal runtime | 4.4 ns/m |
| Signal speed | 0.78 c |
| Conductor structure signal line | 7x 0.16 mm |
| AWG signal line | 26 |
| Conductor cross-section | 4x 2x 0.14 mm ² |
| Wire diameter incl. insulation | 1.05 mm ±0.1 mm |
| External cable diameter | 6.60 mm ±0.2 mm |
| Outer sheath, material | PE-X |
| External sheath, color | black |

NBC-100,0-94S - Data cable



1423514

<https://www.phoenixcontact.com/us/products/1423514>

| | |
|--|--|
| Conductor material | Tin-plated Cu litz wires |
| Material wire insulation | Cell PE |
| Single wire, color | white-blue, white-orange, white-green, white-brown |
| Twisted pairs | 2 cores to the pair |
| Type of pair shielding | Aluminum-lined polyester foil |
| Overall twist | 4 pairs, twisted |
| Max. conductor resistance | ≤ 145 Ω/km |
| Insulation resistance | ≥ 5 GΩ*km |
| Coupling resistance | 5.00 mΩ/m (at 10 MHz) |
| Wave impedance | 100 Ω ±5 Ω (at 100 MHz) |
| Working capacitance | 44 nF (per kilometer) |
| Nominal voltage, cable | 125 V AC (U ₀) |
| Test voltage Core/Core | 1000 V AC (50 Hz, 1 min.) |
| Test voltage Core/Shield | 1000.00 V AC (50 Hz, 1 min.) |
| Minimum bending radius, fixed installation | 6 x D |
| Smallest bending radius, fixed installation | 40 mm |
| Tensile strength | ≤ 60 N (temporary) ≤ 15 N (Permanent) |
| Near end crosstalk attenuation (NEXT) | 100 dB (with 1 MHz) |
| | 99 dB (at 10 MHz) |
| | 95 dB (at 100 MHz) |
| | 92 dB (at 200 MHz) |
| | 90 dB (at 250 MHz) |
| | 83 dB (at 500 MHz) |
| | 81 dB (at 600 MHz) |
| | 80 dB (at 700 MHz) |
| | 77 dB (at 800 MHz) |
| | 75 dB (at 900 MHz) |
| | 74 dB (at 1000 MHz) |
| | 72 dB (at 1100 MHz) |
| 70 dB (at 1200 MHz) | |
| Power-summated near end crosstalk attenuation (PSNEXT) | 97 dB (with 1 MHz) |
| | 96 dB (at 10 MHz) |
| | 92 dB (at 100 MHz) |
| | 89 dB (at 200 MHz) |
| | 87 dB (at 250 MHz) |
| | 80 dB (at 500 MHz) |
| | 78 dB (at 600 MHz) |
| | 77 dB (at 700 MHz) |
| | 74 dB (at 800 MHz) |
| | 72 dB (at 900 MHz) |
| | 71 dB (at 1000 MHz) |
| | 69 dB (at 1100 MHz) |
| 67 dB (at 1200 MHz) | |

NBC-100,0-94S - Data cable



1423514

<https://www.phoenixcontact.com/us/products/1423514>

| | |
|---|-----------------------|
| Return attenuation (RL) | 24 dB (with 1 MHz) |
| | 33.9 dB (at 10 MHz) |
| | 38.3 dB (at 100 MHz) |
| | 35.3 dB (at 200 MHz) |
| | 32.9 dB (at 250 MHz) |
| | 29.7 dB (at 500 MHz) |
| | 30.6 dB (at 600 MHz) |
| | 31 dB (at 700 MHz) |
| | 26.7 dB (at 800 MHz) |
| | 28.6 dB (at 900 MHz) |
| | 27.5 dB (at 1000 MHz) |
| | 26.9 dB (at 1100 MHz) |
| | 26.3 dB (at 1200 MHz) |
| Crosstalk attenuation (ACR) | 100 dB (with 1 MHz) |
| | 99 dB (at 10 MHz) |
| | 93 dB (at 100 MHz) |
| | 88 dB (at 200 MHz) |
| | 86 dB (at 250 MHz) |
| | 78 dB (at 500 MHz) |
| | 74 dB (at 600 MHz) |
| | 72 dB (at 700 MHz) |
| | 69 dB (at 800 MHz) |
| | 67 dB (at 900 MHz) |
| | 65 dB (at 1000 MHz) |
| 63 dB (at 1100 MHz) | |
| 61 dB (at 1200 MHz) | |
| Power-summated crosstalk attenuation (PS-ACR) | 97 dB (with 1 MHz) |
| | 96 dB (at 10 MHz) |
| | 90 dB (at 100 MHz) |
| | 85 dB (at 200 MHz) |
| | 83 dB (at 250 MHz) |
| | 75 dB (at 500 MHz) |
| | 71 dB (at 600 MHz) |
| | 69 dB (at 700 MHz) |
| | 66 dB (at 800 MHz) |
| | 64 dB (at 900 MHz) |
| | 62 dB (at 1000 MHz) |
| | 60 dB (at 1100 MHz) |
| 58 dB (at 1200 MHz) | |
| Shield attenuation | 0.25 dB (with 1 MHz) |
| | 0.76 dB (at 10 MHz) |
| | 2.49 dB (at 100 MHz) |
| | 3.69 dB (at 200 MHz) |
| | 4.18 dB (at 100 MHz) |

NBC-100,0-94S - Data cable



1423514

<https://www.phoenixcontact.com/us/products/1423514>

| | |
|----------------------------------|---|
| | 5.6 dB (at 500 MHz) |
| | 6.74 dB (at 600 MHz) |
| | 7.32 dB (at 700 MHz) |
| | 7.89 dB (at 800 MHz) |
| | 8.5 dB (at 900 MHz) |
| | 9.11 dB (at 1000 MHz) |
| | 9.5 dB (at 1100 MHz) |
| | 9.9 dB (at 1200 MHz) |
| | 60.00 dB (up to 1000 MHz) |
| Halogen-free | in accordance with EN 50267-2-1 |
| | in accordance with EN 60684-2 |
| Flame resistance | in accordance with EN 60332-1-2 |
| | EN 60332-3-25 |
| | in accordance with ISO 14572 5.21 (UN ECE-R 118.01) |
| Concentration of fumes | EN 61034-2 |
| Resistance to oil | in accordance with EN 50306-4, 72 hours at 100°C, IRM 902 |
| Fire protection in rail vehicles | BS 6853 (Internal cable Ia, Ib, II/external cable Ia, Ib, II) |
| | DIN 5510-2 (Fire protection level 1, 2, 3, 4) |
| | EN 45545-2 (Risk level HL1 - HL3) |
| | EN 50306-4 |
| | NF F16-101 (Classification C/F1) |
| | NF F16-101 (Internal cable A1, A2, B/external cable A1, A2, B) |
| | NFPA 130 |
| | PN-K-02511 (Class A) |
| | UIC 564-2 (Class A) |
| Other resistance | Resistant to fuel (in accordance with EN 50306-4, 168 hours at 70°C, IRM 903) |
| | Resistant to ozone (in accordance with EN 50306-4, 72 hours at 40°C, method B, volumetric concentration of 200×10^{-6}) |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) |

NBC-100,0-94S - Data cable



1423514

<https://www.phoenixcontact.com/us/products/1423514>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1423514>



EAC-RoHS

Approval ID: RU D-DE.HB35.B.00371

NBC-100,0-94S - Data cable



1423514

<https://www.phoenixcontact.com/us/products/1423514>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27061801 |
| ECLASS-15.0 | 27061801 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC003249 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

NBC-100,0-94S - Data cable



1423514

<https://www.phoenixcontact.com/us/products/1423514>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

EF3.1 Climate Change

| | |
|---------|-----------------|
| CO2e kg | 215.185 kg CO2e |
|---------|-----------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com