

SYS N4X 120/208Y - Surge protection device



2800714

<https://www.phoenixcontact.com/us/products/2800714>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Indoor/outdoor lightning current arrester and TVSS system for 120/208-240 V



Product description

Combination lightning current arrester and TVSS for 120/208-240 V. Components are housed in an IP66/NEMA 4X cabinet.

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 2800714 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | CL01 |
| Product key | CL1622 |
| GTIN | 4046356643306 |
| Weight per piece (including packing) | 222.22 g |
| Weight per piece (excluding packing) | 222.22 g |
| Customs tariff number | 85363090 |
| Country of origin | DE |

SYS N4X 120/208Y - Surge protection device



2800714

<https://www.phoenixcontact.com/us/products/2800714>

Technical data

Product properties

| | |
|--------------------------------|----------------------------------------------|
| Product type | Surge protection for NEMA power supply units |
| IEC test classification | I + II |
| EN type | T1 |
| Type | Housing for surface mounting |
| Surge protection fault message | Remote indication contact |

Electrical properties

| | |
|-----------------------|-------------------------------------|
| Nominal voltage U_N | < 240 V |
| Fuse | 200 kA VSP100, 100 A, 200 kAIC (IR) |

General

| | |
|---------------|------------------|
| Power Systems | 120/208 V AC Wye |
|---------------|------------------|

Connection data

| | |
|---------------------------------------|----------------------|
| Conductor cross-section flexible min. | 16 mm ² |
| Conductor cross-section flexible max. | 35 mm ² |
| Conductor cross-section, rigid min. | 10 mm ² |
| Conductor cross-section, rigid max. | 50 mm ² |
| Connection method | Screw connection |
| Conductor cross-section flexible min. | 0.14 mm ² |
| Conductor cross-section flexible max. | 1.5 mm ² |
| Conductor cross-section, rigid min. | 0.14 mm ² |
| Conductor cross-section, rigid max. | 1.5 mm ² |

Dimensions

| | |
|--------|--------|
| Width | 400 mm |
| Height | 500 mm |
| Depth | 210 mm |

Material specifications

| | |
|------------------|-----------------------------|
| Color | Steel/stainless steel color |
| | black (RAL 9005) |
| Housing material | Stainless steel 1.4404 |

Protective circuit

| | |
|--------------------------------------------|--------------------|
| Nominal voltage U_N | 120/208 V AC (Wye) |
| Maximum continuous operating voltage U_C | 275 V AC |
| Follow current interrupt rating I_{fi} | 50 kA |
| Response time t_A | ≤ 25 ns |

Environmental and real-life conditions

SYS N4X 120/208Y - Surge protection device



2800714

<https://www.phoenixcontact.com/us/products/2800714>

Ambient conditions

| | |
|---------------------------------|------------------|
| Degree of protection | IP66/NEMA 4X |
| Ambient temperature (operation) | -40 °C ... 80 °C |

Approvals

UL specifications

| | |
|-------------------------------------|--------------------|
| Short-circuit current rating (SCCR) | 50 kA |
| UL type | type 2 |
| Nominal discharge current I_n | 20 kA |
| Maximum Surge Current per Phase | 50 kA |
| Nominal voltage | 120/208 V AC (Wye) |
| Power distribution system | Wye |

Standards and regulations

Standards

| | |
|-----------------------|------------------------------------|
| Standards/regulations | ANSI/UL 1449:2014 Ed.4+R:17MAR2016 |
| | IEC 60643-1 |
| | EN 61643-11 |
| | CAN/CSA-C22.2 No. 8:2013 Ed.5 |

Mounting

| | |
|---------------|------------------------|
| Mounting type | Surface/Panel mounting |
|---------------|------------------------|

SYS N4X 120/208Y - Surge protection device

2800714

<https://www.phoenixcontact.com/us/products/2800714>

Drawings

Circuit diagram



SYS N4X 120/208Y - Surge protection device



2800714

<https://www.phoenixcontact.com/us/products/2800714>

Classifications

ECLASS

ECLASS-13.0

27171202

UNSPSC

UNSPSC 21.0

39121620

SYS N4X 120/208Y - Surge protection device



2800714

<https://www.phoenixcontact.com/us/products/2800714>

Environmental product compliance

EU RoHS

| | |
|-----------------------------------------|-------------------------------------------------------|
| Fulfills EU RoHS substance requirements | Not applicable, Not qualified for the European market |
|-----------------------------------------|-------------------------------------------------------|

China RoHS

| | |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------------------------|
| REACH candidate substance (CAS No.) | Hexahydromethylphthalic anhydride(CAS: n/a) |
| | 4-Nonylphenol, branched and linear(CAS: n/a) |
| | Lead(CAS: 7439-92-1) |

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com