

# STP 5-2 - Marker carriers

0800967

<https://www.phoenixcontact.com/us/products/0800967>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker carriers, snaps into STTB 2,5, STTB 4, PTTB 2,5, and PTTB 4 double-level spring-cage terminal blocks, can be marked with UC-TM 5, UC-TMF 5, UCT-TM 5, UCT-TMF 5, ZB 5, or ZBF 5, gray (RAL 7042), unmarked, mounting type: plug in, text field height: 10.5 mm, text field width: 5 mm

## Your advantages

- The labeling areas of wired multi-level terminal blocks are increased by using marker carriers
- Depending on version, the marker carriers are inserted in the holders on the upper terminal block level

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 0800967       |
| Packing unit                         | 100 pc        |
| Minimum order quantity               | 100 pc        |
| Sales key                            | BG12          |
| Product key                          | BG211A        |
| GTIN                                 | 4017918138776 |
| Weight per piece (including packing) | 0.467 g       |
| Weight per piece (excluding packing) | 0.483 g       |
| Customs tariff number                | 39269097      |
| Country of origin                    | PL            |

# STP 5-2 - Marker carriers



0800967

<https://www.phoenixcontact.com/us/products/0800967>

## Technical data

### Product properties

|              |                 |
|--------------|-----------------|
| Product type | Marker carriers |
|--------------|-----------------|

### Dimensions

|        |          |
|--------|----------|
| Width  | 5.00 mm  |
| Height | 24.90 mm |
| Depth  | 28.60 mm |

### Text field

|                   |         |
|-------------------|---------|
| Text field width  | 5 mm    |
| Text field height | 10.5 mm |

### Material specifications

|  |                                |
|--|--------------------------------|
| Color  | gray (RAL 7042)                |
| Flammability rating according to UL 94                           | V2                             |
| Base element material  | PA                             |
| Relative insulation material temperature index (Elec., UL 746 B) | 125 °C                         |
| Components   | free from silicone and halogen |

### Environmental and real-life conditions

#### Ambient conditions

|   |                   |
|---|-------------------|
| Ambient temperature (operation)                     | -40 °C ... 100 °C |
| Recommended ambient temperature (storage/transport) | 23 °C             |
| Recommended humidity (storage/transport)            | 50 %              |

### Mounting

|               |         |
|---------------|---------|
| Mounting type | plug in |
|---------------|---------|

# STP 5-2 - Marker carriers



0800967

<https://www.phoenixcontact.com/us/products/0800967>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27281105 |
| ECLASS-15.0 | 27281105 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC002248 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# STP 5-2 - Marker carriers



0800967

<https://www.phoenixcontact.com/us/products/0800967>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

### EF3.1 Climate Change

|         |               |
|---------|---------------|
| CO2e kg | 0.003 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)