

GPK 610X610X1,5 ... - Engraving plate



0806424

<https://www.phoenixcontact.com/us/products/0806424>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving plate, Plate, white (RAL 9010), unmarked, can be labeled with: P1 ENGRAVING UNIT, ENGRAVING UNIT, mounting type: screw, rivet, Number of individual labels: 1, text field height: 610 mm, text field width: 610 mm



Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 0806424 |
| Packing unit | 10 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | NULL |
| Product key | BG2415 |
| GTIN | 4017918138509 |
| Weight per piece (including packing) | 576 g |
| Weight per piece (excluding packing) | 576 g |
| Customs tariff number | 39203000 |
| Country of origin | DE |

GPK 610X610X1,5 ... - Engraving plate



0806424

<https://www.phoenixcontact.com/us/products/0806424>

Technical data

Product properties

| | |
|--------------|---------------|
| Product type | Device marker |
|--------------|---------------|

Marking

| | |
|-----------------------------|-----------|
| Number of individual labels | 1 |
| Identification technology | Engraving |

Dimensions

| | |
|--------|-----------|
| Width | 610.00 mm |
| Height | 610.00 mm |
| Depth | 1.53 mm |

Text field

| | |
|-------------------|--------|
| Text field width | 610 mm |
| Text field height | 610 mm |

Material specifications

| | |
|-----------------------|------------------|
| Adhesive strength | 50 µm |
| Adhesive | Acrylic |
| Color | white (RAL 9010) |
| Base element material | ABS |

Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 85 °C |
| Recommended ambient temperature (storage/transport) | 20 °C |
| Recommended humidity (storage/transport) | 50 % (Storage in a dry and dark place in the original packaging is recommended) |

UV resistance

| | |
|---------------|---------------------------------------|
| Specification | DIN EN ISO 4892-2:2021-11 (following) |
|---------------|---------------------------------------|

Wipe resistance of inscriptions

| | |
|---------------|-------------------------------------|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07 |
|---------------|-------------------------------------|

Mounting

| | |
|---------------|--------------|
| Mounting type | screw, rivet |
|---------------|--------------|

GPK 610X610X1,5 ... - Engraving plate



0806424

<https://www.phoenixcontact.com/us/products/0806424>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27281103 |
| ECLASS-15.0 | 27281103 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC001288 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

GPK 610X610X1,5 ... - Engraving plate



0806424

<https://www.phoenixcontact.com/us/products/0806424>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com