

PML-W203 (200X200) - Warning label



0830444

<https://www.phoenixcontact.com/us/products/0830444>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Warning label, Sheet, labeled: Lightning flash and print: 400 V, mounting type: adhesive, diameter: 0 mm, Number of individual labels: 1



Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 0830444 |
| Packing unit | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | BG21 |
| Product key | BG2511 |
| GTIN | 4046356717687 |
| Weight per piece (including packing) | 19.93 g |
| Weight per piece (excluding packing) | 19.93 g |
| Customs tariff number | 39199080 |
| Country of origin | DE |

PML-W203 (200X200) - Warning label



0830444

<https://www.phoenixcontact.com/us/products/0830444>

Technical data

Product properties

| | |
|---------------------|--|
| Product type | Plant marker |
| Area of application | Warning labels |
| | Warning identification according to ISO 7010 |
| Type | Triangle |

Marking

| | |
|-------------------------------------|----------------------------------|
| Number of individual labels | 1 |
| Number of individual labels per row | 1 |
| Printing | Lightning flash and print: 400 V |
| Identification technology | Office laser printing |

Dimensions

| | |
|--------|----------|
| Width | 200 mm |
| Height | 237.5 mm |

Material specifications

| | |
|-----------------------|---------------|
| RoHS compliant | yes |
| Foil strength | 50 µm |
| Adhesive | Acrylic |
| Color | yellow/black |
| Base element material | PVC |
| Components | Silicone-free |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 90 °C |
|---------------------------------|------------------|

Test for substances that would hinder coating with paint or varnish

| | |
|---|----------------------|
| Testing for paint wetting impairment substances (LABS-conformity) | VW PV 3.10.7:2005-02 |
| Result | Test passed |

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |

Wipe resistance of inscriptions

| | |
|-----------------------------|--|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropanol (99%) [67-63-0] | Test passed |

PML-W203 (200X200) - Warning label



0830444

<https://www.phoenixcontact.com/us/products/0830444>

| | |
|---|-------------|
| n-Hexane [CAS No. 110-54-3] | Test passed |
| Water + Petroleum ether [CAS No. 64742-82-1] | Test passed |

Testing in a condensation changing climate in the presence of sulfur dioxide

| | |
|---------------|-------------------|
| Specification | DIN 50018:2013-05 |
| Result | Test passed |
| Climate level | AHT 1.0 S |
| Cycles | 2 |

Salt spray test

| | |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result | Test passed |

Mounting

| | |
|---------------|----------|
| Mounting type | adhesive |
|---------------|----------|

PML-W203 (200X200) - Warning label



0830444

<https://www.phoenixcontact.com/us/products/0830444>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com