

UM3-TM (5X8) - Marker for terminal blocks



0830917

<https://www.phoenixcontact.com/us/products/0830917>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Marker for terminal blocks, Strip, white (RAL 9010), unmarked, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, mounting type: latching, Number of individual labels: 24, text field height: 8 mm, text field width: 5 mm



Your advantages

- The markers, which are supplied in uniform strips, can be printed onto quickly and easily using the BLUEMARK printing systems
- The UM3-TM ... UM labeling range includes terminal markers for Wieland terminal blocks
- The multi-section marking strips are easy to fit and can be easily separated if required
- The markers support multi-line labeling

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 0830917 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | BG08 |
| Product key | BGE21C |
| GTIN | 4046356910514 |
| Weight per piece (including packing) | 2.34 g |
| Weight per piece (excluding packing) | 2.34 g |
| Customs tariff number | 39269097 |
| Country of origin | PL |

UM3-TM (5X8) - Marker for terminal blocks



0830917

<https://www.phoenixcontact.com/us/products/0830917>

Technical data

Product properties

| | |
|---------------------|-----------------|
| Product type | Terminal marker |
| Area of application | Wieland |

Marking

| | |
|-------------------------------------|-------------------|
| Number of individual labels | 24 |
| Number of individual labels per row | 12 |
| Number of marker strips | 2 |
| Slot type | high |
| Identification technology | UV LED technology |

Dimensions

| | |
|--------|---------|
| Width | 8.20 mm |
| Height | 4.45 mm |
| Depth | 4.15 mm |

Text field

| | |
|-------------------|------|
| Text field width | 5 mm |
| Text field height | 8 mm |

Material specifications

| | |
|----------------------------------------|------------------------------------------|
| RoHS compliant | yes |
| Color | white (RAL 9010) |
| Flammability rating according to UL 94 | V2 |
| Base element material | PC |
| Components | free from silicone, halogen, and cadmium |

Environmental and real-life conditions

Ambient conditions

| | |
|-----------------------------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |

Test for substances that would hinder coating with paint or varnish

| | |
|-------------------------------------------------------------------|----------------------|
| Testing for paint wetting impairment substances (LABS-conformity) | VW PV 3.10.7:2005-02 |
| Result | Test passed |

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |

Wipe resistance of inscriptions

UM3-TM (5X8) - Marker for terminal blocks



0830917

<https://www.phoenixcontact.com/us/products/0830917>

| | |
|-------------------------------------------------|------------------------------------------------|
| Specification | IEC 61010-1:2010-06 |
| | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropanol (99%) [67-63-0] | Test passed |
| n-Hexane [CAS No. 110-54-3] | Test passed |
| Water + Petroleum ether [CAS No. 64742-82-1] | Test passed |

Testing in a condensation changing climate in the presence of sulfur dioxide

| | |
|---------------|-------------------|
| Specification | DIN 50018:2013-05 |
| Result | Test passed |
| Climate level | AHT 1.0 S |
| Cycles | 2 |

Salt spray test

| | |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result | Test passed |

Mounting

| | |
|---------------|----------|
| Mounting type | latching |
|---------------|----------|

UM3-TM (5X8) - Marker for terminal blocks



0830917

<https://www.phoenixcontact.com/us/products/0830917>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27281101 |
| ECLASS-15.0 | 27281101 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC000761 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

UM3-TM (5X8) - Marker for terminal blocks



0830917

<https://www.phoenixcontact.com/us/products/0830917>

Environmental product compliance

EU RoHS

| | |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

EF3.1 Climate Change

| | |
|---------|---------------|
| CO2e kg | 0.008 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com