

# PMST (9X38) BU - Insert label



0830969

<https://www.phoenixcontact.com/us/products/0830969>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insert label, blue (RAL 5015), unmarked, mounting type: latching, Number of individual labels: 1



## Your advantages

- The medium marking label is used in conjunction with insertable UCT-PMP ... labels in the CARRIER-PMP
- They are used to clearly identify devices and control cabinets
- They are secured in the CARRIER-PMP using rivets

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 0830969       |
| Packing unit                         | 100 pc        |
| Minimum order quantity               | 100 pc        |
| Product key                          | BG261Z        |
| GTIN                                 | 4046356912433 |
| Weight per piece (including packing) | 0.47 g        |
| Weight per piece (excluding packing) | 0.47 g        |
| Country of origin                    | DE            |

## Technical data

### Product properties

|                     |   |
|---------------------|---|
| Product type        | Plant marker  |
| Area of application | Identification of flow substances according to DIN 2403 |

### Marking

|                                     |   |
|-------------------------------------|---|
| Number of individual labels         | 1 |
| Number of individual labels per row | 1 |

### Dimensions

|        |       |
|--------|-------|
| Width  | 9 mm  |
| Length | 38 mm |

### Material specifications

|  |                 |
|--|-----------------|
| Color                                  | blue (RAL 5015) |
| Material                               | PVC             |
| Flammability rating according to UL 94 | V0              |
| Components                             | Silicone-free   |

### Environmental and real-life conditions

#### Ambient conditions

|   |  |
|---|--|
| Ambient temperature (operation)                     | -30 °C ... 80 °C   |
| Recommended ambient temperature (storage/transport) | 10 °C  |
| Recommended humidity (storage/transport)            | 40 % ... 70 % (Storage in a dry and dark place in the original packaging is recommended) |

#### UV resistance

|               |                                |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result        | Test passed                    |
| Test duration | 96 h                           |
| Procedure     | Artificial irradiation.        |

### Standards and regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

### Mounting

|               |          |
|---------------|----------|
| Mounting type | latching |
|---------------|----------|

# PMST (9X38) BU - Insert label



0830969

<https://www.phoenixcontact.com/us/products/0830969>

## Classifications

### ECLASS

ECLASS-13.0

27281104

### ETIM

ETIM 9.0

EC001288

### UNSPSC

UNSPSC 21.0

39131500

# PMST (9X38) BU - Insert label



0830969

<https://www.phoenixcontact.com/us/products/0830969>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)