# E S6 A 260X260X160 - Empty enclosure

0899019

https://www.phoenixcontact.com/us/products/0899019

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Empty enclosure, material: Stainless steel, 316L/1.4404, surface resistance: brushed, silver-colored, 260 mm x 260 mm x 160 mm, type of locking: Screw-on cover, scope of supply - ATD: Mounting panel, Fixing angle with mounting screws, M12 grounding bolts, affixed externally, Installation notes, Mounting panel

## Your advantages

- Innovative product range of high-quality stainless steel housings as the basis for individual terminal boxes
- Reduced assembly and approval effort thanks to ready-equipped terminal boxes
- Flange plates possible on four sides of the housing, including seal protection
- Housing adjustments using threads, bore holes, and rectangular cutouts with consideration given to normative specifications

## Commercial data

| | |
|---|---|
| Item number | 0899019 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | BH91 |
| Product key | BH9112 |
| GTIN | 4046356927772 |
| Weight per piece (including packing) | 4.551 kg |
| Weight per piece (excluding packing) | 4.551 kg |
| Customs tariff number | 94032080 |
| Country of origin | DE |

## Technical data

### Product properties

| | |
|---|---|
| Product type | Terminal box |
| Scope of supply | Mounting panel |
| | Fixing angle with mounting screws |
| | M12 grounding bolts, affixed externally |
| | Installation notes |


Insulation characteristics

| | |
|---|---|
| Protection class | I |

### Electrical properties

| | |
|---|---|
| Maximum power dissipation | 13 W (T6 up to 40 °C) |
| | 8.1 W (T6 up to 55 °C) |
| | 4.8 W (T6 up to 65 °C) |
| | 17.9 W (T5 up to 40 °C) |
| | 13 W (T5 up to 55 °C) |
| | 9.8 W (T5 up to 65 °C) |
| | 21.1 W (T4 up to 40 °C) |
| | 10.2 W (T4 up to 55 °C) |
| | 13 W (T4 up to 65 °C) |

### Dimensions

| | |
|---|---|
| Dimensional drawing |  |
| Width | 260 mm |
| Height | 260 mm |
| Depth | 160 mm |
| Clearance width, maximum DIN rail length | 204 mm |
| Max. material thickness | 1.5 mm |

### Material specifications

| | |
|---|---|
| Color | silver-colored |
| Material | Stainless steel, 316L/1.4404 |
| Seal material | Silicon |
| Surface characteristics | brushed |
| Note | 240 grain |

## Mechanical properties

General

| | |
|---|---|
| Type of locking (GRP) | Screw-on cover Allen screws |

## Environmental and real-life conditions

Degree of protection (IP code)

| | |
|---|---|
| Degree of protection | IP66 |

Ambient conditions


| | |
|---|---|
| Ambient temperature (operation) | -55 °C ... 135 °C |

## Mounting


| | |
|---|---|
| Assembly note | External fixing clips |

## Drawings

Dimensional drawing



Schematic diagram



## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27180101 |
| ECLASS-15.0 | 27180101 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC000261 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 31261500 |

## Environmental product compliance

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |


Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com



Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com