C S6 A 300X400X200 - Junction box

0899140

https://www.phoenixcontact.com/us/products/0899140

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Junction box, with door hinge and quarter turn locking, including mounting panel, without flange plates, material: Stainless steel, 316L/1.4404, surface resistance: brushed, silver-colored, 300 mm x 400 mm x 200 mm, type of locking: Door with replaceable hinge

Your advantages

- Innovative product range of high-quality stainless steel housings as the basis for individual terminal boxes
- Reduced assembly and approval effort thanks to ready-equipped terminal boxes
- Flange plates possible on four sides of the housing, including seal protection
- Housing adjustments using threads, bore holes, and rectangular cutouts with consideration given to normative specifications

Commercial data

Item number	0899140
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BH9112
GTIN	4055626204703
Weight per piece (including packing)	99.99 g
Weight per piece (excluding packing)	99.99 g
Country of origin	DE

Technical data

Product properties

Product type	Terminal box


Insulation characteristics

Protection class	I

Electrical properties

Maximum power dissipation	28 W (T6 up to 40 °C)
	17.5 W (T6 up to 55 °C)
	10.5 W (T6 up to 65 °C)
	38.5 W (T5 up to 40 °C)
	28 W (T5 up to 55 °C)
	21 W (T5 up to 65 °C)
	45.5 W (T4 up to 40 °C)
	21.9 W (T4 up to 55 °C)
	28 W (T4 up to 65 °C)

Dimensions

Dimensional drawing	
Width	300 mm
Height	400 mm
Depth	200 mm
Clearance width, maximum DIN rail length	1088 mm
Max. material thickness	2 mm

Material specifications

Color	silver-colored
Material	Stainless steel, 316L/1.4404
Seal material	Silicon
Surface characteristics	brushed
Note	240 grain

Mechanical properties

General

Type of locking (GRP)	Door with replaceable hinge Quarter turn locking with two-way

	key bit

Environmental and real-life conditions

Degree of protection (IP code)

Degree of protection	IP66

Ambient conditions


Ambient temperature (operation)	-55 °C ... 135 °C

Mounting


Assembly note	External fixing clips

Drawings

Dimensional drawing



Schematic diagram



Classifications

UNSPSC

UNSPSC 21.0	31261502

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com