

# ST 1-SILED 24 - Fuse plug

0920384

<https://www.phoenixcontact.com/us/products/0920384>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fuse plug, nom. voltage: 400 V, nominal current: 10 A, connection method: Plug-in connection, width: 9.9 mm, height: 45.4 mm, color: black

The figure shows a similar product

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 0920384       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BE19          |
| Product key                          | BE1Z3X        |
| GTIN                                 | 4017918010218 |
| Weight per piece (including packing) | 10.209 g      |
| Weight per piece (excluding packing) | 10.209 g      |
| Customs tariff number                | 85369095      |
| Country of origin                    | PL            |

# ST 1-SILED 24 - Fuse plug



0920384

<https://www.phoenixcontact.com/us/products/0920384>

## Technical data

### Product properties

|              |      |
|--------------|------|
| Product type | Fuse |
|--------------|------|

### Electrical properties

|                       |               |
|-----------------------|---------------|
| Nominal current $I_N$ | 10 A          |
| Fuse                  | G / 6,3 x 32  |
| LED voltage range     | 15 V ... 30 V |

### Input data

|                   |               |
|-------------------|---------------|
| LED voltage range | 15 V ... 30 V |
|-------------------|---------------|

### Connection data

|                   |   |
|-------------------|---|
| Connection method | Plug-in connection  |
| Nominal current   | 10 A  |
| Nominal voltage   | 400 V (In the event of a defective fuse, the downstream circuit is not disconnected.) |

### Dimensions

|        |         |
|--------|---------|
| Width  | 9.9 mm  |
| Height | 45.4 mm |

### Material specifications

|   |                  |
|---|------------------|
| Color   | black (RAL 9005) |
| Flammability rating according to UL 94                                  | V2               |
| Insulating material group   | CTI 600          |
| Insulating material   | PA               |
| Static insulating material application in cold                          | -60 °C           |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C           |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C           |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3      |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3      |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3      |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3      |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg         |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed           |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed           |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed           |

### Environmental and real-life conditions

#### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -60 °C ... 105 °C (max. short-term operating temperature RTI) |
|---------------------------------|---|

# ST 1-SILED 24 - Fuse plug

0920384

<https://www.phoenixcontact.com/us/products/0920384>



|  |   |
|--|---|
|  | Elec.)  |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C   |
| Ambient temperature (actuation)          | -5 °C ... 70 °C   |
| Permissible humidity (storage/transport) | 30 % ... 70 %   |

# ST 1-SILED 24 - Fuse plug

0920384

<https://www.phoenixcontact.com/us/products/0920384>



## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/0920384>



**EAC**

Approval ID: RU C-DE.BL08.B.00714

# ST 1-SILED 24 - Fuse plug

0920384

<https://www.phoenixcontact.com/us/products/0920384>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250305 |
| ECLASS-15.0 | 27250305 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC002018 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121600 |
|-------------|----------|

# ST 1-SILED 24 - Fuse plug

0920384

<https://www.phoenixcontact.com/us/products/0920384>



## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

### EF3.1 Climate Change

|         |               |
|---------|---------------|
| CO2e kg | 0.124 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)