

# MINI MCR-2-SPS-24-15 - Constant voltage source



1033202

<https://www.phoenixcontact.com/us/products/1033202>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Constant voltage source with pluggable connection technology for the generation of a highly precise constant voltage of 15 V and for the supply of sensors without internal power supply. Screw connection technology.

## Commercial data

Item number	1033202
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C404
Product key	DK112Z
GTIN	4055626537962
Weight per piece (including packing)	115.4 g
Weight per piece (excluding packing)	106.72 g
Customs tariff number	85437090
Country of origin	DE

# MINI MCR-2-SPS-24-15 - Constant voltage source



1033202

<https://www.phoenixcontact.com/us/products/1033202>

## Technical data

### Notes

#### Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

### Product properties

Product type	Constant voltage source
Product family	MINI Analog Pro

### Electrical properties

Electrical isolation	2-way isolation
Electrical isolation between input and output	yes
Maximum temperature coefficient	< 0.01 %/K
Maximum transmission error	≤ 0.1 % (of final value)

#### Electrical isolation

Overvoltage category	II
Pollution degree	2

#### Electrical isolation Input/output/power supply IEC/EN 61010-1

Standards/regulations	IEC/EN 61010-1
Rated insulation voltage	300 V <sub>rms</sub>
Test voltage	3 kV AC (50 Hz, 60 s)
Insulation	Reinforced insulation

#### Supply

Supply voltage range	9.6 V DC ... 30 V DC (The DIN rail connector (ME 6,2 TBUS-2 1,5/5-ST-3,81 GN, item no. 2869728) can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail in accordance with EN 60715)
Typical current consumption	< 38.2 mA (24 V) < 79.8 mA (12 V)
Power consumption	< 900 mW (9.6 V DC)

### Input data

#### Signal: Voltage

Voltage input signal	9.6 V DC ... 30 V DC
Transmitter supply voltage	15 V DC

### Output data

#### Signal: Voltage

Max. voltage output signal	15 V DC
Short-circuit current	> 35 mA

# MINI MCR-2-SPS-24-15 - Constant voltage source



1033202

<https://www.phoenixcontact.com/us/products/1033202>

Output voltage with wire break	15 V DC
Output current	≤ 30 mA
Ripple	< 20 mV <sub>PP</sub> (600 Ω)

## Connection data

Connection method	Screw connection
Stripping length	10 mm
Screw thread	M3
Conductor cross-section rigid	0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule) 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule)
Conductor cross-section flexible	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross-section AWG	24 ... 12 (flexible)
Tightening torque	0.5 Nm ... 0.6 Nm

## Ex data

Ex installation (EPL)	Gc Div. 2
-----------------------	--------------

## Signaling

Status display	Green LED (supply voltage)
----------------	----------------------------

## Dimensions

Width	6.2 mm
Height	109.81 mm
Depth	119.2 mm

## Material specifications

Color	gray (RAL 7042)
Housing material	PBT
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 2

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20 (not assessed by UL)
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 2000 m
Permissible humidity (operation)	5 % ... 95 % (non-condensing)

## Approvals

### CE

Certificate	CE-compliant
-------------	--------------

# MINI MCR-2-SPS-24-15 - Constant voltage source



1033202

<https://www.phoenixcontact.com/us/products/1033202>

## ATEX

Identification	⊕ II 3 G Ex ec IIC T4 Gc
Certificate	BVS 20 ATEX E 014X

## IECEX

Identification	Ex ec IIC T4 Gc
Certificate	IECEX BVS 20.0010X

## CCC / China-Ex

Identification	Ex ec IIC T4 Gc
Certificate	2026122303128771

## UL, USA/Canada

Identification	UL 508 Listed
	Class I, Div. 2, Groups A, B, C, D T6
	Class I, Zone 2, Group IIC T6

## Shipbuilding approval

Certificate	DNV GL TAA000021E Rev. 1
-------------	--------------------------

## Shipbuilding data

Temperature	B
Humidity	B
Vibration	A
EMC	A
Enclosure	Required protection according to the Rules shall be provided upon installation on board

## EMC data

Electromagnetic compatibility	Conformance with EMC directive
Noise immunity	EN 61000-6-2
Note	When being exposed to interference, there may be minimal deviations.

## Noise emission

Standards/regulations	EN 61000-6-4
-----------------------	--------------

## Standards and regulations

Electrical isolation	2-way isolation
----------------------	-----------------

## GB Standard

Standards/regulations	GB/T 3836.1
	GB/T 3836.3

## Mounting

Mounting type	DIN rail mounting
Assembly note	The DIN rail connector can be used for bridging the supply voltage. It can be snapped onto a 35 mm EN 60715 DIN rail.

# MINI MCR-2-SPS-24-15 - Constant voltage source



1033202

<https://www.phoenixcontact.com/us/products/1033202>

Mounting position	any
-------------------	-----

# MINI MCR-2-SPS-24-15 - Constant voltage source




1033202

<https://www.phoenixcontact.com/us/products/1033202>

## Drawings

Block diagram



# MINI MCR-2-SPS-24-15 - Constant voltage source




1033202

<https://www.phoenixcontact.com/us/products/1033202>


## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1033202>

 **UL Listed**  
Approval ID: E238705


 **cUL Listed**  
Approval ID: E238705


**DNV**  
Approval ID: TAA000021E

 **IECEx**  
Approval ID: IECEx BVS 20.0010X

 **cUL Listed**  
Approval ID: E196811

 **UL Listed**  
Approval ID: E196811

 **ATEX**  
Approval ID: BVS 20 ATEX E 014X

 **CCC**  
Approval ID: 2022122303115966

# MINI MCR-2-SPS-24-15 - Constant voltage source



1033202

<https://www.phoenixcontact.com/us/products/1033202>

## Classifications

### ECLASS

ECLASS-13.0	27210192
ECLASS-15.0	27210192

### ETIM

ETIM 10.0	EC002498
-----------	----------

### UNSPSC

UNSPSC 21.0	39121000
-------------	----------

# MINI MCR-2-SPS-24-15 - Constant voltage source



1033202

<https://www.phoenixcontact.com/us/products/1033202>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol(CAS: 79-94-7)
SCIP	31c27dc5-0c92-4bc8-8361-89e1dc0315c0

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)