

SACC-CIP-M8FSD-4P SMD SH R32 - Contact carrier



1068454

<https://www.phoenixcontact.com/us/products/1068454>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact carrier, Ethernet/PROFINET CAT5 (100 Mbps), 4-position, Socket, straight, M8, D-coding, SMD reflow

Your advantages

- Reduced mounting costs thanks to two-piece device connector
- Packaging available for automated pick and place assembly
- All common pin assignments and codings available
- Easy device integration thanks to mechanical port screw connections with threaded attachment, press-in contour or direct integration in the front plate
- Additional gasket for the device when not plugged in

Commercial data

Item number	1068454
Packing unit	120 pc
Minimum order quantity	100 pc
Sales key	AB22
Product key	ABQHCH
GTIN	4055626801919
Weight per piece (including packing)	5.03 g
Weight per piece (excluding packing)	2.221 g
Customs tariff number	85366990
Country of origin	DE

1068454

<https://www.phoenixcontact.com/us/products/1068454>

Technical data

Notes

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
--------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Product properties

Product type	Contact insert
Application	Data Signal
Sensor type	Ethernet/PROFINET
Number of positions	4
Seal present	yes
Shielded	yes
Coding	D
Thread type	M8

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	1.5 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	50 V AC 60 V DC
Nominal current I_N	4 A
Transmission speed	100 Mbps
Transmission characteristics (category)	CAT5 (IEC 11801:2002)

Connection data

Connection method	SMD reflow
-------------------	------------

Interfaces

Signal type/category	Ethernet/PROFINET CAT5, 100 Mbps
----------------------	----------------------------------

Material specifications

Material Insulating body	PA
Material Contact	CuZn
Material Contact surface	Au
Material Seal	FKM

SACC-CIP-M8FSD-4P SMD SH R32 - Contact carrier



1068454

<https://www.phoenixcontact.com/us/products/1068454>

Flammability rating according to UL 94	V0
----------------------------------------	----

Connector

Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M8
Coding	D

Cable/line

Signal type/category	Ethernet/PROFINET CAT5, 100 Mbps
----------------------	----------------------------------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Degree of protection (when plugged in)	IP67 (correctly plugged in and locked)
Degree of protection	IP67 (correctly plugged in and locked)
Ambient temperature (operation) (male connector/female connector)	-25 °C ... 105 °C
	-40 °C ... 105 °C (without mechanical actuation)

Standards and regulations

Standard designation	M8 circular connector
Standards/specifications	based on IEC 61076-2-114

Packaging specifications

Type of packaging	Belt
-------------------	------

SACC-CIP-M8FSD-4P SMD SH R32 - Contact carrier




1068454

<https://www.phoenixcontact.com/us/products/1068454>

Drawings

Schematic diagram



Pin assignment M8 socket, 4-pos., view female side

SACC-CIP-M8FSD-4P SMD SH R32 - Contact carrier



1068454

<https://www.phoenixcontact.com/us/products/1068454>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1068454>

 cULus Recognized Approval ID: E221474-20160506				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine				
	60 V	4 A	-	-

1068454

<https://www.phoenixcontact.com/us/products/1068454>

Classifications

ECLASS

ECLASS-13.0	27440223
ECLASS-15.0	27440223

ETIM

ETIM 10.0	EC003557
-----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-CIP-M8FSD-4P SMD SH R32 - Contact carrier



1068454

<https://www.phoenixcontact.com/us/products/1068454>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
-----------------------------------------	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com