

PRC 3-HEAD-FS6-1 - Contact carrier



1070198

<https://www.phoenixcontact.com/us/products/1070198>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact carrier, Range of articles: PRC 35, design: Release with tool or by hand (see accessories), housing material: PPE, color: black, number of positions: 3, min. conductor cross-section: 1.5 mm², max. conductor cross-section: 6 mm², rated voltage: 690 V AC, rated current: 35 A, Connection method: Screw connection, Contact insert without connector housing. Please order the appropriate connector housings according to the accessories list.

Your advantages

- Versatile interfaces with straight and angled connector housings
- Universal accommodation of existing connector heads with screw connection technology
- Modular system for optimized storage
- Locking mechanism can be unlocked manually or using a tool
- Ideal for indoor and outdoor use due to weatherproof materials

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1070198 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB03 |
| Product key | ABLCBA |
| GTIN | 4055626749112 |
| Weight per piece (including packing) | 43.3 g |
| Weight per piece (excluding packing) | 28.925 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |

PRC 3-HEAD-FS6-1 - Contact carrier



1070198

<https://www.phoenixcontact.com/us/products/1070198>

Technical data

Notes

| | |
|---------------------|--|
| Order information: | Contact insert without connector housing. Please order the appropriate connector housings according to the accessories list. |
| Note on application | For assembly notes, please refer to the packing slip |

Product properties

| | |
|---------------------|--|
| Product type | Contact insert |
| Product family | PRC 35 |
| Type | Release with tool or by hand (see accessories) |
| Number of positions | 3 |
| Connection profile | 2+PE |
| Coding | AD |

Insulation characteristics

| | |
|---------------------|----|
| Protection class | II |
| Degree of pollution | 2 |

Electrical properties

| | |
|-----------------------------|--|
| Rated voltage (III/2) | 690 V |
| Rated voltage | 690 V AC (III/2.00) in accordance with IEC 61984 |
| | 600 V AC (III/2.00) in accordance with UL 2238/UL 2237, when mounted |
| | 500 V DC (III/2.00) in accordance with IEC 61535, when mounted |
| Rated surge voltage (III/2) | 8 kV |
| Rated current | 35 A (With 6 mm ² conductor cross-section in accordance with IEC 61984) |
| | 35 A (with AWG 10, in accordance with UL 2237) |
| | 32 A (With 6 mm ² conductor cross-section in accordance with IEC 61535) |

Connection data

| | |
|----------------------------------|---|
| Connection method | Screw connection |
| Tightening torque | ... 1 Nm |
| Conductor cross-section flexible | 4 mm ² ... 6 mm ² |
| Conductor cross-section rigid | 1.5 mm ² ... 6 mm ² |

Dimensions

| | |
|--------|---------|
| Width | 35.9 mm |
| Height | 34.5 mm |
| Length | 51.2 mm |

Material specifications

| | |
|-----------------|------------------|
| Color (Housing) | black (RAL 9005) |
|-----------------|------------------|

PRC 3-HEAD-FS6-1 - Contact carrier



1070198

<https://www.phoenixcontact.com/us/products/1070198>

| | |
|--|-----------------------------------|
| Color of the housing part | black |
| Material Seal | EPDM (Housing seal) |
| Material Contact carrier | PPE |
| Material Contact | CuZn (Contact material, Pb < 0.1) |
| Flammability rating according to UL 94 | V0 |
| Housing material | PPE |
| Contact material | Cu alloy |
| Contact surface material | silver-plated |
| O-ring material | EPDM |

Cable/line

| | |
|---|---------------------------------------|
| Single wire, cross section | 1.5 mm ² 6 mm ² |
| Stripping length of the individual wire | 12 mm (Lay PE conductor 8 mm leading) |
| Halogen-free | yes |

Mechanical properties

Mechanical data

| | |
|-----------------------------|---|
| Insertion/withdrawal cycles | 2000 (Test specification: IEC 60512-13-2) |
|-----------------------------|---|

Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection | IP66/IP68 (2 m / 24 h) IP69K (when mounted) IP66/IP68 (2 m / 24 h) IP69K |
| Category of shock impact | IK08 (-25°C) |
| Ambient temperature (operation) | -40 °C ... 105 °C (dependent on the derating curve) |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Ambient temperature (assembly) | -5 °C ... 85 °C |

PRC 3-HEAD-FS6-1 - Contact carrier


1070198

<https://www.phoenixcontact.com/us/products/1070198>



Drawings

Schematic diagram



Connector pin assignment

PRC 3-HEAD-FS6-1 - Contact carrier



1070198

<https://www.phoenixcontact.com/us/products/1070198>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1070198>



cUL Recognized
Approval ID: E468743-20200116



UL Recognized
Approval ID: E468743-20200116



VDE Zeichengenehmigung
Approval ID: 40054228

| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine | | | | |
| | 320 V | 32 A | - | - |



VDE Zeichengenehmigung
Approval ID: 40054231

| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine | | | | |
| | 690 V | 35 A | - | - |

PRC 3-HEAD-FS6-1 - Contact carrier



1070198

<https://www.phoenixcontact.com/us/products/1070198>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27440605 |
| ECLASS-15.0 | 27440605 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC002560 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

PRC 3-HEAD-FS6-1 - Contact carrier



1070198

<https://www.phoenixcontact.com/us/products/1070198>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Triphenyl phosphate(CAS: 115-86-6) |
| SCIP | 1f654d32-803c-44e4-98b8-9b72ba263bbf |

EF3.1 Climate Change

| | |
|---------|---------------|
| CO2e kg | 0.433 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com