

SAC-2P-10,0-PVC/A-1L-Z - Sensor/actuator cable



1075471

<https://www.phoenixcontact.com/us/products/1075471>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 2-position, PVC, black, free cable end, on Valve connector A, with 1 LED, Wiring: Z diode, cable length: 1.5 m

The figure shows the standard version with 2+PE

Commercial data

Item number	1075471
Packing unit	1 pc
Minimum order quantity	100 pc
Note	Made to order (non-returnable)
Product key	AF1DAA
GTIN	4055626781136
Weight per piece (including packing)	357 g
Weight per piece (excluding packing)	352 g
Country of origin	PL

SAC-2P-10,0-PVC/A-1L-Z - Sensor/actuator cable



1075471

<https://www.phoenixcontact.com/us/products/1075471>

Technical data

Product properties

Product type	Sensor/actuator cable with valve connector
Number of positions	2
No. of cable outlets	1
Shielded	no

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	V0
Seal material	TPU
Material housing valve plug	TPU
Contact material	CuSn
Valve plug contact insert material	PA 6.6
Contact surface material	Sn

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	24 V AC
	24 V DC
Nominal current I_N	4 A

Signaling

Status display	1 LED
Status display present	yes

Connector

Connection 1

Type	free cable end
------	----------------

Connection 2

Type	Valve connector A
Number of positions	2
Material	CuSn (Contact)
	Sn (Contact surface)
	PA 6.6 (Contact carrier)
	TPU (Housing)
Protective circuit	Z diode

Cable/line

SAC-2P-10,0-PVC/A-1L-Z - Sensor/actuator cable




1075471

<https://www.phoenixcontact.com/us/products/1075471>

Cable length	1.5 m
--------------	-------

PVC black [PVC]

Dimensional drawing	
Cable weight	34.9 kg/km
UL AWM Style	2464
Number of positions	2
Shielded	no
Cable type	PVC black [PVC]
Conductor structure signal line	16x 0.20 mm
AWG signal line	20
Conductor cross-section	2x 0.5 mm ²
Wire diameter incl. insulation	1.5 mm ±0.05 mm
External cable diameter	4.80 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	black
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue
Max. conductor resistance	39 Ω/km (at 20 °C)
Insulation resistance	≥ 20 MΩ*km
Nominal voltage, cable	300 V
Test voltage	1200 V
Minimum bending radius, fixed installation	5 x D
Smallest bending radius, fixed installation	24 mm
Flame resistance	according to DIN VDE 0482 According to DIN EN 50265-2-1
Resistance to oil	largely oil-resistant
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 IP67
Ambient temperature (operation) (Valve connector)	-20 °C ... 85 °C (Valve connector)

SAC-2P-10,0-PVC/A-1L-Z - Sensor/actuator cable



1075471

<https://www.phoenixcontact.com/us/products/1075471>

Standards and regulations

Standard designation	Valve connector
Standards/specifications	EN 175301-803

SAC-2P-10,0-PVC/A-1L-Z - Sensor/actuator cable

1075471

<https://www.phoenixcontact.com/us/products/1075471>

Drawings

Dimensional drawing



Valve connector, type A

Dimensional drawing



Valve connector, type A, side view

1075471

<https://www.phoenixcontact.com/us/products/1075471>

Schematic diagram



Valve connector pin assignment, type A

Circuit diagram



Contact assignment of the valve plug

SAC-2P-10,0-PVC/A-1L-Z - Sensor/actuator cable



1075471

<https://www.phoenixcontact.com/us/products/1075471>

Classifications

ECLASS

ECLASS-13.0	27060312
ECLASS-15.0	27060312

ETIM

ETIM 10.0	EC001855
-----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SAC-2P-10,0-PVC/A-1L-Z - Sensor/actuator cable



1075471

<https://www.phoenixcontact.com/us/products/1075471>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Diboron trioxide(CAS: 1303-86-2)
	Lead monoxide (lead oxide)(CAS: 1317-36-8)
SCIP	c448c55b-b147-4b61-a5a3-4cb75bc49959

EF3.1 Climate Change

CO2e kg	6.853 kg CO2e
---------	---------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com