

# FOC-17S24-LCD12-GF03/2 - Connecting cable



1087110

<https://www.phoenixcontact.com/us/products/1087110>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M17 series with preassembled FO socket assembly: 24-pos. M17 socket, LC duplex on the other end, 2 m long, multimode fiberglass G62.5/125 µm OM1, IP67 degree of protection after being inserted, fixed installation for indoor use

## Your advantages

- Prefabricated FO connection assembly, no fusion splicing required on site, plug and play

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1087110       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | AB15          |
| Product key                          | ABNHBB        |
| GTIN                                 | 4055626882079 |
| Weight per piece (including packing) | 139 g         |
| Weight per piece (excluding packing) | 139 g         |
| Customs tariff number                | 85367000      |
| Country of origin                    | CN            |

1087110

<https://www.phoenixcontact.com/us/products/1087110>

## Technical data

### Product properties

|                     |                         |
|---------------------|-------------------------|
| Product type        | Data cable preassembled |
| Number of positions | 24                      |

### Electrical properties

|                     |                       |
|---------------------|-----------------------|
| Transmission medium | Multi-mode fiberglass |
|---------------------|-----------------------|

### Material specifications

|  |      |
|--|------|
| Flammability rating according to UL 94 | V0   |
| Outer sheath, material                 | LSZH |

### Connector

#### Connection 1

|                      |           |
|----------------------|-----------|
| Degree of protection | IP65/IP67 |
|----------------------|-----------|

#### Connection 2

|                      |      |
|----------------------|------|
| Degree of protection | IP20 |
|----------------------|------|

### Cable/line

|   |                          |
|---|--------------------------|
| Cable length                                | 2 m                      |
| Cable type                                  | Fiberglass               |
| Cable type                                  | Fan out                  |
| Outer sheath, material                      | LSZH                     |
| Smallest bending radius, fixed installation | 30 mm                    |
| Halogen-free                                | according to IEC 60754-1 |

#### FO cable

|             |                                  |
|-------------|----------------------------------|
| Fiber       | 62.5/125 µm OM1                  |
| Fiber type  | Multimode fiberglass 62.5/125 µm |
| Attenuation | < 1.5 dB (1300 nm)               |

# FOC-17S24-LCD12-GF03/2 - Connecting cable



1087110

<https://www.phoenixcontact.com/us/products/1087110>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1087110>



**EAC**

Approval ID: 19060508

# FOC-17S24-LCD12-GF03/2 - Connecting cable



1087110

<https://www.phoenixcontact.com/us/products/1087110>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060307 |
| ECLASS-15.0 | 27060307 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC001855 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# FOC-17S24-LCD12-GF03/2 - Connecting cable



1087110

<https://www.phoenixcontact.com/us/products/1087110>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)