

# IPD PL CAP W32 WP GY - Protective cap

1088711

<https://www.phoenixcontact.com/us/products/1088711>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Protective cap, IPD, with locking element, IP66, IP68, IP69K, width: 32 mm, color: gray, for IPD P 5P2,5..., for IPD W 5P2,5..., IPD H 5P,5..., IPD Y 5P2,5

## Your advantages

- Easy distribution of power, as components are plugged directly
- Simple, time-saving wiring in the field with Push-Lock connection
- Reliable installation in harsh environments with IP66, IP68, and IP69K throughout the entire system
- Secure, tool-free locking even in particularly difficult installation situations
- Fast commissioning with preassembled cable assemblies

## Commercial data

Item number	1088711
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF51
Product key	AF6ZBX
GTIN	4055626891255
Weight per piece (including packing)	16.4 g
Weight per piece (excluding packing)	16 g
Customs tariff number	39269097
Country of origin	DE

# IPD PL CAP W32 WP GY - Protective cap



1088711

<https://www.phoenixcontact.com/us/products/1088711>

## Technical data

### Product properties

Product type	Protective cap
Product family	IPD
Retaining cord present	no

### Insulation characteristics

Degree of pollution	3
---------------------	---

### Dimensions

Width	32 mm
-------	-------

### Material specifications

Color	light gray (RAL 7035)
Material Protective cap	PA
Material Seal	NBR
Flammability rating according to UL 94	V0

### Cable/line

Halogen-free	yes
--------------	-----

### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	50
-----------------------------	----

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66
	IP68 (2 m / 24 h)
	IP69K
Ambient temperature (operation)	-30 °C ... 100 °C
Resistance to UV radiation	yes

### Mounting

Mounting type	<ul style="list-style-type: none"><li>• Position the protective cap centrally in front of the counterpart. The Phoenix Contact logo must be at the top on both mating elements. Make sure that the coding pin is located outside the pin connector pattern.</li><li>• The connection is coded and only snaps into place in one position. The rotary element automatically locks the connection and reaches its starting position again.</li><li>• The STS KN6031 2,2x6 thermoplastic screw (or similar items) can be used in the bore hole provided (torque: 0.2 Nm) to secure the protective cap to an IPD panel feed-through.</li></ul>
---------------	---

# IPD PL CAP W32 WP GY - Protective cap



1088711

<https://www.phoenixcontact.com/us/products/1088711>

## Assembly note

- Position the protective cap centrally in front of the counterpart. The Phoenix Contact logo must be at the top on both mating elements. Make sure that the coding pin is located outside the pin connector pattern.
- The connection is coded and only snaps into place in one position. The rotary element automatically locks the connection and reaches its starting position again.
- Make sure that the inside of the protective cap is clean and dry before fitting it.
- The self-locking rotary elements of the IPD PL CAP... protective cap and the IPD PL... connector are provided with a coding pin. Make sure not to damage the coding pin.

# IPD PL CAP W32 WP GY - Protective cap



1088711

<https://www.phoenixcontact.com/us/products/1088711>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1088711>



**VDE Zeichengenehmigung**

Approval ID: 40059408



**cULus Listed**

Approval ID: E468743

# IPD PL CAP W32 WP GY - Protective cap



1088711

<https://www.phoenixcontact.com/us/products/1088711>

## Classifications

### ECLASS

ECLASS-13.0	27440691
ECLASS-15.0	27440691

### ETIM

ETIM 10.0	EC002863
-----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# IPD PL CAP W32 WP GY - Protective cap



1088711

<https://www.phoenixcontact.com/us/products/1088711>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)