SOL-ES-BSC-PYR - Sensor

1093211

https://www.phoenixcontact.com/us/products/1093211

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Hukseflux Thermal Sensors B.V. pyranometer for measuring the irradiation intensity in W/m^2 with a 180° aperture opening. The measured value is provided via Modbus/RTU (RS-485). Corresponds to the accuracy class “First Class” in accordance with ISO 9060.

Product description

All “Solarline Environment Sensors” (SOL-ES) are accessories for the Phoenix Contact weather station. They are especially suitable for capturing weather data in photovoltaic systems.

Corresponding mounting material is available as accessories.

Your advantages

- Includes ISO 9060 testing certificates for the classification First Class
- Corresponds to IEC 61724-1, Class B
- Efficient calibration and maintenance organization

Commercial data

Item number	1093211
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DTHAAA
GTIN	4055626911359
Weight per piece (including packing)	700 g
Weight per piece (excluding packing)	700 g
Country of origin	DE

Technical data

Notes

Note regarding documentation	For technical data, refer to the product documentation in the “Downloads” area

Product properties

Product type	Sensor

Classifications

ECLASS

ECLASS-13.0	27143137
ECLASS-15.0	27143137

ETIM

ETIM 10.0	EC000926

UNSPSC

UNSPSC 21.0	43201500

Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com