# PSR-M-EF3-SDI12-MAT-PI - Extension module

1104884

https://www.phoenixcontact.com/us/products/1104884

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

CRA-READY



Safe extension module with 12 safe inputs for monitoring safety shut-off mats and switching strips, TBUS interface, up to SIL 3, Cat. 4/PL e, pluggable Push-in terminal block, TBUS connector included

## Product description

The configurable and individually scalable PSRmodular safety system is a flexible safety solution for monitoring your machine or system. The safe extension module provides the system with additional safe inputs to monitor safety shut-off mats and switching capacity.

## Your advantages

- Cost-effective safety solution with a high level of adaptability to individual requirements
- Fast startup, thanks to easy hardware and software configuration
- Machine downtimes minimized with comprehensive, easy-to-understand diagnostics
- Tool-free and time-saving installation thanks to Push-in technology
- Low housing width of just 22.6 mm
- Up to Cat. 4/PL e in accordance with ISO 13849-1, SIL 3 in accordance with EN IEC 62061, SIL 3 in accordance with IEC 61508
- Suitable for elevator applications in accordance with EN 81-20

ELEKTROGERÄTE RÜCKNAHME

## Commercial data

| | |
|---|---|
| Item number | 1104884 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | DN02 |
| Product key | DNA362 |
| GTIN | 4055626973067 |
| Weight per piece (including packing) | 171.4 g |
| Weight per piece (excluding packing) | 141 g |
| Customs tariff number | 85371098 |
| Country of origin | IT |

# Technical data

## Notes

| | |
|---|---|
| Note on application | Only for industrial use |
| Note on application | As things stand now, we are preparing the product so that, as of December 11, 2027, it will comply with the requirements of the EU Cyber Resilience Act (CRA) based on the information currently available regarding the CRA. |

## Product properties

| | |
|---|---|
| Product type | Safety device |
| Application | Emergency stop |
| | Light grid |
| | Safety door |
| | Safety shut-off mats |
| | Switching capacities |
| Control | 1 and 2 channel |
| Special properties | The product is being prepared for compliance with the Cyber Resilience Act (CRA) |

### Insulation characteristics

| | |
|---|---|
| Protection class | III |

### Insulation characteristics

| | |
|---|---|
| Overvoltage category | II |
| Degree of pollution | 2 |

### Times

| | |
|---|---|
| Response time | see user manual |
| Restart time | min. 5 s (Boot time) |
| | max. 10 s (Boot time) |

## Electrical properties

| | |
|---|---|
| Maximum power dissipation for nominal condition | 4.28 W (with max. permissible load) |
| Nominal operating mode | 100% operating factor |
| Interfaces | DIN rail TBUS for connection to the master module, supplied as standard |
| Rated surge voltage/insulation | Basic insulation 4 kV between 24 V power supply and I/Os to the housing |

### Supply

| | |
|---|---|
| Designation | A1/A2 |
| Rated control circuit supply voltage $U_S$ | 19.2 V DC ... 28.8 V DC |
| Rated control circuit supply voltage $U_S$ | 24 V DC -20 % / +20 % (external fuse, typically 4 A) |
| Rated control supply current $I_S$ | typ. 53 mA |
| Power consumption at $U_S$ | typ. 1.27 W |
| Inrush current | < 2 A ($\Delta t$ = 1.5 ms at $U_s$) |

| | |
|---|---|
| Filter time | typ. 10 ms (at A1 in the event of voltage dips at $U_s$) |
| Protective circuit | Serial protection against polarity reversal |

## Input data

Digital: IN1, IN2, IN3, IN4, IN5, IN6, IN7, IN8, IN9, IN10, IN11, IN12

| | |
|---|---|
| Description of the input | Safety-related digital inputs |
| | IEC 61131-2 Type 2 |
| Number of inputs | 12 |
| Input voltage range "0" signal | 0 V DC ... 5 V DC |
| Input voltage range "1" signal | 11 V DC ... 28.8 V DC |
| Input current range "0" signal | < 1 mA |
| Filter time | min. 3 ms ±2 ms (adjustable) |
| | max. 250 ms ±2 ms (adjustable) |
| | Test pulse rate ≥ 2x set filter time, min. Test pulse rate = 10 ms |
| Cable length | max. 100 m (per input) |
| Max. permissible overall conductor resistance | max. 1.2 kΩ (Input and reset circuit at $U_S$) |
| Current consumption | typ. 7.5 mA (typ. with $U_S$) |
| | max. 9.5 mA (at a control voltage of 28.8 V DC) |

## Output data

Clock: T1, T2, T3, T4, T5, T6, T7, T8

| | |
|---|---|
| Output description | PNP, IEC 61131-2 Typ 0,1 |
| Number of outputs | 8 |
| Voltage | 24 V DC (via A1) |
| Output voltage when switched off | max. 0.1 V |
| Maximum inrush current | 1.1 A (Δt = 3 s at $U_s$) |
| Limiting continuous current | 100 mA (per channel) |
| | 800 mA (Total current of all outputs) |
| Leakage current | max. 100 µA |
| Test pulses | ≤ 200 µs (Test pulse duration) |
| | Test pulse rate = 8 x $t_{Cycle}$ [ms] |
| Short-circuit protection | Yes (self-limitation at 1.1 A) |
| Cable length | max. 100 m (per output) |
| Max. capacitive load | max. 470 nF |
| Max. inductive load | max. 2.4 mH |
| Discharging circuit | Yes, internal |

## Connection data

Connection technology

| | |
|---|---|
| pluggable | yes |

Conductor connection

| | |
|---|---|
| Connection method | Push-in connection |

| | |
|---|---|
| Conductor cross-section rigid | 0.2 mm² ... 2.5 mm² |
| Conductor cross-section flexible | 0.2 mm² ... 2.5 mm² |
| Conductor cross-section AWG | 24 ... 14 |
| Stripping length | 10 mm |

## Signaling

| | |
|---|---|
| Status display | 1 x LED (green), 2 x LED (orange) |
| | 12 x LED (yellow) |
| Operating voltage display | 1 x LED (green) |
| Error indication | 2 x LED (red) |

## Dimensions

| | |
|---|---|
| Width | 22.61 mm |
| Height | 107.74 mm |
| Depth | 113.6 mm |

## Material specifications

| | |
|---|---|
| Color (Housing) | yellow (RAL 1018) |
| Housing material | Polyamide PA non-reinforced |

## Characteristics

### Safety data

| | |
|---|---|
| Stop category (EN 60204-1) | 0 |

### Safety data: EN ISO 13849

| | |
|---|---|
| Performance level (PL) | e (2-channel wiring) |
| | d (1-channel wiring) |

### Safety data: IEC 61508 - High-demand for 2-channel wiring

| | |
|---|---|
| Safety Integrity Level (SIL) | 3 |

### Safety data: IEC 61508 - High-demand for 1-channel wiring

| | |
|---|---|
| Safety Integrity Level (SIL) | 2 |

### Safety data: EN IEC 62061

| | |
|---|---|
| Safety Integrity Level (SIL) | 3 (2-channel wiring) |
| | 2 (1-channel wiring) |

## Environmental and real-life conditions

### Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 |
| Min. degree of protection of inst. location | IP54 |
| Ambient temperature (operation) | -10 °C ... 55 °C (observe derating) |
| Ambient temperature (storage/transport) | -20 °C ... 85 °C |
| Maximum altitude | ≤ 2000 m (Above sea level) |

| | |
|---|---|
| Max. permissible humidity (storage/transport) | 95 % (non-condensing) |
| Max. permissible relative humidity (operation) | 95 % (non-condensing) |
| Shock | 10g for Δt = 16 ms (continuous shock, 1000 shocks in each space direction) |
| Vibration (operation) | 10 Hz ... 150 Hz, 2g |

## Approvals

CE


| | |
|---|---|
| Identification | CE-compliant |

## Mounting


| | |
|---|---|
| Mounting type | DIN rail mounting |
| Assembly note | Observe derating |
| Mounting position | vertical or horizontal |

## Drawings

Application drawing




Block diagram




Block diagram

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1104884

**cULus Listed**
Approval ID: E238705

**Functional Safety**
Approval ID: Z10029429 0013Rev.02

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27371819 |
| ECLASS-15.0 | 27371819 |
| ECLASS-15.0 ASSET | 27250101 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC001449 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39122200 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |


Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com



Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com