
# FOC-LC:AA-LC:AA-OS2:D01/1 - FO patch cable

1115630

https://www.phoenixcontact.com/us/products/1115630

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Single-mode OS2 duplex jumper, LC-LC, APC polishing, length 1 m



## Your advantages

- Glass fiber optical, 8-shaped FO cable jumper
- Singlemode patch cable for indoor installation
- Excellent mechanical and optical properties
- Indoor use, suitable for FO distribution and termination devices
- Made of halogen-free flame-retardant material, RoHS compliant
- All components satisfy UL 94, V0
- Satisfies industry standards for optical and mechanical properties
- Insertion loss ≤0.5 dB (varies depending on the condition)
- Connector with UPC polishing for optimum attenuation values

## Commercial data

| | |
|---|---|
| Item number | 1115630 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB16 |
| Product key | ABNIBC |
| GTIN | 4063151039387 |
| Weight per piece (including packing) | 19.7 g |
| Weight per piece (excluding packing) | 19.7 g |
| Customs tariff number | 85447000 |
| Country of origin | CN |

# Technical data

## Product properties

| | |
|---|---|
| Product type | Data cable preassembled |
| Number of positions | 2 |

## Electrical properties

| | |
|---|---|
| Transmission medium | FO |
| Transmission speed | 100 Gbps |
| Transmission speed | 100 GBit/s |

## Mechanical properties

| | |
|---|---|
| Tensile strength short-term/long-term | 70 N |

### Mechanical data

| | |
|---|---|
| Insertion/withdrawal cycles | ≥ 500 |

## Material specifications

| | |
|---|---|
| Flammability rating according to UL 94 | V0 |
| Outer sheath, material | LSZH |

## Dimensions

### External dimensions

| | |
|---|---|
| External diameter min. | 2.00 mm |
| External diameter max. | 4.00 mm |

## Connector

### Connection 1

| | |
|---|---|
| Type | Plug straight LC/APC 8° / IP20 |
| Degree of protection | IP20 |

### Connection 2

| | |
|---|---|
| Type | Plug straight LC / IP20 |
| Degree of protection | IP20 |

## Cable/line

| | |
|---|---|
| Cable length | 1 m |
| Cable weight | 5.3 kg/km |
| Cable type | FO duplex cable |
| Cable type | Zip cord |
| Cable abbreviation | I-V(ZN)H |
| Outer sheath, material | LSZH |
| External sheath, color | yellow |
| Single wire, number of litz wires | 2 |

| | |
|---|---|
| Individual wire diameter | 900 µm |
| Bending radius, long-term | 50.00 mm |
| Bending radius short term/long term | 30.00 mm |
| Smallest bending radius, fixed installation | 30 mm |
| Smallest bending radius, movable installation | 16 mm |
| Tensile strength short-term/long-term | 70 N |
| Lateral pressure, long-term | 100.00 N/cm |
| Halogen-free | complying with IEC 60754-1/2 |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |
| Concentration of fumes | in accordance with IEC 61034 |
| Flame resistance | yes |
| Behavior in fire | No corrosive or toxic fumes |

FO cable

| | |
|---|---|
| Fiber | Fiberglass |
| Fiber type | Single mode fiberglass, 9/125 µm |
| Attenuation | < 0.5 dB/km (1310 nm) |
| Return Loss | ≥ 60 dB |
| Transmission medium | Single-mode fiberglass |

## Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 60 °C |
| Ambient temperature (assembly) | -20 °C ... 60 °C |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |

## Standards and regulations

| | |
|---|---|
| Behavior in fire | No corrosive or toxic fumes |
| Flame resistance | yes |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |
| Concentration of fumes | in accordance with IEC 61034 |
| Standards/specifications | IEC 61300-3-4 |
| | RL: IEC 61300-3-6 |

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27061003 |
| ECLASS-15.0 | 27061003 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC002700 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 26121600 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

EF3.1 Climate Change

| | |
|---|---|
| CO2e kg | 5.403 kg CO2e |


Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com



Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com