

PRC 5-CA-M-H07-4-5,0 - Connecting cable



1150677

<https://www.phoenixcontact.com/us/products/1150677>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connecting cable, Range of articles: PRC 35, color: black, number of positions: 5, rated voltage: 690 V AC, rated current: 32 A, Connection method: Screw connection, This item is also available with other cable lengths. For your specific requirements, please contact your local PHOENIX CONTACT subsidiary.

Your advantages

- Time savings of 80% for startup with Plug and Play
- Locking mechanism can be unlocked manually or using a tool
- Suitable for applications in atmospheres containing salt and in direct sunlight
- Ideal for indoor and outdoor use due to weatherproof materials

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1150677 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB03 |
| Product key | ABL CDA |
| GTIN | 4063151147952 |
| Weight per piece (including packing) | 2,351 g |
| Weight per piece (excluding packing) | 2,115.216 g |
| Customs tariff number | 85444290 |
| Country of origin | PL |

PRC 5-CA-M-H07-4-5,0 - Connecting cable



1150677

<https://www.phoenixcontact.com/us/products/1150677>

Technical data

Notes

| | |
|--------------------|---|
| Order information: | This item is also available with other cable lengths. For your specific requirements, please contact your local PHOENIX CONTACT subsidiary. |
|--------------------|---|

Product properties

| | |
|---------------------|------------------------------|
| Product type | Assembled installation cable |
| Product family | PRC 35 |
| Number of positions | 5 |
| Connection profile | 4+PE |
| Coding | AD |

Insulation characteristics

| | |
|---------------------|----|
| Protection class | II |
| Degree of pollution | 2 |

Electrical properties

| | |
|-----------------------------|---|
| Rated voltage (III/2) | 690 V |
| Rated voltage | 690 V AC (III/2.00) in accordance with IEC 61984 |
| | 600 V AC (III/2.00) In accordance with UL 2238 |
| | 500 V AC / DC (III/2.00) in accordance with IEC 61535, when mounted |
| Rated surge voltage (III/2) | 8 kV |
| Rated current | 32 A (in accordance with IEC 61984) |
| | 25 A (in accordance with IEC 61535) |

Dimensions

| | |
|--------|---------|
| Width | 37.6 mm |
| Height | 37.6 mm |
| Length | 5 m |

Material specifications

| | |
|--|-----------------------------------|
| Color | black |
| Color of the housing part | black |
| Material Seal | EPDM (Cable seal) |
| | EPDM (Housing seal) |
| Material Housing | PPE |
| Material Contact carrier | PPE |
| Material Cable gland | PPE |
| Material Contact | CuZn (Contact material, Pb < 0.1) |
| Flammability rating according to UL 94 | V0 |
| Contact material | Cu |
| Contact surface material | silver-plated |

PRC 5-CA-M-H07-4-5,0 - Connecting cable



1150677

<https://www.phoenixcontact.com/us/products/1150677>

Environmental and real-life conditions

Ambient conditions

| | |
|---|-----------------|
| Ambient temperature (operation) | 30 °C ... 60 °C |
| Ambient temperature (storage/transport) | 30 °C ... 60 °C |
| Ambient temperature (assembly) | 5 °C ... 60 °C |

PRC 5-CA-M-H07-4-5,0 - Connecting cable



1150677

<https://www.phoenixcontact.com/us/products/1150677>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27440604 |
| ECLASS-15.0 | 27440604 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC002587 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

PRC 5-CA-M-H07-4-5,0 - Connecting cable



1150677

<https://www.phoenixcontact.com/us/products/1150677>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Triphenyl phosphate(CAS: 115-86-6) |
| SCIP | e8ba0291-3190-4502-bfe5-e9171b4b7d82 |

EF3.1 Climate Change

| | |
|---------|---------------|
| CO2e kg | 5.608 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com