

# SAC-3P-M12MRS/ 2,0-PUR PE - Power cable



1176069

<https://www.phoenixcontact.com/us/products/1176069>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 3-position, PUR halogen-free, black, Plug angled M12, coding: S, on free cable end, cable length: 2 m, For alternating current up to 16 A/250 V

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Protection against incorrect connection using special S-coding

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1176069                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BF05                           |
| Product key                          | AF1CCP                         |
| GTIN                                 | 4063151206550                  |
| Weight per piece (including packing) | 167.72 g                       |
| Weight per piece (excluding packing) | 22.22 g                        |
| Customs tariff number                | 85444290                       |
| Country of origin                    | PL                             |

# SAC-3P-M12MRS/ 2,0-PUR PE - Power cable



1176069

<https://www.phoenixcontact.com/us/products/1176069>

## Technical data

### Product properties

|                      |               |
|----------------------|---------------|
| Product type         | Power cable   |
| Application          | Energy supply |
| Number of positions  | 3             |
| No. of cable outlets | 1             |
| Shielded             | no            |
| Coding               | S             |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Material specifications

|  |                              |
|--|------------------------------|
| Flammability rating according to UL 94 | V0                           |
| Material of grip body                  | PP                           |
| Contact material                       | CuZn                         |
| Contact surface material               | Ni/Au                        |
| Contact carrier material               | PA                           |
| Material for screw connection          | Zinc die-cast, nickel-plated |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 690 V AC                   |
| Nominal current $I_N$ | 16 A                       |

### Mechanical properties

#### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | > 100 |
|-----------------------------|-------|

### Connector

#### Connection 1

|             |                 |
|-------------|-----------------|
| Type        | Plug angled M12 |
| Coding type | S (Power)       |

#### Connection 2

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

### Cable/line

|              |     |
|--------------|-----|
| Cable length | 2 m |
|--------------|-----|

PUR black [PUR]

# SAC-3P-M12MRS/ 2,0-PUR PE - Power cable



1176069

<https://www.phoenixcontact.com/us/products/1176069>

|   |  |
|---|--|
| Dimensional drawing                           |    |
| Cable weight                                  | 74 kg/km   |
| UL AWM Style                                  | 20233 / 10493 (80°C/300 V)   |
| Number of positions                           | 3  |
| Shielded                                      | no   |
| Cable type                                    | PUR black [PUR]  |
| Conductor structure, voltage supply           | 78x 0.15 mm  |
| AWG power supply                              | 16   |
| Conductor cross-section                       | 3x 1.5 mm <sup>2</sup>   |
| Wire diameter incl. insulation                | 2.25 mm ±0.05 mm   |
| External cable diameter                       | 6.80 mm ±0.2 mm  |
| Outer sheath, material                        | PUR  |
| External sheath, color                        | black  |
| Conductor material                            | Bare Cu litz wires   |
| Material wire insulation                      | PP   |
| Single wire, color                            | black 1, black 2, green/yellow   |
| Overall twist                                 | 3 wires, twisted   |
| Max. conductor resistance                     | ≤ 14.1 Ω/m (at 20 °C)  |
| Insulation resistance                         | ≥ 1 GΩ*km (at 20 °C)   |
| Nominal voltage, cable                        | 300 V AC   |
| Test voltage                                  | 3000 V   |
| Minimum bending radius, fixed installation    | 5 x D  |
| Minimum bending radius, flexible installation | 10 x D   |
| Smallest bending radius, fixed installation   | 34 mm  |
| Smallest bending radius, movable installation | 68 mm  |
| Dynamic load capacity (bending)               | Max. bending cycles: 4000000, Bending radius: 10 x D, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s <sup>2</sup> |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815<br>in accordance with DIN EN 50267-2-1  |
| Flame resistance                              | According to UL 758/1581 (Cable Flame)<br>according to UL 758/1581 FT1<br>According to DIN EN 60332-1-2                                |
| Resistance to oil                             | according to DIN EN 60811-404, 168 h at 100 °C   |
| Other resistance                              | Hydrolysis and microbe resistant as per VDE 0282 section 10<br>Low adhesion<br>abrasion-resistant                                      |

# SAC-3P-M12MRS/ 2,0-PUR PE - Power cable



1176069

<https://www.phoenixcontact.com/us/products/1176069>

|                                 |   |
|---------------------------------|---|
|                                 | Resistant to salt water                         |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation)    |
|                                 | -25 °C ... 80 °C (Cable, flexible installation) |

## Environmental and real-life conditions

### Ambient conditions

|   |  |
|---|--|
| Degree of protection  | IP65   |
|   | IP67 (without preloading, as additional test in accordance with IEC 60529) |
| Ambient temperature (operation) (male connector/female connector) | -25 °C ... 85 °C (Plug / socket)   |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-111 |

# SAC-3P-M12MRS/ 2,0-PUR PE - Power cable

1176069

<https://www.phoenixcontact.com/us/products/1176069>


## Drawings

Dimensional drawing



M12 x 1 male plug, angled

Schematic diagram



Pin assignment of M12 plug, 3-pos., S-coded, view of pin side

# SAC-3P-M12MRS/ 2,0-PUR PE - Power cable



1176069

<https://www.phoenixcontact.com/us/products/1176069>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060327 |
| ECLASS-15.0 | 27060327 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC001855 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-3P-M12MRS/ 2,0-PUR PE - Power cable



1176069

<https://www.phoenixcontact.com/us/products/1176069>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

### EF3.1 Climate Change

|         |               |
|---------|---------------|
| CO2e kg | 8.127 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)