

SACB-10/3-L-PTP-M8 HD - Distributor box



1197625

<https://www.phoenixcontact.com/us/products/1197625>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Distributor box, application: Standard, connection method: M8 socket Metal, number of slots: 10, number of positions: 3, coding: A, slot assignment: single, status display: yes, PNP; master cable connection: plug-in push-in spring connection 180°, shielding: no

Your advantages

- Safety in the field, thanks to molded housing and high degree of protection
- Convenient: increased machine availability thanks to quick and easy diagnostics
- Flexible: distributor box with connector hood for on-site assembly

Commercial data

Item number	1197625
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF40
Product key	AF3BCD
GTIN	4063151366582
Weight per piece (including packing)	262.7 g
Weight per piece (excluding packing)	262.7 g
Customs tariff number	85366990
Country of origin	DE

SACB-10/3-L-PTP-M8 HD - Distributor box



1197625

<https://www.phoenixcontact.com/us/products/1197625>

Technical data

Notes

Assembly note	NOTE: Observe the permissible bending radii when routing cables, since the degree of protection may be at risk if the bending forces are too high. Reduce mechanical loads upstream of the connector, e.g., by using cable ties.
Note on application	Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories".

Product properties

Product type	Distributor box
Application	Standard
Number of positions	3
Number of slots	10
Coding	A
LED	yes

System properties

Local diagnostics

Monitored function	Supply voltage
Optical representation	Green LED

Electrical properties

Max. operating voltage U_{max}	30 V DC
Local diagnostics	Supply voltage Green LED
	Status display I/O Yellow LED
Nominal voltage U_N	24 V DC
Rated current, total	8 A
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	2 A

Connection data

Conductor connection

Sensor/actuator connection system	M8 socket
Conductor cross-section Flexible signal line	0.2 mm ² ... 1.5 mm ²
Conductor cross-section Flexible power supply	0.2 mm ² ... 1.5 mm ²
Connection cross section AWG Flexible signal line	24 ... 16
Connection cross section AWG Flexible power supply	24 ... 16
Stripping length Signal line	10 mm
Stripping length of the sheath	70 mm (Master cable)
Tightening torque, cover screw	1 Nm
Tightening torque of mounting screw for fixing the housing	0.8 Nm

SACB-10/3-L-PTP-M8 HD - Distributor box



1197625

<https://www.phoenixcontact.com/us/products/1197625>

Cable/line

External cable diameter	6 mm ... 12 mm
Connection method	plug-in push-in spring connection

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-25 °C ... 80 °C

Standards and regulations

Standard designation	M8 connector
Standards/specifications	IEC 61076-2-104

SACB-10/3-L-PTP-M8 HD - Distributor box




1197625

<https://www.phoenixcontact.com/us/products/1197625>

Drawings

Dimensional drawing



SACB-10/3-L-PTP-M8 HD - Distributor box

1197625

<https://www.phoenixcontact.com/us/products/1197625>

Schematic diagram




M8 slot, socket, 3-pos.

SACB-10/3-L-PTP-M8 HD - Distributor box

1197625

<https://www.phoenixcontact.com/us/products/1197625>

Schematic diagram



PCB connector positioning - the UN connection is on the end of the connector hood opposite the cable gland


SACB-10/3-L-PTP-M8 HD - Distributor box



1197625

<https://www.phoenixcontact.com/us/products/1197625>

Circuit diagram



SACB-10/3-L-PTP-M8 HD - Distributor box



1197625

<https://www.phoenixcontact.com/us/products/1197625>

Classifications

ECLASS

ECLASS-13.0	27440111
ECLASS-15.0	27440111

ETIM

ETIM 10.0	EC003558
-----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

SACB-10/3-L-PTP-M8 HD - Distributor box



1197625

<https://www.phoenixcontact.com/us/products/1197625>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com