NS 32 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204106

https://www.phoenixcontact.com/us/products/1204106

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, white passivated, G profile, color: silver-colored

Commercial data

Item number	1204106
Packing unit	10 m
Minimum order quantity	20 m
Sales key	BE72
Product key	BE7253
GTIN	4017918106423
Weight per piece (including packing)	1,470 g
Weight per piece (excluding packing)	1,470 g
Customs tariff number	72166190
Country of origin	DE

NS 32 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204106


https://www.phoenixcontact.com/us/products/1204106

Technical data

Product properties

Product type	DIN rail

Dimensions

Dimensional drawing	
Width	32 mm
Depth	15 mm
Length	2000 mm

Material specifications

Color	silver-colored
Material	Steel
Coating	galvanized, white passivated

Standards and regulations

Connection in acc. with standard	IEC / EN
Tests	acc. to EN 60715


Electrical tests

Short-time withstand current

Equivalent E-Cu cross-section	35 mm²
Short-time current resistance 1s	4.2 kA
Max. permissible thermal nominal current for PEN function	125 A

Drawings

Dimensional drawing



Classifications

ECLASS

ECLASS-13.0	27400602
ECLASS-15.0	27400602

ETIM

ETIM 10.0	EC001285

UNSPSC

UNSPSC 21.0	39121700

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

EF3.1 Climate Change

CO2e kg	3.089 kg CO2e

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com