

SACC-CIP-M8FS-6P SMD-SPX - Sample set



1239218

<https://www.phoenixcontact.com/us/products/1239218>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sample set, 6-position, Socket, straight, M8, A-coding, SMD, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

Commercial data

Item number	1239218
Packing unit	5 pc
Minimum order quantity	5 pc
Product key	ABQXAA
GTIN	4063151420048
Weight per piece (including packing)	6.4 g
Weight per piece (excluding packing)	2.173 g
Country of origin	DE

SACC-CIP-M8FS-6P SMD-SPX - Sample set



1239218

<https://www.phoenixcontact.com/us/products/1239218>

Technical data

Notes

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
--------------------	--

Product properties

Product type	Contact insert
Number of positions	6
Seal present	yes
Coding	A
Thread type	M8

Insulation characteristics

Overvoltage category	III
----------------------	-----

Electrical properties

Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\leq 100 \text{ M}\Omega$
Nominal voltage U_N	30 V
Nominal current I_N	1.5 A

Connection data

Connection method	SMD
-------------------	-----

Material specifications

Flammability rating according to UL 94	V0
Seal material	FKM
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA

Connector

Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M8
Coding	A

Environmental and real-life conditions

Ambient conditions

SACC-CIP-M8FS-6P SMD-SPX - Sample set



1239218

<https://www.phoenixcontact.com/us/products/1239218>

Degree of protection (when plugged in)	IP67 (correctly plugged in and locked)
Degree of protection (not plugged in)	IP65 (not plugged in, by means of additional O-ring seal with device)
Ambient temperature (operation) (male connector/female connector)	-25 °C ... 105 °C (Plug / socket)
	-40 °C ... 105 °C (without mechanical actuation)

Standards and regulations

Standard designation	M8 circular connector
Standards/specifications	according to IEC 61076-2-104

SACC-CIP-M8FS-6P SMD-SPX - Sample set


1239218

<https://www.phoenixcontact.com/us/products/1239218>



Drawings

Schematic diagram



Pin assignment M8 socket, 6-pos.

SACC-CIP-M8FS-6P SMD-SPX - Sample set



1239218

<https://www.phoenixcontact.com/us/products/1239218>

Classifications

ECLASS

ECLASS-13.0

27440223

ETIM

ETIM 9.0

EC003557

UNSPSC

UNSPSC 21.0

26121600

SACC-CIP-M8FS-6P SMD-SPX - Sample set



1239218

<https://www.phoenixcontact.com/us/products/1239218>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com