
# FLKM-D37SUB/M/MT/8AO/ETHA - Termination board

1274065

https://www.phoenixcontact.com/us/products/1274065

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE termination board for Siemens SIMATIC® ET 200SP HA, with specific marking, with knife-disconnect terminal block, and test pick-off, as well as power supply terminal blocks

## Commercial data

| | |
|---|---|
| Item number | 1274065 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | C421 |
| Product key | DK218S |
| GTIN | 4063151465896 |
| Weight per piece (including packing) | 240 g |
| Weight per piece (excluding packing) | 200 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

# Technical data

## Product properties

| | |
|---|---|
| Product type | Interface module |
| No. of channels | 8 |

Insulation characteristics: Air clearances and creepage distances

| | |
|---|---|
| Insulation | Functional insulation |
| Overvoltage category | II |
| Pollution degree | 2 |

## Electrical properties

| | |
|---|---|
| Operating voltage (DC) | ≤ 30 V DC |
| Current (per branch) | ≤ 1 A |
| Current (Voltage supply) | ≤ 2 A (per terminal block 1P1/2P1) |

Air clearances and creepage distances

| | |
|---|---|
| Rated insulation voltage | 63 V |
| Rated surge voltage | 0.8 kV (1.2/50 µs) |

Supported controller: SIEMENS ET 200SP HA

| | |
|---|---|
| Suitable I/O module | 6DL1135-6TF00-0PH1 (Terminal Block H1/M1) |

## Connection data

Connection 1 (control level)

| | |
|---|---|
| Connection in acc. with standard | IEC 60807-2 |
| Connection method | D-SUB pin strip |
| Screw thread | UNC 4-40 |
| Number of connections | 1 |
| Number of positions | 37 |
| Insertion/withdrawal cycles | > 500 |
| Pitch | 2.77 mm |

Connection 2 (field level)

| | |
|---|---|
| Connection method | Screw connection with disconnect knife |
| Stripping length | 8 mm |
| Screw thread | M3 |
| Number of positions | 16 |
| Conductor cross-section rigid | 0.2 mm² ... 4 mm² |
| Conductor cross-section rigid (2 conductors with same cross section) | 0.2 mm² ... 1 mm² |
| Conductor cross-section flexible | 0.2 mm² ... 4 mm² |
| | 0.25 mm² ... 2.5 mm² (Ferrule without plastic sleeve) |
| | 0.25 mm² ... 1.5 mm² (Ferrule with plastic sleeve) |
| | 0.2 mm² ... 1 mm² |

| | |
|---|---|
| Conductor cross-section flexible (2 conductors with same cross section) | 0.25 mm² ... 0.75 mm² (Ferrule without plastic sleeve) |
| | 0.5 mm² ... 1 mm² (TWIN ferrule with plastic sleeve) |
| Conductor cross-section AWG | 24 ... 12 |
| Tightening torque | 0.5 Nm ... 0.6 Nm |
| Pitch | 5.08 mm |

Connection 3 (field level)

| | |
|---|---|
| Connection method | Test socket |
| Number of positions | 16 |

Connection 4 (supply)

| | |
|---|---|
| Connection method | Screw connection with disconnect knife |
| Number of connections | 1 |
| Number of positions | 4 |
| Conductor cross-section rigid | 0.2 mm² ... 4 mm² |
| Conductor cross-section flexible | 0.2 mm² ... 4 mm² |
| | 0.25 mm² ... 2.5 mm² (Ferrule without plastic sleeve) |
| | 0.25 mm² ... 1.5 mm² (Ferrule with plastic sleeve) |
| Conductor cross-section AWG | 24 ... 12 |
| Tightening torque | 0.5 Nm ... 0.6 Nm |

## Signaling

| | |
|---|---|
| Status display present | no |

## Dimensions

Item dimensions

| | |
|---|---|
| Width | 101.25 mm |
| Height | 77.03 mm |
| Depth | 50.57 mm |

## Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection (Module) | IP00 |
| Degree of protection (Installation location) | ≥ IP54 |
| Ambient temperature (operation) | -20 °C ... 70 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Altitude | ≤ 2000 m |

## Approvals

UKCA

| | |
|---|---|
| Certificate | UKCA-compliant |

## Standards and regulations

Air clearances and creepage distances

| | |
|---|---|
| Standards/regulations | EN IEC 60664-1 |

## Mounting


| | |
|---|---|
| Mounting type | DIN rail mounting |
| Mounting position | any |

## Notes

| | |
|---|---|
| Notes on operation | For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met. |

## Drawings

Circuit diagram



## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1274065

**cULus Listed**
Approval ID: E238705

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27141152 |
| ECLASS-15.0 | 27141152 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC002780 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121400 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 6(c) |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | 63ce39b1-14db-40ec-b0a3-6df2177757b1 |

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com