

CABLE-FLK14/AXIO/OE/0,14/3,0M - Cable



1369905

<https://www.phoenixcontact.com/us/products/1369905>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Round cable set; controller: Axioline Realtime I/O; connection 1: Single wires (8-position) (The wires are marked and fitted with ferrules); connection 2: IDC/FLK socket strip (1x 14-position); cable length: 3 m

Your advantages

- 8 preassembled open ends, for connection to the Axioline real-time I/O system
- 1:1 connection
- Transmission of groups of 8 channels

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1369905 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | C421 |
| Product key | DK221P |
| GTIN | 4063151726676 |
| Weight per piece (including packing) | 155.2 g |
| Weight per piece (excluding packing) | 157.5 g |
| Customs tariff number | 85444290 |
| Country of origin | DE |

CABLE-FLK14/AXIO/OE/0,14/3,0M - Cable



1369905

<https://www.phoenixcontact.com/us/products/1369905>

Technical data

Product properties

| | |
|--------------|--------------|
| Product type | System cable |
|--------------|--------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|--|
| Degree of protection | IP00 |
| Degree of protection (Installation location) | ≥ IP54 (Installation location) |
| Ambient temperature (operation) (fixed installation) | -40 °C ... 70 °C (fixed installation) |
| Ambient temperature (operation) (flexible installation) | -10 °C ... 70 °C (flexible installation) |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |
| Altitude | ≤ 2000 m |

Electrical properties

| | |
|--------------------------|----------------------------------|
| Operating voltage (AC) | ≤ 30 V AC |
| Operating voltage (DC) | ≤ 60 V DC |
| Nominal operating mode | 100% operating factor |
| Current (Per path, 50°C) | ≤ 1 A (Uncoiled, see derating) |
| Current (Per path, 70°C) | ≤ 0.6 A (Uncoiled, see derating) |

Supported controller: PHOENIX CONTACT Axioline

| | |
|-------------------|--------------------|
| Suitable I/O card | AXL F DI16... |
| | AXL F DI32... |
| | AXL F DI64... |
| | AXL F DO16... |
| | AXL F DO32... |
| | AXL F DO64... |
| | AXL F DI16/DO16... |
| | AXL F DI16/DO8... |
| | AXL SE DI16... |
| | AXL SE DO16... |

Cable/line

| | |
|--------------|-----|
| Cable length | 3 m |
|--------------|-----|

10X0.14 [PVC]

| | |
|---------------------------------|-----------------|
| UL AWM Style | 2464/1061 |
| Number of positions | 10 |
| Shielded | no |
| Cable type | 10X0.14 [PVC] |
| Conductor type | Round cable set |
| Conductor structure signal line | 7x 0.16 mm |
| AWG signal line | 26 |

CABLE-FLK14/AXIO/OE/0,14/3,0M - Cable



1369905

<https://www.phoenixcontact.com/us/products/1369905>


| | |
|---|---|
| Conductor cross-section | 10x 0.14 mm ² |
| Wire diameter incl. insulation | 1 mm ±0.03 mm |
| External cable diameter | 6.10 mm ±0.4 mm |
| Outer sheath, material | Semi-rigid PVC |
| External sheath, color | gray |
| Conductor material | Tin-plated Cu litz wires |
| Cable resistance | ≤ 145 Ω/km (20 °C) |
| Insulation resistance | ≥ 20 MΩ*km (20 °C) |
| Smallest bending radius, fixed installation | 52 mm |
| Smallest bending radius, movable installation | 98 mm |
| Dynamic load capacity (bending) | Max. bending cycles: 5000 |
| Halogen-free | no |
| Flame resistance | IEC 60332-1-2 (raw cable) |
| | VDE 0842, Part 332-1-2 (raw cable) |
| | IEC 60332-3-22 (raw cable) |
| | UL VW-1 |
| | CSA FT-1 |
| Resistance to oil | can withstand occasional splashes (raw cable) |
| Cable type | Cable for one module |

Color code: Single-core wire

| | |
|--------|--------------------|
| black | IDC/FLK14 (1) = () |
| brown | IDC/FLK14 (2) = () |
| red | IDC/FLK14 (3) = () |
| orange | IDC/FLK14 (4) = () |
| yellow | IDC/FLK14 (5) = () |
| green | IDC/FLK14 (6) = () |
| blue | IDC/FLK14 (7) = () |
| violet | IDC/FLK14 (8) = () |

Connection data

Connection 1

| | |
|---------------------------|--|
| Connection method | Single wires |
| Stripping length (Sheath) | ≈  mm |
| Number of positions | 8 |
| Note | The wires are marked and fitted with ferrules |

Connection 2

| | |
|----------------------------------|------------------------------|
| Connection in acc. with standard | IEC 60603-13 (in compliance) |
| Connection method | IDC/FLK socket strip |
| Number of connections | 1 |
| Number of positions | 14 |
| Conductor cross-section AWG | 26 |
| Insertion/withdrawal cycles | > 50 |

CABLE-FLK14/AXIO/OE/0,14/3,0M - Cable



1369905

<https://www.phoenixcontact.com/us/products/1369905>

| | |
|-------|---------|
| Pitch | 2.54 mm |
|-------|---------|

Notes

| | |
|--------------------|--|
| Notes on operation | For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met. |
|--------------------|--|

CABLE-FLK14/AXIO/OE/0,14/3,0M - Cable

1369905

<https://www.phoenixcontact.com/us/products/1369905>



Drawings

Schematic diagram



CABLE-FLK14/AXIO/OE/0,14/3,0M - Cable



1369905


<https://www.phoenixcontact.com/us/products/1369905>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1369905>

 **UL Listed**
Approval ID: E238705

 **cUL Listed**
Approval ID: E238705

 **EAC**
Approval ID: RU*-DE.HB*35.B00385

CABLE-FLK14/AXIO/OE/0,14/3,0M - Cable



1369905

<https://www.phoenixcontact.com/us/products/1369905>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27242220 |
| ECLASS-15.0 | 27242220 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC000237 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

CABLE-FLK14/AXIO/OE/0,14/3,0M - Cable



1369905

<https://www.phoenixcontact.com/us/products/1369905>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com