

# SAC-8P-10,0-28X/M12FS SH OD - Sensor/actuator cable



1407284

<https://www.phoenixcontact.com/us/products/1407284>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 8-position, PE-X/PE-X halogen-free, black-gray RAL 7021, shielded, free cable end, on Socket straight M12, coding: A, cable length: 10 m, for outdoor applications, with high-grade steel knurl

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Robust throughout: resistant to oil, UV, and ozone, withstands temperatures from -40°C ... +105°C
- Reliable signal transmission – 360° shielding in environments with electromagnetic interference

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1407284                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BF03                           |
| Product key                          | AF1CKA                         |
| GTIN                                 | 4046356774024                  |
| Weight per piece (including packing) | 823.7 g                        |
| Weight per piece (excluding packing) | 823.7 g                        |
| Customs tariff number                | 85444290                       |
| Country of origin                    | PL                             |

# SAC-8P-10,0-28X/M12FS SH OD - Sensor/actuator cable



1407284

<https://www.phoenixcontact.com/us/products/1407284>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Application          | External areas        |
| Number of positions  | 8                     |
| No. of cable outlets | 1                     |
| Shielded             | yes                   |
| Coding               | A                     |

### Insulation characteristics

|                     |   |
|---------------------|---|
| Degree of pollution | 3 |
|---------------------|---|

### Material specifications

|  |                 |
|--|-----------------|
| Flammability rating according to UL 94 | V0              |
| Seal material                          | FPM             |
| Material of grip body                  | PP              |
| Contact material                       | CuSn            |
| Contact surface material               | Ni/Au           |
| Contact carrier material               | PP              |
| Material for screw connection          | Stainless steel |

### Electrical properties

|                       |          |
|-----------------------|----------|
| Insulation resistance | ≥ 100 MΩ |
| Nominal voltage $U_N$ | 30 V AC  |
|                       | 30 V DC  |
| Nominal current $I_N$ | 2 A      |

### Mechanical properties

#### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | ≥ 100 |
|-----------------------------|-------|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | no |

### Connection data

#### Conductor connection

|                   |                        |
|-------------------|------------------------|
| Tightening torque | 0.4 Nm (M12 connector) |
|-------------------|------------------------|

### Connector

#### Connection 1

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

# SAC-8P-10,0-28X/M12FS SH OD - Sensor/actuator cable

1407284

<https://www.phoenixcontact.com/us/products/1407284>


## Connection 2

|                     |                     |
|---------------------|---------------------|
| Type                | Socket straight M12 |
| Number of positions | 8                   |
| Coding type         | A                   |

## Cable/line

|              |      |
|--------------|------|
| Cable length | 10 m |
|--------------|------|

## PE-X black [28X]

|                                 |  |
|---------------------------------|--|
| Dimensional drawing             |  |
| Cable weight                    | 81 kg/km   |
| Number of positions             | 8  |
| Shielded                        | yes  |
| Cable type                      | PE-X black [28X]   |
| Conductor structure signal line | 32x 0.10 mm  |
| AWG signal line                 | 24   |
| Conductor cross-section         | 8x 0.25 mm <sup>2</sup>  |
| Wire diameter incl. insulation  | 1.17 mm ±0.02 mm   |
| External cable diameter         | 7.25 mm ±0.3 mm  |
| Outer sheath, material          | PE-X   |
| External sheath, color          | black-gray RAL 7021  |
| Conductor material              | Bare Cu litz wires   |
| Material, filler                | PP yarn  |
| Material wire insulation        | PE-X   |
| Single wire, color              | white, brown, green, yellow, gray, pink, blue, red                                 |
| Thickness, insulation           | approx. 0.25 mm (Core insulation)  |
| Inner sheath thickness          | approx. 0.50 mm  |
| Thickness, outer sheath         | approx. 0.70 mm  |
| Overall twist                   | 8 wires around filler to the core  |
| Length of twist, overall twist  | 67 mm  |
| Optical shield covering         | 85 %   |
| Max. conductor resistance       | ≤ 78 Ω/km (at 20 °C)   |
| Insulation resistance           | ≥ 100 MΩ*km (at 20 °C)   |
| Working capacitance             | approx. 80 pF (Line-line)<br>approx. 125 pF (Line-shield)                          |
| Nominal voltage, cable          | ≤ 300 V AC   |
| Test voltage                    | ≥ 3000 V AC (Spark test)   |

# SAC-8P-10,0-28X/M12FS SH OD - Sensor/actuator cable



1407284

<https://www.phoenixcontact.com/us/products/1407284>

|   |  |
|---|--|
| Test voltage Core/Shield                      | ≥ 1000.00 V AC (for 10 s)  |
| Minimum bending radius, fixed installation    | 5 x D  |
| Minimum bending radius, flexible installation | 10 x D   |
| Smallest bending radius, fixed installation   | 37 mm  |
| Smallest bending radius, movable installation | 73 mm  |
| Dynamic load capacity (bending)               | Max. bending cycles: 1000000, Bending radius: 10 x D, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s <sup>2</sup> |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815   |
|   | in accordance with DIN EN 50267-2-1  |
| Flame resistance                              | According to DIN EN 60332-1-2  |
|   | according to DIN EN 50266-2-5  |
| Resistance to oil                             | According to DIN EN 60811-2-1, 168 h at 100°C  |
|   | According to DIN EN 50306  |
| Other resistance                              | Resistance to fuels (according to IEC 60811, 168 h at 70°C)  |
|   | UV resistant (according to DIN VDE 0276-605)   |
| Special properties                            | Inductance approx. 0.48 mH/km  |
|   | Irradiated   |
| Ambient temperature (operation)               | -40 °C ... 105 °C (cable, fixed installation)  |
|   | -15 °C ... 105 °C (Cable, flexible installation)   |
|   | 20 °C ±5 °C (cable, drag chain applications)   |

## Environmental and real-life conditions

### Ambient conditions

|   |   |
|---|---|
| Degree of protection  | IP65  |
|   | IP67  |
|   | IP68  |
|   | IP69K   |
| Ambient temperature (operation) (male connector/female connector) | -40 °C ... 105 °C (Plug / socket)   |
| Ambient temperature (operation) (Operation)                       | -40 °C ... 85 °C (On sudden changes in temperature (according to IEC 60512-11-4)) |

## Standards and regulations

### M12

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |

# SAC-8P-10,0-28X/M12FS SH OD - Sensor/actuator cable

1407284

<https://www.phoenixcontact.com/us/products/1407284>


## Drawings

Dimensional drawing



M12 x 1 socket, straight

Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side

# SAC-8P-10,0-28X/M12FS SH OD - Sensor/actuator cable



1407284

<https://www.phoenixcontact.com/us/products/1407284>

Circuit diagram



Contact assignment of the M12 socket

# SAC-8P-10,0-28X/M12FS SH OD - Sensor/actuator cable



1407284

<https://www.phoenixcontact.com/us/products/1407284>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1407284>

### **DNV**

Approval ID: TAE00002K4



### **EAC-RoHS**

Approval ID: RU D-DE.HB35.B.00387

# SAC-8P-10,0-28X/M12FS SH OD - Sensor/actuator cable



1407284

<https://www.phoenixcontact.com/us/products/1407284>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060311 |
| ECLASS-15.0 | 27060311 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC001855 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-8P-10,0-28X/M12FS SH OD - Sensor/actuator cable



1407284

<https://www.phoenixcontact.com/us/products/1407284>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

### EF3.1 Climate Change

|         |                |
|---------|----------------|
| CO2e kg | 12.642 kg CO2e |
|---------|----------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)