

# QPD T 3PE1,5 3X8-13 BK - T distributor



1414710

<https://www.phoenixcontact.com/us/products/1414710>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



T distributor, connection method: IDC connection, number of positions: 3+PE, 0.5 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>, 690 V, 17.5 A, PA, black, With three QUICKON nuts, coding: Coding profile, external cable diameter: 10 mm ... 13 mm

## Your advantages

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- Safer connection with mechanical coding to protect against mismatching, and touch-proof protection in accordance with DIN EN 0105
- Flexible and compact - by connecting connections internally, H and T-distributors can be used to branch master cables or they can be used as star distributors

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1414710       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF50          |
| Product key                          | AF6DBA        |
| GTIN                                 | 4055626032061 |
| Weight per piece (including packing) | 123.6 g       |
| Weight per piece (excluding packing) | 124 g         |
| Customs tariff number                | 85366990      |
| Country of origin                    | PL            |

# QPD T 3PE1,5 3X8-13 BK - T distributor

1414710

<https://www.phoenixcontact.com/us/products/1414710>

## Technical data

### Product properties

|                       |                   |
|-----------------------|-------------------|
| Product type          | Power distributor |
| Product family        | QPD               |
| Type                  | T distributor     |
| Number of positions   | 4                 |
| Connection profile    | 3+PE              |
| Position marking      | 1, 2, 3, PE       |
| Number of connections | 3                 |
| No. of cable outlets  | 3                 |
| Coding                | Coding profile    |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Connection data


#### Connection technology

|   |                |
|---|----------------|
| Connection method   | IDC connection |
| Frequency of connections between conductors of the same cross section | max. 10        |

#### Conductor connection

|                                  |   |
|----------------------------------|---|
| Conductor cross-section flexibel | 0.5 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Conductor cross-section solid    | 0.5 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Connection cross section AWG     | 20 ... 16                                   |
| Tightening torque Union nut      | 8 Nm  |
| Tightening torque Locking nut    | 5 Nm  |

### Dimensions

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Width               | 71.1 mm  |
| Height              | 26 mm  |
| Length              | 147.8 mm   |

### Electrical properties

|                             |      |
|-----------------------------|------|
| Rated surge voltage (II/2)  | 8 kV |
| Rated surge voltage (III/2) | 8 kV |
| Rated surge voltage (III/3) | 6 kV |

# QPD T 3PE1,5 3X8-13 BK - T distributor



1414710

<https://www.phoenixcontact.com/us/products/1414710>

|                       |          |
|-----------------------|----------|
| Rated current         | 17.5 A   |
| Contact resistance    | < 3 mΩ   |
| rated voltage (II/2)  | 1000 V   |
| rated voltage (III/2) | 1000 V   |
| Rated voltage (III/3) | 690 V    |
| Nominal voltage $U_N$ | 690 V AC |
|                       | 690 V DC |
| Nominal current $I_N$ | 17.5 A   |

## Mechanical properties

### Mechanical data

|                             |                                       |
|-----------------------------|---------------------------------------|
| Insertion/withdrawal cycles | max. 50 (QUICKON connections max. 10) |
|-----------------------------|---------------------------------------|

## Material specifications

|  |                   |
|--|-------------------|
| Color                                  | black (RAL 9005)  |
| Material Housing                       | PA                |
| Material Contact                       | Cu                |
| Material Contact surface               | silver-plated     |
| Flammability rating according to UL 94 | V0                |
| Material wire insulation               | PVC/PE/TPE/rubber |

## Cable/line

|   |                                    |
|---|------------------------------------|
| Structure of individual litz in acc. with VDE 0295 / smallest wire diameter | VDE 0295 class 1 to 6/min. 0.15 mm |
| External cable diameter   | 10 mm ... 13 mm                    |
| Wire diameter including insulation  | 1.6 mm ... 3 mm                    |
| Position marking  | 1, 2, 3, PE                        |
| Material wire insulation  | PVC/PE/TPE/rubber                  |

## Environmental and real-life conditions

### Ambient conditions


|   |  |
|---|--|
| Degree of protection                    | IP66                                   |
|   | IP68 (2 m / 24 h)                      |
|   | IP69K                                  |
|   | Touch-proof when not plugged in (IP2X) |
| Impact strength                         | IK07 (-5 °C)                           |
| Ambient temperature (operation)         | -40 °C ... 100 °C                      |
| Temperature when conductor connected    | -5 °C ... 50 °C                        |
| Ambient temperature (storage/transport) | -40 °C ... 100 °C                      |

# QPD T 3PE1,5 3X8-13 BK - T distributor


1414710

<https://www.phoenixcontact.com/us/products/1414710>

## Drawings



Dimensional drawing



Derating diagram

# QPD T 3PE1,5 3X8-13 BK - T distributor

1414710

<https://www.phoenixcontact.com/us/products/1414710>



# QPD T 3PE1,5 3X8-13 BK - T distributor



1414710

<https://www.phoenixcontact.com/us/products/1414710>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1414710>



**IECEE CB Scheme**  
Approval ID: DE1-65875



**DNV GL**  
Approval ID: TAE00003J5



**VDE Zeichengenehmigung**  
Approval ID: 40029149



**UL Listed**  
Approval ID: E468743

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine |                       |                       |                   |                             |
|       | 600 V                 | 8 A                   | - 16              | -                           |



**cUL Listed**  
Approval ID: E468743

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine |                       |                       |                   |                             |
|       | 600 V                 | 8 A                   | - 16              | -                           |

# QPD T 3PE1,5 3X8-13 BK - T distributor



1414710

<https://www.phoenixcontact.com/us/products/1414710>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27440603 |
| ECLASS-15.0 | 27440603 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC002567 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# QPD T 3PE1,5 3X8-13 BK - T distributor



1414710

<https://www.phoenixcontact.com/us/products/1414710>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

### EF3.1 Climate Change

|         |               |
|---------|---------------|
| CO2e kg | 7.104 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)