

# MG-INC-M20-S67L-PTES-LG - Membrane screw connection



1415187

<https://www.phoenixcontact.com/us/products/1415187>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Membrane screw connection, material for screw connection: Polypropylene, application: Standard, external cable diameter 6 mm ... 13 mm, shielding: no, connecting thread: M20, color: light gray

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1415187       |
| Packing unit                         | 20 pc         |
| Minimum order quantity               | 20 pc         |
| Sales key                            | BF68          |
| Product key                          | AF7DFX        |
| GTIN                                 | 4055626038018 |
| Weight per piece (including packing) | 4.68 g        |
| Weight per piece (excluding packing) | 3.554 g       |
| Customs tariff number                | 39269097      |
| Country of origin                    | DE            |

# MG-INC-M20-S67L-PTES-LG - Membrane screw connection



1415187

<https://www.phoenixcontact.com/us/products/1415187>

## Technical data


### Mounting

|               |   |
|---------------|---|
| Assembly note | for 0.8 mm ... 3.5 mm wall thickness, for 20 mm ... 20.7 mm bore hole |
|---------------|---|

### Product properties

|                          |                   |
|--------------------------|-------------------|
| Product type             | Cable screw gland |
| Application              | Standard          |
| Manufacturer             | WISKA             |
| Manufacturer Designation | CLIXX 20          |
| Shielded                 | no                |

### Dimensions

|                                  |   |
|----------------------------------|---|
| Dimensional drawing              |  |
| Length                           | 15 mm   |
| Length of the connecting thread  | 8 mm  |
| Length without connecting thread | 7 mm  |
| Diameter                         | 20 mm   |
| Connecting thread diameter       | 20 mm   |
| Hole diameter                    | 20 mm ... 20.7 mm   |
| Hexagon angular dimension        | 34 mm   |
| Thread type connection side      | M20   |

### Material specifications

|                               |                       |
|-------------------------------|-----------------------|
| Color                         | light gray (RAL 7035) |
| Seal material                 | TPE                   |
| Material for screw connection | Polypropylene         |

### Cable/line

|                         |                |
|-------------------------|----------------|
| External cable diameter | 6 mm ... 13 mm |
|-------------------------|----------------|

### Environmental and real-life conditions

#### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Degree of protection            | IP66<br>IP67     |
| Ambient temperature (operation) | -40 °C ... 65 °C |


# MG-INC-M20-S67L-PTES-LG - Membrane screw connection



1415187

<https://www.phoenixcontact.com/us/products/1415187>

## Drawings



# MG-INC-M20-S67L-PTES-LG - Membrane screw connection



1415187

<https://www.phoenixcontact.com/us/products/1415187>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27140890 |
| ECLASS-15.0 | 27140801 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC000441 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121300 |
|-------------|----------|

# MG-INC-M20-S67L-PTES-LG - Membrane screw connection



1415187

<https://www.phoenixcontact.com/us/products/1415187>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

### EF3.1 Climate Change

|         |               |
|---------|---------------|
| CO2e kg | 0.035 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)