

# SACC-DSI-FS-8CON-PG9/0,5-0,14 - Device connector rear mounting



1415279

<https://www.phoenixcontact.com/us/products/1415279>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 8-position, Socket, straight, M12, A-coding, on free cable end, Individual wires, cable length: 0.5 m, 0.14 mm<sup>2</sup>, potted, this item is expected to be lead-free from Q3 2026 in accordance with RoHS II without exception 6c (Pb < 0.1%), a lead-free alternative is possible on request in advance

## Commercial data

Item number	1415279
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB24
Product key	ABQCHE
GTIN	4055626043067
Weight per piece (including packing)	23.9 g
Weight per piece (excluding packing)	22.639 g
Customs tariff number	85444290
Country of origin	DE

# SACC-DSI-FS-8CON-PG9/0,5-0,14 - Device connector rear mounting



1415279

<https://www.phoenixcontact.com/us/products/1415279>

## Technical data

### Notes

Order information:	Lock nut is included in the scope of delivery
General	Contact connection method: Crimp connection

### Mounting

Mounting type	Rear mounting (Pg9)
Tightening torque	2 Nm ... 3 Nm

### Product properties

Product type	Circular connectors (device side)
Application	Signal
Number of positions	8
No. of cable outlets	1
Coding	A
Thread type	M12

### Material specifications

Material Molding compound	PUR (potted)
---------------------------	--------------

### Connection data

#### Conductor connection

Connection method	Individual wires
Contact connection type	Socket
Conductor cross-section	0.14 mm <sup>2</sup>
Tightening torque	2 Nm ... 3 Nm

### Connector

#### Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Coding	A

#### Connection 2

Head design	free cable end
-------------	----------------

### Cable/line

Cable length	0.5 m
Cable cross section	0.14 mm <sup>2</sup>
AWG signal line	26

# SACC-DSI-FS-8CON-PG9/0,5-0,14 - Device connector rear mounting



1415279

<https://www.phoenixcontact.com/us/products/1415279>

## Environmental and real-life conditions

### Ambient conditions

UL Type Rating	Type 4 (indoor use only)
----------------	--------------------------

# SACC-DSI-FS-8CON-PG9/0,5-0,14 - Device connector rear mounting



1415279

<https://www.phoenixcontact.com/us/products/1415279>

## Classifications

### ECLASS

ECLASS-13.0	27440103
ECLASS-15.0	27440103

### ETIM

ETIM 10.0	EC003570
-----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# SACC-DSI-FS-8CON-PG9/0,5-0,14 - Device connector rear mounting



1415279

<https://www.phoenixcontact.com/us/products/1415279>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	5dbd021a-39fd-48b0-a33d-8833cf22448e

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)