

# SACC-CIP-M12MS-8P SMD SH-SP - Sample set



1418649

<https://www.phoenixcontact.com/us/products/1418649>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sample set, 8-position, Pin, straight, M12, A-coding, SMD reflow, this item is expected to be lead-free from Q1 2027 in accordance with RoHS II without exception 6c (Pb < 0.1%), a lead-free alternative is possible on request in advance

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1418649       |
| Packing unit                         | 5 pc          |
| Minimum order quantity               | 5 pc          |
| Product key                          | ABQXAA        |
| GTIN                                 | 4055626163017 |
| Weight per piece (including packing) | 8.23 g        |
| Weight per piece (excluding packing) | 3.855 g       |
| Country of origin                    | DE            |

## Technical data

### Notes

|                    |  |
|--------------------|--|
| Notes on operation | The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration. |
|--------------------|--|

### Product properties

|                     |                |
|---------------------|----------------|
| Product type        | Contact insert |
| Number of positions | 8              |
| Seal present        | yes            |
| Shielded            | yes            |
| Coding              | A              |
| Thread type         | M12            |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Rated surge voltage   | 0.8 kV                     |
| Contact resistance    | $\leq 3 \text{ m}\Omega$   |
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 30 V                       |
| Nominal current $I_N$ | 2 A                        |

### Connection data

|                   |            |
|-------------------|------------|
| Connection method | SMD reflow |
|-------------------|------------|

### Material specifications

|  |      |
|--|------|
| Flammability rating according to UL 94 | V0   |
| Seal material                          | FKM  |
| Contact material                       | CuZn |
| Contact surface material               | Au   |
| Contact carrier material               | PA   |

### Connector

#### Connection 1

|                   |          |
|-------------------|----------|
| Head design       | Pin      |
| Head cable outlet | straight |
| Head thread type  | M12      |
| Coding            | A        |

1418649

<https://www.phoenixcontact.com/us/products/1418649>

## Mechanical properties

### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | > 100 |
|-----------------------------|-------|

## Environmental and real-life conditions

### Ambient conditions

|   |   |
|---|---|
| Degree of protection (not plugged in)                             | IP65 (not plugged in, by means of additional O-ring seal with device) |
| Degree of protection  | IP67 (correctly plugged in and locked)                                |
|   | IP65 (not plugged in, by means of additional O-ring seal with device) |
| Ambient temperature (operation) (male connector/female connector) | -25 °C ... 105 °C   |
|   | -40 °C ... 105 °C (without mechanical actuation)                      |
| UL Type Rating  | Type 4 (indoor use only)  |

## Standards and regulations

|                          |                              |
|--------------------------|------------------------------|
| Standard designation     | M12 circular connector       |
| Standards/specifications | according to IEC 61076-2-101 |

1418649

<https://www.phoenixcontact.com/us/products/1418649>

## Drawings

Schematic diagram



Pin assignment M12 plug, 8-pos., view plug side

# SACC-CIP-M12MS-8P SMD SH-SP - Sample set



1418649

<https://www.phoenixcontact.com/us/products/1418649>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1418649>

|  <b>cULus Recognized</b><br>Approval ID: E221474-20160506 |                       |                       |                   |                             |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| keine  |                       |                       |                   |                             |
|  | 30 V                  | 2 A                   | -                 | -                           |

# SACC-CIP-M12MS-8P SMD SH-SP - Sample set



1418649

<https://www.phoenixcontact.com/us/products/1418649>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27440223 |
| ECLASS-15.0 | 27440223 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC003557 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# SACC-CIP-M12MS-8P SMD SH-SP - Sample set



1418649

<https://www.phoenixcontact.com/us/products/1418649>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)