

HC-STA-D07-BAWS-EL-AL - Housing

1419252

<https://www.phoenixcontact.com/us/products/1419252>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Panel mounting base D7, with single locking latch, material: Die-cast aluminum, salt water resistant, height: 28.5 mm, cable gland: none, Standard, angled

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1419252 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF56 |
| Product key | AF7APF |
| GTIN | 4055626159836 |
| Weight per piece (including packing) | 29.3 g |
| Weight per piece (excluding packing) | 29.3 g |
| Customs tariff number | 85389099 |
| Country of origin | CN |

HC-STA-D07-BAWS-EL-AL - Housing

1419252

<https://www.phoenixcontact.com/us/products/1419252>

Technical data


Notes

| | |
|---------|---|
| General | for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12 |
|---------|---|

Product properties

| | |
|---------------------|----------------------------|
| Product type | Housing with locking latch |
| Housing type | Panel mounting base |
| Product family | HC-STA-D07 |
| Application | Standard |
| Type | D7 |
| Shielded | no |
| Pg screw connection | none |

Dimensions

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 38 mm |
| Height | 28.5 mm |
| Length | 24.2 mm |
| Hole diameter | 3.2 mm |

Installation dimensions

| | |
|-------------------------------|-------|
| Width of the assembly cutout | 21 mm |
| Length of the assembly cutout | 21 mm |

Material specifications

| | |
|--|---|
| Flammability rating according to UL 94 | V0 (Interlock) |
| Seal material Flat gasket | NBR, conductive |
| Housing material | Die-cast aluminum, salt water resistant |
| Housing surface material | uncoated |
| Locking latch material | PA |

Mechanical properties

Mechanical data

| | |
|--------------|-------|
| Locking type | Latch |
|--------------|-------|

Connection data

| | |
|-------------------|--|
| Tightening torque | 0.5 Nm ... 0.8 Nm (For M3 mounting screws on the panel-mount base) |
|-------------------|--|

HC-STA-D07-BAWS-EL-AL - Housing



1419252

<https://www.phoenixcontact.com/us/products/1419252>

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|-------------------|
| Degree of protection | IP66 |
| | IP67 |
| Enclosure rating (NEMA) | 4 (UL 50e) |
| | 4X (UL 50e) |
| Impact strength | IK06 |
| Ambient temperature (operation) | -40 °C ... 125 °C |

HC-STA-D07-BAWS-EL-AL - Housing




1419252

<https://www.phoenixcontact.com/us/products/1419252>

Drawings

Dimensional drawing



Dimensional drawing

HC-STA-D07-BAWS-EL-AL - Housing

1419252

<https://www.phoenixcontact.com/us/products/1419252>

Dimensional drawing



- HC-A03
- HC-A04
- HC-D07
- HC-D08
- HC-Q05
- HC-Q07
- HC-Q12



- HC-Q02
- HC-Q03
- HC-Q04

Mounting cutout

1419252

<https://www.phoenixcontact.com/us/products/1419252>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1419252>

DNV

Approval ID: TAE000037S



cUL Recognized

Approval ID: E255026



UL Recognized

Approval ID: E255026

1419252

<https://www.phoenixcontact.com/us/products/1419252>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27440202 |
| ECLASS-15.0 | 27440202 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC000437 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

1419252

<https://www.phoenixcontact.com/us/products/1419252>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com