

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug straight M8, coding: B, on Socket straight M8, cable length: 2 m

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1423839                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BF01                           |
| Product key                          | AF1BDA                         |
| GTIN                                 | 4055626356822                  |
| Weight per piece (including packing) | 70.6 g                         |
| Weight per piece (excluding packing) | 68.6 g                         |
| Customs tariff number                | 85444290                       |
| Country of origin                    | PL                             |

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Number of positions  | 5                     |
| No. of cable outlets | 1                     |
| Shielded             | no                    |
| Coding               | B                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|  |   |
|--|---|
| Flammability rating according to UL 94 | HB  |
| Seal material                          | NBR   |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Contact material                       | CuSn  |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material for screw connection          | Zinc die-cast, nickel-plated                |

### Electrical properties

|                       |         |
|-----------------------|---------|
| Nominal voltage $U_N$ | 30 V AC |
|                       | 30 V DC |
| Nominal current $I_N$ | 3 A     |

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | no |

### Connector

#### Connection 1

|                     |                  |
|---------------------|------------------|
| Type                | Plug straight M8 |
| Number of positions | 5                |
| Coding type         | B                |

#### Connection 2

|                     |                    |
|---------------------|--------------------|
| Type                | Socket straight M8 |
| Number of positions | 5                  |

### Cable/line

|              |     |
|--------------|-----|
| Cable length | 2 m |
|--------------|-----|

PUR, black, 5th conductor gray [115]

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

|   |  |
|---|--|
| Cable weight                                  | 30 kg/km   |
| UL AWM Style                                  | 20549  |
| Number of positions                           | 5  |
| Shielded                                      | no   |
| Cable type                                    | PUR, black, 5th conductor gray [115]   |
| Conductor structure signal line               | 32x 0.10 mm  |
| AWG signal line                               | 24   |
| Conductor cross-section                       | 0.25 mm <sup>2</sup>   |
| Wire diameter incl. insulation                | 1.17 mm ±0.02 mm   |
| External cable diameter                       | 4.70 mm ±0.15 mm   |
| Outer sheath, material                        | PUR  |
| External sheath, color                        | black-gray RAL 7021  |
| Conductor material                            | Bare Cu litz wires   |
| Material, filler                              | PP   |
| Material wire insulation                      | PP   |
| Single wire, color                            | brown, white, blue, black, gray  |
| Thickness, insulation                         | approx. 0.21 mm (Core insulation)<br>approx. 0.70 mm (Outer cable sheath)  |
| Overall twist                                 | 5 cores, twisted   |
| Length of twist, overall twist                | 75 mm  |
| Max. conductor resistance                     | ≤ 75 Ω/km  |
| Insulation resistance                         | ≥ 1 GΩ*km  |
| Nominal voltage, cable                        | ≤ 300 V (AC)   |
| Test voltage                                  | ≥ 3000 V (AC)  |
| Smallest bending radius, fixed installation   | 23.5 mm  |
| Smallest bending radius, movable installation | 47 mm  |
| Dynamic load capacity (bending)               | Max. bending cycles: 10000000, Bending radius: 47 mm, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s <sup>2</sup> |
| Dynamic load capacity (torsion)               | Torsion: ±180 °/m, Torsion cycles: ≥5000000, Torsional frequency: 35 cycles/min.   |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815<br>in accordance with DIN EN 50267-2-1  |
| Flame resistance                              | according to UL 758/1581 (horizontal)<br>in accordance with UL 758/1581 FT2  |
| Resistance to oil                             | According to DIN EN 60811-2-1, 168 h at 100°C  |
| Other resistance                              | hydrolysis and microbe resistant<br>Resistant to salt water<br>Low adhesion<br>abrasion-resistant                                      |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)<br>-25 °C ... 80 °C (Cable, flexible installation)  |

## Environmental and real-life conditions

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

## Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Degree of protection            | IP65                             |
|                                 | IP67                             |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M8 connector    |
| Standards/specifications | IEC 61076-2-104 |

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable

1423839

<https://www.phoenixcontact.com/us/products/1423839>

## Drawings

Dimensional drawing



M8 x 1 male plug, straight version

Dimensional drawing



Socket M8 x 1, straight

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable

1423839

<https://www.phoenixcontact.com/us/products/1423839>

Schematic diagram



Pin assignment, pin side, M8, 5-pos., B-coded

Schematic diagram



Pin assignment, socket side, M8, 5-pos., B-coded

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

Circuit diagram



Contact assignment of M8 plugs/sockets

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable





1423839

<https://www.phoenixcontact.com/us/products/1423839>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1423839>

|  <b>UL Listed</b><br>Approval ID: FILE E 221474 |                       |                       |                   |                             |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| keine  |                       |                       |                   |                             |
|  | 30 V                  | 3 A                   | -                 | -                           |

|  <b>cUL Listed</b><br>Approval ID: FILE E 221474 |                       |                       |                   |                             |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
|   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| keine   |                       |                       |                   |                             |
|   | 30 V                  | 3 A                   | -                 | -                           |

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060311 |
| ECLASS-15.0 | 27060311 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC001855 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-5P-M 8MSB/ 2,0-115/M 8FSB - Sensor/actuator cable



1423839

<https://www.phoenixcontact.com/us/products/1423839>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)