

# SAC-4P-M12MRT/ 1,5-PUR SH - Power cable



1424124

<https://www.phoenixcontact.com/us/products/1424124>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 4-position, PUR halogen-free, black RAL 9005, shielded (Advanced Shielding Technology), Plug angled M12, coding: T, on free cable end, cable length: 1.5 m, For direct current up to 12 A/63 V

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Protection against incorrect connection using special T-coding
- Shield power reliably – 360° shielding to reduce electromagnetic loads
- Our standard: robust halogen-free PUR cable

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1424124       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF05          |
| Product key                          | AF1CCQ        |
| GTIN                                 | 4046356693288 |
| Weight per piece (including packing) | 250.7 g       |
| Weight per piece (excluding packing) | 22.22 g       |
| Customs tariff number                | 85444290      |
| Country of origin                    | PL            |

# SAC-4P-M12MRT/ 1,5-PUR SH - Power cable



1424124

<https://www.phoenixcontact.com/us/products/1424124>

## Technical data

### Product properties

|                      |               |
|----------------------|---------------|
| Product type         | Power cable   |
| Application          | Energy supply |
| Number of positions  | 4             |
| No. of cable outlets | 1             |
| Shielded             | yes           |
| Coding               | T             |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Material specifications

|  |                              |
|--|------------------------------|
| Flammability rating according to UL 94 | V0                           |
| Material of grip body                  | PP                           |
| Contact material                       | CuZn                         |
| Contact surface material               | Ni/Au                        |
| Contact carrier material               | PA                           |
| Material for screw connection          | Zinc die-cast, nickel-plated |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 63 V DC                    |
| Nominal current $I_N$ | 12 A                       |

### Mechanical properties

#### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | > 100 |
|-----------------------------|-------|

### Connector

#### Connection 1

|             |                 |
|-------------|-----------------|
| Type        | Plug angled M12 |
| Coding type | T (Power)       |

#### Connection 2

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

### Cable/line

|              |       |
|--------------|-------|
| Cable length | 1.5 m |
|--------------|-------|


PUR halogen-free black [PUR]

# SAC-4P-M12MRT/ 1,5-PUR SH - Power cable



1424124

<https://www.phoenixcontact.com/us/products/1424124>

|   |   |
|---|---|
| Dimensional drawing                           |   |
| Cable weight                                  | 99 kg/km  |
| UL AWM Style                                  | 20549 / 10493 (80°C/300 V)  |
| Number of positions                           | 4   |
| Shielded                                      | yes   |
| Cable type                                    | PUR halogen-free black [PUR]  |
| Conductor structure, voltage supply           | 44x 0.20 mm   |
| AWG power supply                              | 16  |
| Conductor cross-section                       | 4x 1.5 mm <sup>2</sup>  |
| Wire diameter incl. insulation                | 2.2 mm ±0.05 mm   |
| External cable diameter                       | 7.50 mm ±0.3 mm   |
| Outer sheath, material                        | PUR   |
| External sheath, color                        | black RAL 9005  |
| Conductor material                            | Bare Cu litz wires  |
| Material wire insulation                      | PP  |
| Single wire, color                            | brown, white, blue, black   |
| Thickness, insulation                         | 0.80 mm (Outer cable sheath)  |
| Overall twist                                 | 4 wires optimally twisted   |
| Max. conductor resistance                     | ≤ 14.1 Ω/km (at 20 °C)  |
| Insulation resistance                         | ≥ 1 GΩ*km (at 20 °C)  |
| Nominal voltage, cable                        | 300 V AC  |
| Test voltage                                  | 3000 V AC   |
| Smallest bending radius, fixed installation   | 38 mm   |
| Smallest bending radius, movable installation | 75 mm   |
| Dynamic load capacity (bending)               | Max. bending cycles: 5000000, Bending radius: 75 mm, Bending radius: 10 x D, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s <sup>2</sup> |
| Dynamic load capacity (torsion)               | Torsion: ±180 °/m, Torsion cycles: 500000, Torsional frequency: 35 cycles/min.  |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815<br>according to IEC 60754-1  |
| Flame resistance                              | in accordance with UL 758/1581 FT2<br>DIN EN 60332-2-2 (20 s)   |
| Resistance to oil                             | according to DIN EN 60811-404, 168 h at 100 °C  |
| Special properties                            | Flexible cable conduit capable  |
| Ambient temperature (operation)               | -50 °C ... 85 °C (cable, fixed installation)<br>-30 °C ... 85 °C (Cable, flexible installation)   |

# SAC-4P-M12MRT/ 1,5-PUR SH - Power cable



1424124

<https://www.phoenixcontact.com/us/products/1424124>

## Environmental and real-life conditions

### Ambient conditions

|   |                                  |
|---|----------------------------------|
| Degree of protection  | IP65                             |
|   | IP67                             |
| Ambient temperature (operation) (male connector/female connector) | -25 °C ... 85 °C (Plug / socket) |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-111 |

# SAC-4P-M12MRT/ 1,5-PUR SH - Power cable

1424124

<https://www.phoenixcontact.com/us/products/1424124>

## Drawings

Dimensional drawing




M12 x 1 male plug, angled

Schematic diagram



Pin assignment for M12 plug, 4-pos., T-coded, view of plug side

Diagram



Base curve

Circuit diagram



Contact assignment of the M12 plug

# SAC-4P-M12MRT/ 1,5-PUR SH - Power cable



1424124

<https://www.phoenixcontact.com/us/products/1424124>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1424124>

|  <b>UL Listed</b><br>Approval ID: E468743 |                       |                       |                   |                             |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| keine  |                       |                       |                   |                             |
|  | 63 V                  | 12 A                  | - 16              | - 16                        |

|  <b>cUL Listed</b><br>Approval ID: E468743 |                       |                       |                   |                             |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
|   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| keine   |                       |                       |                   |                             |
|   | 63 V                  | 12 A                  | - 16              | -                           |

|  <b>EAC-RoHS</b><br>Approval ID: RU D-DE.HB35.B.00387 |  |  |  |  |
|--|--|--|--|--|
|--|--|--|--|--|

# SAC-4P-M12MRT/ 1,5-PUR SH - Power cable



1424124

<https://www.phoenixcontact.com/us/products/1424124>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060327 |
| ECLASS-15.0 | 27060327 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC001855 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-4P-M12MRT/ 1,5-PUR SH - Power cable



1424124

<https://www.phoenixcontact.com/us/products/1424124>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

### EF3.1 Climate Change

|         |               |
|---------|---------------|
| CO2e kg | 3.493 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)