# G-INVEN-M20-M67N-PNES-LG - Cable gland

1424534

https://www.phoenixcontact.com/us/products/1424534

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 6 mm ... 11 mm, shielding: no, connecting thread: M20 x 1.5, color: lightgray RAL 7035, with pressure compensation element and flat gasket

## Product description

Cable gland with integrated pressure compensation element. Prevents low pressure forming in the housing. Membrane: resistant to water and dirt

## Your advantages

- Reduces the formation of condensation
- Screw connection with integrated pressure compensation element
- Plastic material conforms to UL 746C f1

## Commercial data

| | |
|---|---|
| Item number | 1424534 |
| Packing unit | 5 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF68 |
| Product key | AF7DCX |
| GTIN | 4055626374390 |
| Weight per piece (including packing) | 12.2 g |
| Weight per piece (excluding packing) | 11.61 g |
| Customs tariff number | 39269097 |
| Country of origin | TR |

## Technical data


### Product properties

| | |
|---|---|
| Product type | Cable screw gland |
| Application | Standard |
| No. of conductors | 1 |
| Manufacturer | BIMED |
| Manufacturer Designation | BMVG-12 |
| Air flow rate | 40 (l/h at a pressure differential of 70 mbar) |
| Shielded | no |
| Execution of the strain relief | A |

### Characteristics

| | |
|---|---|
| Category of shock impact | 5 |
| Design, Strain relief | A |

### Dimensions

| | |
|---|---|
| Dimensional drawing |   |
| Length | 40 mm |
| Length of the connecting thread | 10 mm |
| Hole diameter | 20.1 mm ... 20.2 mm |
| Wrench size, union nut | 24 mm |
| Wrench size, support | 24 mm |
| Thread type connection side | M20 x 1.5 |
| Thread pitch | 1.5 mm |

### Connection data

| | |
|---|---|
| Tightening torque | 5 Nm ±0.2 Nm (Cap nut) |
| | 3 Nm (Support sleeve) |

### Material specifications

| | |
|---|---|
| Color | light gray (RAL 7035) |
| Material | PTFE (The material specification refers to the ventilation membrane) |
| Flammability rating according to UL 94 | V2 |
| Material grommet GRP | NBR (Flat gasket) |
| | CR |
| Material for screw connection | PA |

### Cable/line

| | |
|---|---|
| External cable diameter Cable 1 | 6 mm ... 11 mm |
| External cable diameter | 6 mm ... 12 mm (for UL 514 B) |
| Halogen-free | no |


## Environmental and real-life conditions

### Ambient conditions

| | |
|---|---|
| Degree of protection | IP67 |
| | IP66 |
| Enclosure rating (NEMA) | 1 |
| | 4 |
| | 4X |
| | 12 |
| | 13 |
| Ambient temperature (operation) | -20 °C ... 100 °C (static) |

## Drawings

Dimensional drawing




Dimensional drawing

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1424534

**DNV**
Approval ID: TAE00003WX

**cUL Recognized**
Approval ID: E199260

**UL Recognized**
Approval ID: E199260

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27140801 |
| ECLASS-15.0 | 27140801 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC000441 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121300 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

EF3.1 Climate Change

| | |
|---|---|
| CO2e kg | 0.685 kg CO2e |


Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com



Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com