

# SACC-DSI-M12FS-8CON-L180PSCUP - Device connector rear mounting



1436327

<https://www.phoenixcontact.com/us/products/1436327>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator flush-type connector, socket, 8-pos., M12, A-coded, rear/screw mounting with Pg9 thread, with solder cups, plastic version

## Commercial data

Item number	1436327
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB23
Product key	ABQEHL
GTIN	4046356438292
Weight per piece (including packing)	6.835 g
Weight per piece (excluding packing)	6.5 g
Customs tariff number	85366990
Country of origin	DE

# SACC-DSI-M12FS-8CON-L180PSCUP - Device connector rear mounting



1436327

<https://www.phoenixcontact.com/us/products/1436327>

## Technical data

### Notes

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
--------------------	--

### Mounting

Mounting type	Rear mounting (Pg9, with locking nut)
Tightening torque	3 Nm ... 4 Nm (Installation-side)

### Product properties

Product type	Circular connectors (device side)
Number of positions	8
Shielded	no
Coding	A
Thread type	M12

### Insulation characteristics

Overvoltage category	II
Degree of pollution	3

### Material specifications

Material Housing	PA 6.6
Material Insulating body	PA 6.6
Material Contact	CuZn
Material Contact surface	Au
Material Seal	Viton
Flammability rating according to UL 94	HB

### Electrical properties

Rated surge voltage	0.8 kV
Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage $U_N$	30 V
Nominal current $I_N$	2 A
Max. conductor resistance	57.6 m $\Omega$ /m

### Connection data

#### Conductor connection

Connection method	Solder cup
-------------------	------------

# SACC-DSI-M12FS-8CON-L180PSCUP - Device connector rear mounting



1436327

<https://www.phoenixcontact.com/us/products/1436327>

Contact connection type	Socket
Conductor cross-section	0.25 mm <sup>2</sup>
Conductor cross-section flexible	... 0.25 mm <sup>2</sup>
Tightening torque	3 Nm ... 4 Nm (Installation-side)

## Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

## Connector

### Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Coding	A

## Cable/line

Wire diameter incl. insulation	1.15 mm ±0.07 mm
Cable cross section	0.25 mm <sup>2</sup>
Conductor structure signal line	14x 0.15 mm
Thickness, insulation	0.21 mm
Nominal voltage, cable	300 V
Test voltage, cable	2000 V AC
Cable resistance	≤ 57.6 mΩ/m
Cable insulation resistance	≥ 20 MΩ*km

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation) (male connector/female connector)	-25 °C ... 85 °C (Plug / socket) -40 °C ... 85 °C (without mechanical actuation)
UL Type Rating	Type 4 (indoor use only)

## Standards and regulations

Standard designation	M12 circular connector
Standards/specifications	according to IEC 61076-2-101


# SACC-DSI-M12FS-8CON-L180PSCUP - Device connector rear mounting

1436327

<https://www.phoenixcontact.com/us/products/1436327>

## Drawings

Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side

# SACC-DSI-M12FS-8CON-L180PSCUP - Device connector rear mounting



1436327

<https://www.phoenixcontact.com/us/products/1436327>

## Classifications

### ECLASS

ECLASS-13.0	27440109
ECLASS-15.0	27440109

### ETIM

ETIM 10.0	EC003569
-----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# SACC-DSI-M12FS-8CON-L180PSCUP - Device connector rear mounting



1436327

<https://www.phoenixcontact.com/us/products/1436327>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	e924173d-415f-45a9-ab20-872ce2f29e83

### EF3.1 Climate Change

CO2e kg	1.152 kg CO2e
---------	---------------

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)