

SACC-E-M12MS-8CON-M16 PSCUP - Device connector front mounting



1436408

<https://www.phoenixcontact.com/us/products/1436408>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator flush-type connector, male, 8-pos., M12, A-coded, front/screw mounting with M16 thread, with solder cups, plastic version

Commercial data

Item number	1436408
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB23
Product key	ABQEEJ
GTIN	4046356438353
Weight per piece (including packing)	6.335 g
Weight per piece (excluding packing)	6.304 g
Customs tariff number	85366990
Country of origin	DE

SACC-E-M12MS-8CON-M16 PSCUP - Device connector front mounting



1436408

<https://www.phoenixcontact.com/us/products/1436408>

Technical data

Notes

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
--------------------	--

Mounting

Mounting type	Front mounting (M16 x 1,5)
Tightening torque	1.25 Nm ... 1.5 Nm (Installation-side)

Product properties

Product type	Circular connectors (device side)
Number of positions	8
No. of cable outlets	1
Shielded	no
Coding	A
Thread type	M12

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Material Housing	PA 6.6
Material Insulating body	PA 6.6
Material Contact	CuZn
Material Contact surface	Au
Material Seal	Viton
Flammability rating according to UL 94	HB

Electrical properties

Rated surge voltage	0.8 kV
Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	30 V
Nominal current I_N	2 A

Connection data

Conductor connection

Connection method	Solder cup
-------------------	------------

SACC-E-M12MS-8CON-M16 PSCUP - Device connector front mounting



1436408

<https://www.phoenixcontact.com/us/products/1436408>

Contact connection type	Pin
Conductor cross-section flexible	... 0.25 mm ²
Tightening torque	1.25 Nm ... 1.5 Nm (Installation-side)

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

Connector

Connection 1

Head design	Pin
Head cable outlet	straight
Head thread type	M12
Coding	A

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation) (male connector/female connector)	-25 °C ... 85 °C (Plug / socket) -40 °C ... 85 °C (without mechanical actuation)
UL Type Rating	Type 4 (indoor use only)

Standards and regulations

Standard designation	M12 circular connector
Standards/specifications	according to IEC 61076-2-101

SACC-E-M12MS-8CON-M16 PSCUP - Device connector front mounting

1436408

<https://www.phoenixcontact.com/us/products/1436408>

Drawings

Schematic diagram



Pin assignment M12 plug, 8-pos., A-coded, view plug side

SACC-E-M12MS-8CON-M16 PSCUP - Device connector front mounting



1436408

<https://www.phoenixcontact.com/us/products/1436408>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1436408>



cULus Recognized

Approval ID: E221474-20070307

SACC-E-M12MS-8CON-M16 PSCUP - Device connector front mounting



1436408

<https://www.phoenixcontact.com/us/products/1436408>

Classifications

ECLASS

ECLASS-13.0	27440109
ECLASS-15.0	27440109

ETIM

ETIM 10.0	EC003569
-----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-E-M12MS-8CON-M16 PSCUP - Device connector front mounting



1436408

<https://www.phoenixcontact.com/us/products/1436408>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	77838f5d-5ed6-44f4-95b3-7b2e354673c1

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com