

SAC-3P- 0,234-PUR/C-1L-Z SO - Sensor/actuator cable



1439159

<https://www.phoenixcontact.com/us/products/1439159>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, PUR halogen-free, black-gray RAL 7021, free cable end, on Valve connector C (8 mm), with 1 LED, Wiring: Z diode

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 1439159 |
| Packing unit | 5 pc |
| Minimum order quantity | 5 pc |
| Note | Made to order (non-returnable) |
| Sales key | BF07 |
| Product key | AF1DEA |
| GTIN | 4046356505208 |
| Weight per piece (including packing) | 63.54 g |
| Weight per piece (excluding packing) | 63.54 g |
| Customs tariff number | 85444290 |
| Country of origin | PL |

SAC-3P- 0,234-PUR/C-1L-Z SO - Sensor/actuator cable



1439159

<https://www.phoenixcontact.com/us/products/1439159>

Technical data

Product properties

| | |
|--------------|--|
| Product type | Sensor/actuator cable with valve connector |
|--------------|--|

Electrical properties

| | |
|-----------------------|---------|
| Nominal voltage U_N | 24 V AC |
| | 24 V DC |

Connector

Connection 1


| | |
|------|----------------|
| Type | free cable end |
|------|----------------|

Connection 2

| | |
|--------------------|--------------------------|
| Type | Valve connector C (8 mm) |
| Protective circuit | Z diode |

Cable/line

PUR halogen-free black [PUR]

| | |
|---------------------------------|--|
| Dimensional drawing |  |
| Cable weight | 23 kg/km |
| UL AWM Style | 20549 |
| Number of positions | 3 |
| Shielded | no |
| Cable type | PUR halogen-free black [PUR] |
| Conductor structure signal line | 42x 0.10 mm |
| AWG signal line | 22 |
| Conductor cross-section | 3x 0.34 mm ² (Signal line) |
| Wire diameter incl. insulation | 1.27 mm ±0.02 mm (Signal line) |
| External cable diameter | 3.85 mm ±0.15 mm |
| Outer sheath, material | PUR |
| External sheath, color | black-gray RAL 7021 |
| Conductor material | Bare Cu litz wires |
| Material wire insulation | PP |
| Single wire, color | brown, blue, black |
| Thickness, insulation | ≥ 0.21 mm (Core insulation) |

SAC-3P- 0,234-PUR/C-1L-Z SO - Sensor/actuator cable



1439159

<https://www.phoenixcontact.com/us/products/1439159>

| | |
|---|--|
| | approx. 0.50 mm (Outer cable sheath) |
| Overall twist | 3 wires, twisted |
| Max. conductor resistance | max. 58 Ω/km (at 20 °C) |
| Insulation resistance | ≥ 100 GΩ*km (at 20 °C) |
| Nominal voltage, cable | ≤ 300 V |
| Test voltage | ≥ 3000 V |
| Smallest bending radius, fixed installation | 19 mm |
| Smallest bending radius, movable installation | 38 mm |
| Dynamic load capacity (bending) | Max. bending cycles: 10000000, Bending radius: 38 mm, Bending radius: 10 x D, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s ² |
| Dynamic load capacity (torsion) | Torsion: ±180 °/m, Torsion cycles: ≥5000000, Torsional frequency: 35 cycles/min. |
| Halogen-free | in accordance with DIN VDE 0472 part 815 |
| Flame resistance | in accordance with UL 758/1581 FT2 DIN EN 60332-2-2 (20 s) |
| Resistance to oil | in accordance with DIN EN 60811-2-1 |
| Other resistance | Highly resistant to acids, alkaline solutions and solvents hydrolysis and microbe resistant partly UV-resistant (in accordance with DIN EN ISO 4892-2-A) |
| Special properties | Flexible cable conduit capable Silicone-free Free of substances which would hinder coating with paint or varnish |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) -25 °C ... 80 °C (Cable, flexible installation) |

SAC-3P- 0,234-PUR/C-1L-Z SO - Sensor/actuator cable



1439159

<https://www.phoenixcontact.com/us/products/1439159>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-15.0 | 27060312 |
| ECLASS-13.0 | 27060312 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 31251501 |
|-------------|----------|

SAC-3P- 0,234-PUR/C-1L-Z SO - Sensor/actuator cable



1439159

<https://www.phoenixcontact.com/us/products/1439159>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com