

# SACB-4/ 4- 5,0PUR SCO P - Distributor box



1452398

<https://www.phoenixcontact.com/us/products/1452398>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Distributor box, application: Standard, connection method: M12 socket Plastic, number of slots: 4, number of positions: 4, coding: A, slot assignment: single, status display: no, Universal; master cable connection: Fixed connection 180°, PUR/PVC, cable length: 5 m, shielding: no

## Your advantages

- Safety in the field, thanks to molded housing and high degree of protection
- Save time, thanks to installation with SPEEDCON fast locking system

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1452398       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF41          |
| Product key                          | AF3CBA        |
| GTIN                                 | 4046356553780 |
| Weight per piece (including packing) | 558.6 g       |
| Weight per piece (excluding packing) | 535.2 g       |
| Customs tariff number                | 85444290      |
| Country of origin                    | DE            |

# SACB-4/ 4- 5,0PUR SCO P - Distributor box



1452398

<https://www.phoenixcontact.com/us/products/1452398>

## Technical data

### Notes

|                     |   |
|---------------------|---|
| Assembly note       | <b>NOTE:</b> Observe the permissible bending radii when routing cables, since the degree of protection may be at risk if the bending forces are too high. Reduce mechanical loads upstream of the connector, e.g., by using cable ties. |
| Note on application | Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories".  |

### Product properties

|                     |                 |
|---------------------|-----------------|
| Product type        | Distributor box |
| Application         | Standard        |
| Number of positions | 4               |
| Number of slots     | 4               |
| Coding              | A               |
| LED                 | no              |

### Electrical properties

|   |          |
|---|----------|
| Nominal voltage $U_N$                   | 120 V AC |
|   | 120 V DC |
| Rated current, total                    | 12 A     |
| Max. current carrying capacity per path | 2 A      |
| Current carrying capacity per slot      | 4 A      |

### Connection data

#### Conductor connection

|  |            |
|--|------------|
| Sensor/actuator connection system                          | M12 socket |
| Tightening torque slot sensor/actuator cable               | 0.4 Nm     |
| Tightening torque of mounting screw for fixing the housing | 0.5 Nm     |

#### Connection assignment

|  |                        |
|--|------------------------|
| Slot/position = Wire color or connection | 1 / 4 (A) = WH         |
|  | 2 / 4 (A) = GN         |
|  | 3 / 4 (A) = YE         |
|  | 4 / 4 (A) = GY         |
|  | 1-4 / 1 (+ 120 V) = BN |
|  | 1-4 / 3 (0 V) = BU     |
|  | 1-4 / 5 (PE) = GNYE    |

### Signaling

|                        |    |
|------------------------|----|
| Status display present | no |
|------------------------|----|

### Dimensions

# SACB-4/ 4- 5,0PUR SCO P - Distributor box



1452398

<https://www.phoenixcontact.com/us/products/1452398>

|                     |        |
|---------------------|--------|
| Dimensional drawing |        |
| Width               | 54 mm  |
| Height              | 23 mm  |
| Length              | 117 mm |

## Material specifications

|  |             |
|--|-------------|
| Material Threaded sleeve               | PBT         |
| Material Housing                       | PBT         |
| Material Molding compound              | PUR         |
| Flammability rating according to UL 94 | V0          |
| Seal material O-ring                   | NBR         |
| Contact material                       | Cu alloy    |
| Contact surface material               | gold-plated |
| Contact carrier material               | PA          |

## Cable/line

|              |     |
|--------------|-----|
| Cable length | 5 m |
|--------------|-----|

### PUR/PVC black [PUR]

|                                     |   |
|-------------------------------------|---|
| Dimensional drawing                 |   |
| Cable weight                        | 77.9 kg/km  |
| UL AWM Style                        | 20549   |
| Number of positions                 | 7   |
| Shielded                            | no  |
| Cable type                          | PUR/PVC black [PUR]   |
| Conductor structure signal line     | 19x 0.15 mm   |
| AWG signal line                     | 22  |
| Conductor structure, voltage supply | 42x 0.15 mm   |
| AWG power supply                    | 18  |
| Conductor cross-section             | 4x 0.34 mm <sup>2</sup> (Signal line)<br>3x 0.75 mm <sup>2</sup> (power line) |

# SACB-4/ 4- 5,0PUR SCO P - Distributor box



1452398

<https://www.phoenixcontact.com/us/products/1452398>

|   |   |
|---|---|
| Wire diameter incl. insulation                | 1.3 mm ±0.1 mm (Signal line)  |
|   | 1.8 mm ±0.1 mm (power line)   |
| External cable diameter                       | 6.90 mm ±0.2 mm   |
| Outer sheath, material                        | PUR   |
| External sheath, color                        | black RAL 9005  |
| Conductor material                            | Bare Cu litz wires  |
| Material wire insulation                      | PVC   |
| Single wire, color                            | brown, blue, green/yellow, white, green, yellow, gray   |
| Inner sheath thickness                        | ≥ 0.15 mm   |
| Thickness, outer sheath                       | ≥ 0.38 mm   |
| Overall twist                                 | Wires twisted in layers   |
| Nominal voltage, cable                        | 300 V   |
| Test voltage                                  | 2000 V  |
| Minimum bending radius, fixed installation    | 7.5 x D   |
| Minimum bending radius, flexible installation | 10 x D  |
| Smallest bending radius, fixed installation   | 52 mm   |
| Smallest bending radius, movable installation | 69 mm   |
| Dynamic load capacity (bending)               | Max. bending cycles: 1500000, Bending radius: 69 mm, Traversing path: 2 m, Traversing rate: 2 m/s |
| Flame resistance                              | DIN EN 50265  |
| Resistance to oil                             | according to VDE 0472 Part 803  |
| Other resistance                              | Highly resistant to acids, alkaline solutions and solvents  |
| Special properties                            | Silicone-free   |
| Ambient temperature (operation)               | -40 °C ... 90 °C (cable, fixed installation)  |
|   | -5 °C ... 80 °C (Cable, flexible installation)  |
|   | 80 °C (in acc. with UL)   |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Degree of protection            | IP65             |
|                                 | IP67             |
| Ambient temperature (operation) | -25 °C ... 80 °C |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |

# SACB-4/ 4- 5,0PUR SCO P - Distributor box



1452398

<https://www.phoenixcontact.com/us/products/1452398>

## Drawings

Dimensional drawing




# SACB-4/ 4- 5,0PUR SCO P - Distributor box

1452398


<https://www.phoenixcontact.com/us/products/1452398>

Schematic diagram



M12 slot, socket, 4-pos.

Circuit diagram



# SACB-4/ 4- 5,0PUR SCO P - Distributor box




1452398

<https://www.phoenixcontact.com/us/products/1452398>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1452398>

|  <b>cUL Recognized</b><br>Approval ID: E118976 |                       |                       |                   |                      |
|---|-----------------------|-----------------------|-------------------|----------------------|
|   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
| keine   |                       |                       |                   |                      |
|   | 120 V                 | -                     | -                 | -                    |

|  <b>UL Recognized</b><br>Approval ID: E118976 |                       |                       |                   |                      |
|--|-----------------------|-----------------------|-------------------|----------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
| keine  |                       |                       |                   |                      |
|  | 120 V                 | -                     | -                 | -                    |

# SACB-4/ 4- 5,0PUR SCO P - Distributor box



1452398

<https://www.phoenixcontact.com/us/products/1452398>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27440108 |
| ECLASS-15.0 | 27440108 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC002585 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31251500 |
|-------------|----------|

# SACB-4/ 4- 5,0PUR SCO P - Distributor box



1452398

<https://www.phoenixcontact.com/us/products/1452398>

## Environmental product compliance

### EU RoHS

|   |                    |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

### China RoHS

|  |  |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|  | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)