

SACB-4/ 8-L-SC SCO P - Distributor box



1452990

<https://www.phoenixcontact.com/us/products/1452990>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Distributor box, application: Standard, connection method: M12 socket Plastic, number of slots: 4, number of positions: 5, coding: A, slot assignment: Double, status display: yes, PNP; master cable connection: Spring-cage connection 180°, shielding: no

Your advantages

- Safety in the field, thanks to molded housing and high degree of protection
- Convenient: increased machine availability thanks to quick and easy diagnostics
- Save space: distributor box with double occupancy for two sensors in one slot
- Save time, thanks to installation with SPEEDCON fast locking system
- Flexible: distributor box with connector hood for on-site assembly

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1452990 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF41 |
| Product key | AF3CBC |
| GTIN | 4046356553612 |
| Weight per piece (including packing) | 157.8 g |
| Weight per piece (excluding packing) | 159 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

SACB-4/ 8-L-SC SCO P - Distributor box



1452990

<https://www.phoenixcontact.com/us/products/1452990>

Technical data

Product properties

| | |
|---------------------|-----------------|
| Product type | Distributor box |
| Application | Standard |
| Number of positions | 5 |
| Number of slots | 4 |
| Coding | A |
| LED | yes |

System properties

Local diagnostics

| | |
|------------------------|----------------|
| Monitored function | Supply voltage |
| Optical representation | Green LED |

Electrical properties

| | |
|---|-------------------------------|
| Max. operating voltage U_{max} | 30 V DC |
| Local diagnostics | Supply voltage Green LED |
| | Status display I/O Yellow LED |
| Nominal voltage U_N | 24 V DC |
| Rated current, total | 12 A |
| Max. current carrying capacity per path | 2 A |
| Current carrying capacity per slot | 4 A |

Connection data

Conductor connection

| | |
|--|---|
| Sensor/actuator connection system | M12 socket |
| Conductor cross-section Flexible signal line | 0.2 mm ² ... 0.5 mm ² |
| Conductor cross-section Flexible power supply | 0.2 mm ² ... 1.5 mm ² |
| Connection cross section AWG Flexible signal line | 24 ... 20 |
| Connection cross section AWG Flexible power supply | 24 ... 16 |
| Stripping length Signal line | 6 mm |
| Stripping length Power supply | 10 mm |
| Stripping length of the sheath | 50 mm (Master cable) |
| Tightening torque, cover screw | 1 Nm |
| Tightening torque slot sensor/actuator cable | 0.4 Nm |
| Tightening torque of mounting screw for fixing the housing | 0.5 Nm |
| Tightening torque, union nut | 2.5 Nm |

Connection assignment

| | |
|--|------------------|
| Slot/position = Wire color or connection | 1 / 4 (A) = WH |
| | 1 / 2 (B) = GYPK |
| | 2 / 4 (A) = GN |

SACB-4/ 8-L-SC SCO P - Distributor box



1452990

<https://www.phoenixcontact.com/us/products/1452990>

| | |
|--|-----------------------|
| | 2 / 2 (B) = RDBU |
| | 3 / 4 (A) = YE |
| | 3 / 2 (B) = WHGN |
| | 4 / 4 (A) = GY |
| | 4 / 2 (B) = BNGN |
| | 1-4 / 1 (+ 24 V) = BN |
| | 1-4 / 3 (0 V) = BU |
| | 1-4 / 5 (PE) = GNYE |

Signaling

| | |
|------------------------|-----|
| Status display present | yes |
|------------------------|-----|

Dimensions

| | |
|---------------------|--|
| Dimensional drawing | <p>The drawing shows two views of the distributor box. The side view (top) shows a height of 42.6 mm, a base width of 15.6 mm, and a total length of 117 mm. The top view (bottom) shows a width of 54 mm, a depth of 73 mm, and a total length of 107 mm. A hole diameter of 4.5 mm is indicated.</p> |
| Width | 54 mm |
| Height | 43 mm |
| Length | 117 mm |

Material specifications

| | |
|--|-------------|
| Material Threaded sleeve | PBT |
| Material Housing | PBT |
| Material Molding compound | PUR |
| Flammability rating according to UL 94 | V0 |
| Seal material O-ring | NBR |
| Contact material | Cu alloy |
| Contact surface material | gold-plated |
| Contact carrier material | PA |

Cable/line

| | |
|-------------------------|------------------------|
| External cable diameter | 7 mm ... 12 mm |
| Connection method | Spring-cage connection |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|------------------|
| Degree of protection | IP65 |
| | IP67 |
| Ambient temperature (operation) | -25 °C ... 80 °C |

SACB-4/ 8-L-SC SCO P - Distributor box



1452990

<https://www.phoenixcontact.com/us/products/1452990>

Standards and regulations

| | |
|--------------------------|-----------------|
| Standard designation | M12 connector |
| Standards/specifications | IEC 61076-2-101 |

SACB-4/ 8-L-SC SCO P - Distributor box



1452990

<https://www.phoenixcontact.com/us/products/1452990>

Drawings

Dimensional drawing



SACB-4/ 8-L-SC SCO P - Distributor box

1452990

<https://www.phoenixcontact.com/us/products/1452990>

Schematic diagram



M12 slot, socket, 5-pos.

Circuit diagram



SACB-4/ 8-L-SC SCO P - Distributor box



1452990

<https://www.phoenixcontact.com/us/products/1452990>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1452990>

|  cUL Recognized Approval ID: E118976 | | | | |
|---|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| keine | | | | |
| | 24 V | - | - | - |

|  UL Recognized Approval ID: E118976 | | | | |
|--|-----------------------|-----------------------|-------------------|----------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| keine | | | | |
| Signal | - | 2 A | - | - |
| | 24 V | 4 A | - | - |

SACB-4/ 8-L-SC SCO P - Distributor box



1452990

<https://www.phoenixcontact.com/us/products/1452990>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27440111 |
| ECLASS-15.0 | 27440111 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC003558 |
|-----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 31251500 |
|-------------|----------|

SACB-4/ 8-L-SC SCO P - Distributor box



1452990

<https://www.phoenixcontact.com/us/products/1452990>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com