

CUC-SI-CM/USBA3.0 - Data interface



1484218

<https://www.phoenixcontact.com/us/products/1484218>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Data interface, design: USB-A, number of positions: 9, 5 Gbps, USB 3.0, material: PA, connection method: Coupling, USB 3.0



Your advantages

- Simple and tool-free mounting thanks to central fastening nut
- Space-saving installation with a standard panel cutout of Ø 22.5 mm
- Quick and easy maintenance work, updates, etc. on closed control cabinets and devices

Commercial data

Item number	1484218
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB18
Product key	ABNKAC
GTIN	4063151922191
Weight per piece (including packing)	25.23 g
Weight per piece (excluding packing)	22.625 g
Customs tariff number	85366990
Country of origin	DE

1484218

<https://www.phoenixcontact.com/us/products/1484218>

Technical data

Product properties

Product type	Data front plate
Number of positions	9
Connection profile	USB-A
Shielded	yes

Insulation characteristics

Overvoltage category	I
Degree of pollution	3

Electrical properties

Rated surge voltage	≥ 500 V AC
Rated current	1 A (Signal contacts at T = 98°C)
	3 A (Power contacts at T = 90°C)
Insulation resistance	≥ 1000 MΩ
Nominal voltage U _N	5 V DC
Nominal current I _N	3 A
Contact resistance per contact pair	≤ 30 mΩ
Transmission medium	Copper
Transmission speed	≤ 5 Gbps
Transmission characteristics (category)	USB 3.0
Power transmission	4,5 W (according to USB-IF)

Connection data

Connection method	Coupling
Tightening torque	... 1 Nm

Interfaces

Signal type/category	USB 3.0 USB 3.0, 5 Gbps
----------------------	-------------------------

Dimensions

Width	29.5 mm
Height	45.1 mm
Length	40.3 mm

Material specifications

Flammability rating according to UL 94 (Housing)	V0
Flammability rating according to UL 94 (Protective cover)	HB
Housing material	PA
Contact material	Copper alloy
Contact surface material	gold-plated
Contact carrier material	Plastic

CUC-SI-CM/USBA3.0 - Data interface



1484218

<https://www.phoenixcontact.com/us/products/1484218>

Material, protective cover	TPE-V
Material for screw connection	PA

Cable/line

Signal type/category	USB 3.0 USB 3.0, 5 Gbps
----------------------	-------------------------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 1500
-----------------------------	--------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65/IP67 (with closed protective cover)
Ambient temperature (operation)	-40 °C ... 70 °C

Mounting

Mounting type	Front mounting
Assembly note	Panel thicknesses: 1 mm ... 5 mm

CUC-SI-CM/USBA3.0 - Data interface



1484218

<https://www.phoenixcontact.com/us/products/1484218>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1484218>



UL Listed

Approval ID: E335024-V5S1



cUL Listed

Approval ID: E335024-V5S1

Classifications

ECLASS

ECLASS-15.0	27440109
ECLASS-13.0	27440209

ETIM

ETIM 10.0	EC003569
-----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

1484218

<https://www.phoenixcontact.com/us/products/1484218>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com